SITE DEVELOPMENT PLAN
STELLA GLEN
LOTS 9-11 & 14-17 (FORMERLY LOTS 1-7) AND P/O LOTS 8, 12 & 13 (F-15-105)

GENERAL NOTES

1. THE PROJECT IS IN CONFORMANCE WITH THE LATEST HOWARD COUNTY STANDARDS UNLESS WAIVERS HAVE BEEN APPROVED.
2. ALL CONSTRUCTION SHALL BE IN ACCORDANCE WITH THE LATEST STANDARDS AND SPECIFICATIONS OF HOWARD COUNTY PLUS MSHA STANDARDS AND SPECIFICATIONS IF APPLICABLE.
3. THE CONTRACTOR IS TO NOTIFY THE FOLLOWING UTILITIES OR AGENCIES AT LEAST FIVE DAYS BEFORE STARTING WORK ON THESE DRAWINGS:

MISS UTILITY	1-800-257-7777
VERIZON TELEPHONE COMPANY:	1-410-954-6281
HOWARD COUNTY BUREAU OF UTILITIES:	410-313-2366
AT&T CABLE LOCATION DIVISION:	1-800-393-3553
B.G.&E. CO. CONTRACTOR SERVICES:	410-850-4620
B.G.&E. CO. UNDERGROUND DAMAGE CONTROL:	410-787-4620
STATE HIGHWAY ADMINISTRATION:	410-531-5533

4. THIS SITE DEVELOPMENT PLAN IS SUBJECT TO THE FOLLOWING DPZ FILES: ECP-13-024 CONT. #24-3108, WP-13-138, SP-13-009, F-14-049, SDP-13-059FC
5. THE EXISTING TOPOGRAPHY IS TAKEN FROM A FIELD RUN TOPOGRAPHIC SURVEY WITH 2-FOOT CONTOUR INTERVALS PREPARED BY ROBERT H. VOGEL ENGINEERING, INC., DATED JUNE 2012.
6. THE PROJECT BOUNDARY SHOWN HEREON IS BASED ON A FIELD RUN MONUMENTED BOUNDARY SURVEY PERFORMED ON OR ABOUT JUNE, 2012 BY ROBERT H. VOGEL ENGINEERING, INC.
7. THE CONTRACTOR SHALL NOTIFY "MISS UTILITY" AT 1-800-257-7777 AT LEAST 48 HOURS PRIOR TO ANY EXCAVATION WORK BEING DONE.
8. THE CONTRACTOR SHALL NOTIFY THE DEPARTMENT OF PUBLIC WORKS/BUREAU OF ENGINEERING/CONSTRUCTION INSPECTION DIVISION AT (410) 313-1880 AT LEAST FIVE (5) WORKING DAYS PRIOR TO THE START OF WORK.
9. ANY DAMAGE TO PUBLIC RIGHT-OF-WAY, PAVING, OR EXISTING UTILITIES WILL BE CORRECTED AT THE CONTRACTOR'S EXPENSE.
10. TO THE BEST OF THE OWNERS KNOWLEDGE, THERE ARE NO CEMETERIES OR GRAVE SITES LOCATED ON THE SUBJECT PROPERTY.
11. STORM WATER MANAGEMENT FOR THIS PROJECT IS PROVIDED BY THE USE OF ALTERNATIVE SURFACES, NON-STRUCTURAL PRACTICES, AND MICRO-SCALE PRACTICES IN ACCORDANCE WITH ENVIRONMENTAL SITE DESIGN CRITERIA. NON-STRUCTURAL PRACTICES INCLUDE ROOFTOP DISCONNECTION (N-1) AND NON-ROOFTOP DISCONNECTION (N-2). MICRO-SCALE PRACTICES INCLUDE RAIN GARDENS (M-7) AND GRASS SWALES (M-8). ALTERNATIVE SURFACES INCLUDE PERVIOUS CONCRETE (A-2). ON-LOT NON-STRUCTURAL AND MICRO-SCALE PRACTICES WILL BE PRIVATELY OWNED AND MAINTAINED BY THE HOMEOWNER. ALTERNATIVE SURFACE, NON-STRUCTURAL, AND MICRO-FACILITIES MANAGING RUNOFF FROM THE USE-IN-COMMON DRIVEWAY WILL BE MAINTAINED BY THE HOMEOWNERS IN ACCORDANCE WITH THE USE-IN-COMMON MAINTENANCE AGREEMENT.
12. THIS SUBDIVISION IS SUBJECT TO SECTION 18.122B OF THE HOWARD COUNTY CODE. PUBLIC WATER AND/OR SEWER SERVICE HAS BEEN GRANTED UNDER THE TERMS AND PROVISIONS THEREOF, EFFECTIVE 4/17/14, ON WHICH DATE DEVELOPER AGREEMENT #F-14-049 WAS FILED AND ACCEPTED.
13. THIS PROJECT HAS AN APPROVED PRELIMINARY EQUIVALENT SKETCH PLAN (SP-13-009) WHICH WAS SIGNED ON 9/25/13 AND IS THEREFORE GRANDFATHERED UNDER THE THE 2/2/04 COMPREHENSIVE ZONING PLAN AND AND THE COMP. LITE ZONING REGULATIONS EFFECTIVE 7/28/06 AND IS SUBJECT TO THE SUBDIVISION AND LAND DEVELOPMENT REGULATIONS IN EFFECT AT THAT TIME. DEVELOPMENT OF THESE LOTS MUST COMPLY WITH SETBACK AND BUFFER REGULATIONS IN EFFECT AT THE TIME OF SP APPROVAL.
14. THE SUBJECT PROPERTY IS ZONED "R-20" IN ACCORDANCE WITH THE 2/2/04 COMPREHENSIVE ZONING PLAN AND THE COMP. LITE ZONING REGULATIONS EFFECTIVE ON 7/28/06.
15. THIS SITE IS NOT LOCATED IN A HISTORIC DISTRICT.
16. THE PROPOSED SUBDIVISION AND RELATED CONSTRUCTION WILL NOT IMPACT EXISTING ENVIRONMENTAL FEATURES AND BUFFERS.
17. EXISTING UTILITIES ARE BASED ON ROAD CONSTRUCTION PLANS, FIELD SURVEYS, PUBLIC WATER AND AND SEWER EXTENSION PLANS AND AVAILABLE RECORD DRAWINGS. APPROXIMATE LOCATION OF EXISTING UTILITIES ARE SHOWN FOR THE CONTRACTORS INFORMATION. CONTRACTOR SHALL LOCATE EXISTING UTILITIES WELL IN ADVANCE OF CONSTRUCTION ACTIVITIES AND TAKE ALL NECESSARY PRECAUTIONS TO PROTECT THE EXISTING UTILITIES AND TO MAINTAIN UNINTERRUPTED SERVICE. ANY DAMAGE INCURRED DUE TO CONTRACTOR'S OPERATION SHALL BE REPAIRED IMMEDIATELY AT THE CONTRACTOR'S EXPENSE.
18. THE COORDINATES SHOWN HEREON ARE BASED UPON THE HOWARD COUNTY GEODETIC CONTROL, WHICH IS BASED UPON THE MARYLAND STATE PLANE COORDINATE SYSTEM. HOWARD COUNTY MONUMENT NOS. 3513 AND 41CC WERE USED FOR THIS PROJECT.
19. NO RARE, THREATENED OR ENDANGERED SPECIES WERE OBSERVED ON THE PROPERTY.
20. THERE IS NO 100-YR FLOODPLAIN WITHIN THE LIMITS OF THIS SITE.
21. SEDIMENT AND EROSION CONTROL WILL BE PROVIDED FOR THIS SITE.
22. THE WETLANDS DELINEATION STUDY FOR THIS PROJECT WAS PREPARED BY ECO-SCIENCE PROFESSIONALS, INC., DATED SEPTEMBER 12, 2012, AND APPROVED ON JUNE 20, 2013. THERE ARE NO PROPOSED DISTURBANCES TO THE WETLANDS OR ASSOCIATED BUFFERS.
23. FOREST STAND DELINEATION PLAN WAS PREPARED BY ECO-SCIENCE PROFESSIONALS, INC., DATED SEPTEMBER 12, 2012. AND APPROVED IN CONJUNCTION WITH SP-13-009.
24. A TOTAL OF 7 LOTS ARE PROPOSED UNDER THIS PLAN.
25. NO CLEARING, GRADING, REMOVAL OF VEGETATIVE COVER OR TREES, PAVING OR NEW STRUCTURES SHALL BE PERMITTED WITHIN THE LIMITS OF THE WETLANDS, STREAMS OR THEIR REQUIRED BUFFERS. FLOODPLAIN AND FOREST CONSERVATION EASEMENT AREAS.
26. WETLANDS AND THEIR BUFFERS WILL NOT BE IMPACTED BY THE CONSTRUCTION OF THE SITE.
27. A NOISE WALL IS REQUIRED FOR THIS SITE AND WILL BE CONSTRUCTED IN ACCORDANCE WITH SHA PROJECT HO-3175170 WHICH IS FUNDED FOR CONSTRUCTION.
28. THERE ARE NO SPECIMEN TREES LOCATED ON THIS SITE.
29. FOREST CONSERVATION OBLIGATIONS IN ACCORDANCE WITH SECTION 16.1202 OF THE HOWARD COUNTY CODE AND FOREST CONSERVATION MANUAL SHALL BE PROVIDED BY THE PLACEMENT OF 2.76 AC. (2:1 RATIO) OF RETENTION INTO AN OFFSITE FOREST CONSERVATION BANK IDENTIFIED AS DENSITY SOLUTIONS, APPROVED UNDER F-14-049, WHICH IS SUFFICIENT TO MEET THE 1.28 AC. OF REQUIRED REFORESTATION AND 0.10 AC. OF REQUIRED AFFORESTATION.
30. UTILIZE HOWARD COUNTY STANDARD DETAIL NO. R-6.02 FOR THE USE-IN-COMMON DRIVEWAY ENTRANCE AT SHAKER DRIVE.
31. DRIVEWAY(S) SHALL BE PROVIDED PRIOR TO ISSUANCE OF A USE AND OCCUPANCY PERMIT FOR ANY NEW DWELLINGS TO INSURE SAFE ACCESS FOR FIRE AND EMERGENCY VEHICLES PER THE FOLLOWING MINIMUM REQUIREMENTS:
    a) WIDTH - 12 FEET (16 FEET SERVING MORE THAN ONE RESIDENCE).
    b) SURFACE - 6 INCHES OF COMPACTED CRUSHER RUN BASE WITH TAR AND CLIP COATING. (1-1/2" MIN).
    c) GEOMETRY - MAXIMUM 15% GRADE, MAXIMUM 10% GRADE CHANGE AND MINIMUM 45-FOOT TURNING RADIUS.
    d) STRUCTURE (CULVERTS/BRIDGES) - CAPABLE OF SUPPORTING 25 GROSS TONS (H25 LOADING).
    e) DRAINAGE ELEMENTS - CAPABLE OF SAFELY PASSING 100-YEAR FLOOD WITH NO MORE THAN 1 FOOT DEPTH OVER DRIVEWAY SURFACE.
    f) STRUCTURE CLEARANCES - MINIMUM 12 FEET.
    g) MAINTENANCE - SUFFICIENT TO INSURE ALL WEATHER USE.
32. THERE IS AN EXISTING HOUSE TO REMAIN WHICH SHALL BE LOCATED ON LOT 11. THE EXISTING DRIVEWAY TO LOT 11 SHALL BE REMOVED PRIOR TO RECORDATION OF THE FINAL PLAT AND ACCESS TO LOT 11 SHALL BE PROVIDED BY THE U/C SHARED DRIVEWAY FOR LOTS 9-11, 14-17 AND F-15-105 LOTS 12 & 13. ANY NEW ADDITIONS OR NEW CONSTRUCTION TO THE EXISTING HOUSE SHALL CONFORM TO SETBACKS AS SHOWN ON THE FINAL PLAT FOR THIS SUBDIVISION.
33. SHAKER DRIVE IS NOT A SCENIC ROAD.
34. LOTS 9-11, 14-17 AND F-15-105 LOTS 12 & 13 WILL UTILIZE A USE-IN-COMMON DRIVEWAY. A USE-IN-COMMON MAINTENANCE AGREEMENT FOR THE SHARED DRIVEWAY HAS BEEN RECORDED SIMULTANEOUSLY WITH THE FINAL PLAT.
35. THIS PLAN HAS BEEN PREPARED IN ACCORDANCE WITH THE PROVISIONS OF SECTION 16.124 OF THE HOWARD COUNTY CODE AND THE LANDSCAPE MANUAL. A FINANCIAL SURETY IN THE AMOUNT OF $8,850.00 FOR THE REQUIRED 17 SHADE TREES AND 45 SHRUBS SHALL BE POSTED WITH F-14-049.
36. DEED REFERENCE: L. 8293/F. 433
37. THE TRAFFIC STUDY FOR THIS PROJECT WAS PREPARED BY THE TRAFFIC GROUP, INC., DATED JULY 12, 2012, AND WAS APPROVED ON JUNE 20, 2013.
38. THIS PROPERTY IS LOCATED WITHIN THE METROPOLITAN DISTRICT.
39. FLAG AND PIPESTEM LOTS, REFUSE COLLECTION, SNOW REMOVAL AND ROAD MAINTENANCE FOR LOTS 9-11, 14-17 AND F-15-105 LOTS 12 & 13 ARE PROVIDED TO THE JUNCTION OF THE FLAG OR PIPESTEM AND ROAD RIGHT-OF-WAY LINE AND NOT ONTO THE PIPESTEM LOT DRIVEWAY.
40. A PRIVATE RANGE OF ADDRESS SIGN ASSEMBLY SHALL BE FABRICATED BY HOWARD COUNTY BUREAU OF HIGHWAYS FOR THE DRIVEWAY ACCESS POINT ONTO SHAKER DRIVE AT THE DEVELOPERS/OWNERS EXPENSE. CONTACT HOWARD COUNTY TRAFFIC DIVISION AT 410-313-5752 FOR DETAILS AND COST ESTIMATES.
41. CERTIFIED TEST PITS HAVE BEEN PROVIDED TO VERIFY THAT GROUNDWATER AND ROCK ARE NOT PRESENT AT RAIN GARDEN LOCATIONS.
42. A DESIGN MANUAL WAIVER TO ALLOW SEVEN USERS ON A USE-IN-COMMON SHARED DRIVEWAY WAS APPROVED BY THE DEVELOPMENT ENGINEERING DIVISION ON MARCH 19, 2013.
43. REFERENCE WP-13-138, DENIED ON MARCH 25, 2013, TO ALLOW FOREST CONSERVATION EASEMENTS ON LOTS LESS THAN 10 ACRES.
44. BG&E HAS REVIEWED AND APPROVED PROPOSED TRASH PAD SCREENING AND PERIMETER TREE PLANTINGS.
45. A FEE-IN-LIEU OF OPEN SPACE FOR THE SIX LOTS HAS BEEN PAID IN CONJUNCTION WITH THE FINAL PLAT ($9,000.00).
46. ALL EXISTING WELLS AND SEPTIC SYSTEM COMPONENTS MUST BE PROPERLY ABANDONED AND NOTIFICATION OF SUCH SENT TO THE HEALTH DEPARTMENT PRIOR TO HEALTH OFFICER SIGNATURE OF THE FINAL RECORD PLAT.
47. TRAFFIC CONTROL DEVICES, MARKINGS AND SIGNING SHALL BE IN ACCORDANCE WITH THE LATEST EDITION OF THE MANUAL OF UNIFORM TRAFFIC CONTROL DEVICES (MUTCD). ALL STREET AND REGULATORY SIGNS SHALL BE IN PLACE PRIOR TO THE PLACEMENT OF ANY ASPHALT.
48. SIGN POSTS USED FOR TRAFFIC CONTROL SIGNS INSTALLED IN THE COUNTY RIGHT-OF-WAY SHALL BE MOUNTED ON A 2" GALVANIZED STEEL, PERFORATED, SQUARE TUBE POST (14 GAUGE) INSERTED INTO A 2-1/2" GALVANIZED STEEL, PERFORATED, SQUARE TUBE SLEEVE (12 GAUGE) 3' LONG. A GALVANIZED STEEL POLE CAP SHALL BE MOUNTED ON TOP OF EACH POST.
49. IN ACCORDANCE WITH SECTION 128 OF THE HOWARD COUNTY ZONING REGULATIONS, BAY WINDOWS, CHIMINEYS, OR EXTERIOR STAIRWAYS NOT MORE THAN 16 FT. IN WIDTH MAY PROJECT NOT MORE THAN 4 FEET INTO ANY SETBACKS. PORCHES, OR DECKS OPEN OR ENCLOSED, MAY PROJECT NOT MORE THAN 10 FEET INTO ANY FRONT OR REAR YARD SETBACK.
50. THE DECK SETBACK ENCROACHMENT FOR LOT 17 IS ALLOWED UNDER SECTION 16.120 (b)(4)(iii)(c) OF THE HOWARD COUNTY SUBDIVISION AND LAND DEVELOPMENT REGULATIONS TO ALLOW THE DECK TO PROJECT UP TO 10 FEET BEYOND THE BUILDING ENVELOPE.

SHEET INDEX

DESCRIPTION	SHEET NO.
COVER SHEET	1 OF 8
SITE LAYOUT PLAN	2 OF 8
SOILS MAP & PHASE 1 GRADING, EROSION AND SEDIMENT CONTROL PLAN	3 OF 8
SOILS MAP & PHASE 2 GRADING, EROSION AND SEDIMENT CONTROL PLAN	4 OF 8
GRADING, EROSION AND SEDIMENT CONTROL NOTES AND DETAILS	5 OF 8
DRAINAGE AREA MAP AND SWM PLAN	6 OF 8
LANDSCAPE AND FOREST CONSERVATION PLAN	7 OF 8
MICRO-BIORETENTION PLANTING DETAILS	8 OF 8

APPROVED: HOWARD COUNTY DEPARTMENT OF PLANNING AND ZONING

CHIEF, DEVELOPMENT ENGINEERING DIVISION	DATE 5.13.16
CHIEF, DIVISION OF LAND DEVELOPMENT	DATE 5-17-16
DIRECTOR	DATE 5-17-16

SITE DATA

LOCATION: TAX MAP 36, BLOCK 19
PARCEL: 57, 58 & 417
10580 SHAKER DRIVE, COLUMBIA, MARYLAND
DEED REFERENCE: L. 8293 / F. 433
6TH ELECTION DISTRICT
PRESENT ZONING: R-20
TOTAL PROJECT AREA: 160,511 SF / 3.68 AC.
LIMIT OF DISTURBANCE: 2.64 AC. (TOTAL)
PROPOSED USE OF SITE: RESIDENTIAL (SFD)
NUMBER OF RESIDENTIAL LOTS: 7 LOTS
AREA OF RESIDENTIAL LOTS: 3.68 AC.
AREA OF PROPOSED ROADS AND OPEN SPACE DEDICATION: 0.00 AC.
OPEN SPACE REQUIRED: 0.00 AC.
OPEN SPACE PROVIDED: 0.00 AC.
IMPERVIOUS AREA: 0.79 AC.
AREA OF STREAM/BUFFER: 0.00 AC.
AREA OF WETLANDS/BUFFER: 0.23 AC.
AREA OF STEEP SLOPES (25% OR GREATER): 0.01 AC.
AREA OF FLOOD PLAIN: 0.00 AC.
NET PROJECT AREA: 3.44 AC.
AREA OF EXISTING FOREST COVER: 0.64 AC.
AREA OF ERODIBLE SOILS: 1.13 AC.

SWM PRACTICE CHART

ESD PRACTICES BY LOT

LOT #	ADDRESS	ESD PRACTICE
#9	10505 JUSTICE PLACE	DISCONNECT ROOFTOP RUNOFF (N-1), RAIN GARDEN (M-7), AND SHARED RESPONSIBILITY FOR USE-IN-COMMON DRIVEWAY PRACTICES.
#10	10509 JUSTICE PLACE	DISCONNECT ROOFTOP RUNOFF (N-1), RAIN GARDEN (M-7), AND SHARED RESPONSIBILITY FOR USE-IN-COMMON DRIVEWAY PRACTICES.
#11	10513 JUSTICE PLACE	SHARED RESPONSIBILITY FOR USE-IN-COMMON DRIVEWAY PRACTICES.
#14	10516 JUSTICE PLACE	DISCONNECT ROOFTOP RUNOFF (N-1), RAIN GARDEN (M-7), DISCONNECT NON-ROOFTOP RUNOFF (N-2), AND SHARED RESPONSIBILITY FOR USE-IN-COMMON DRIVEWAY PRACTICES.
#15	10512 JUSTICE PLACE	DISCONNECT ROOFTOP RUNOFF (N-1), RAIN GARDEN (M-7), DISCONNECT NON-ROOFTOP RUNOFF (N-2), AND SHARED RESPONSIBILITY FOR USE-IN-COMMON DRIVEWAY PRACTICES.
#16	10508 JUSTICE PLACE	DISCONNECT ROOFTOP RUNOFF (N-1), RAIN GARDEN (M-7), DISCONNECT NON-ROOFTOP RUNOFF (N-2), AND SHARED RESPONSIBILITY FOR USE-IN-COMMON DRIVEWAY PRACTICES.
#17	10504 JUSTICE PLACE	DISCONNECT ROOFTOP RUNOFF (N-1), RAIN GARDEN (M-7), AND SHARED RESPONSIBILITY FOR USE-IN-COMMON DRIVEWAY PRACTICES.
UIC DRIVEWAY	-	PERVIOUS CONCRETE (A-2), GRASSED SWALE (M-8), AND DISCONNECT NON-ROOFTOP RUNOFF (N-2)

COLUMBIA PIKE MD ROUTE 29
PROPOSED 8' NOISE BARRIER PROPOSED 16' NOISE BARRIER
SHAKER DR.
LOCATED ON PLAT 17948
N 10°04'31" W 224.34'
JUSTICE PLACE
LOT 9 20,820 SF
EXISTING 12' PRIVATE R/W L.8293 F.433
CHRIST MEMORIAL PRESBYTERIAN, INC. TAX MAP 36 PARCEL: 54 L. 5256 F. 650 1.81 AC. USE: RESIDENTIAL ZONED: R-20
CHRIST MEMORIAL PRESBYTERIAN, INC. LOT 12
CHARLES W. EASTER TAX MAP 36 PARCEL 453 L. 1420 F. 453 1.47 AC. USE: RESIDENTIAL ZONED: R-20
EX. HOUSE TO REMAIN
S60°40'40"E 583.78'
LOT 10 21,115 SF (TOTAL)
EX. 15' PRIVATE R/W
E 1349950
N 555600
E 1350650
N 555600
EX. PUBLIC SEWER & UTILITY EASEMENT PLAT MDR 9987
CHARLES L. ANN KYUNG-SOOK ANN TAX MAP 36 PARCEL: 252 L. 13659 F. 213 31,373 SF USE: RESIDENTIAL ZONED: R-20
EX. 30' PUBLIC SEWER, WATER, & UTILITY EASEMENT (PLAT 22836)
VARIABLE WIDTH PRIVATE USE-IN-COMMON ACCESS EASEMENT FOR LOTS 9-17
EX. VARIABLE WIDTH PRIVATE USE-IN-COMMON ACCESS EASEMENT FOR LOTS 1-7 (PLAT 22836) (TO BE ABANDONED)
TO BE REMOVED BY SHA PROJECT HO-3175170
DAVID N. ELLIOTT JASON D. ELLIOTT TAX 36 PARCEL: 414 PLAT: 22836 L. 25427 F. 329 LOT: 1 23,005 SF USE: RESIDENTIAL ZONED: R-20
N 02°11'55" E 132.04'
EX. SHED
EX. HOUSE
EX. GARAGE
EX. DECK
EX. WELL
EX. SEPTIC
EX. SHED
EX. GAZEBO
EX. WELL
EX. SEPTIC
EX. SHED
EX. GAZEBO
EX. SHED
EX. HOUSE
EX. GARAGE
EX. SHED
EX. HOUSE
EX. GARAGE
EX. SHED
EX. HOUSE
EX. GARAGE


COLUMBIA PIKE
MD ROUTE 29
PRINCIPAL ARTERIAL
NORTH BOUND
RW=VARIES
SHC DAT 51717
SHAKER DR.
LOCAL ROAD
40' RIGHT OF WAY
L.5897 F.88
DRIVEWAY APRON DETAIL R-6.02
REMOVE AND REPLACE CONCRETE CURB & GUTTER AND SIDEWALK AS REQUIRED
℄ SHAKER DR. STA. 10+00=
℄ USE IN COMMON STA. 0+00
N 555,629.97 / E 1,350,043.65
16' UIC ACCESS
10' PLANT BUFFER
APPROX. LOCATION OF MSHA NOISE WALL AND 65 DBL LINE
E 1349900
N 555600
PROP. 4'x10' TRASH PAD
PROP. UIC ADDRESS SIGN
LOT 9
20,820 SF
N53°06'08"E 150.84'
S50°40'40"E
EXISTING 12' PRIVATE R/W L.8293 F.433
CHRIST MEMORIAL PRESBYTERIAN, INC.
TM: 36 PARCEL: 54
L. 5258 / F. 655
1.91 AC.
USE: RESIDENTIAL
ZONED: R-20
CHRIST MEMORIAL PRESBYTERIAN, INC.
LOT 12
Maryland State Grid Meridian
CHARLES W. EASTER
TM: 36 PARCEL: 463
L. 1420 / F. 463
1.47 AC.
USE: RESIDENTIAL ZONED: R-20
EX. HOUSE TO REMAIN
P/O LOT 8
(F-15-105)
LOT 10
20,567 SF
21,141SF (TOTAL)
S50°40'40"E 565.26'
N51°04'31"W 224.34'
JUSTICE PLACE
EX. 30' PUBLIC SEWER, WATER, & UTILITY EASEMENT (PLAT 22836)
VARIABLE WIDTH PRIVATE USE-IN-COMMON ACCESS EASEMENT FOR LOTS 9-17
EX. VARIABLE WIDTH PRIVATE USE-IN-COMMON ACCESS EASEMENT FOR LOTS 1-7 (PLAT 22836) (TO BE ABANDONED)
EX. PUBLIC SEWER & UTILITY EASMENT PLAT MDR 9987
CHARLES I. AHN
KYONG-SOOK AHN
TM: 36 PARCEL: 252
L. 13459 / F. 213
31,973 SF
USE: RESIDENTIAL
ZONED: R-20
DAVID N. ELLIOTT
JASMIN D. ELLIOTT
TM: 36 PARCEL: 56
PLAT: 17848
L. 2314 / F. 432
LOT: 1
20,005 SF
USE: RESIDENTIAL
ZONED: R-20
THOMAS E. SMITH
EVA MAY B. SMITH
TM: 36 PARCEL: 56
PLAT: 17848
L. 9925 / F. 136
LOT: 2
21,453 SF
USE: RESIDENTIAL
ZONED: R-20
DAVID N. ELLIOTT
JASMIN D. ELLIOTT
TM: 36 PARCEL: 56
PLAT: 17848
L. 2314 / F. 432
LOT: 3
21,453 SF
USE: RESIDENTIAL
ZONED: R-20
RANDOLPH J. OSTLIE
CAROLYN C. OSTLIE
TM: 36 PARCEL: 233
ARROWHEAD
L. 637 / F. 620
LOT: 4
31,493 SF
USE: RESIDENTIAL
ZONED: R-20
CAROLYN B. EDWARDS
BLANCHE D. PETERS J/T
TM: 36 PARCEL: 233
ARROWHEAD
L. 10163 / F. 692
LOT: 5
20,081 SF
USE: RESIDENTIAL
ZONED: R-20
JERRY A. TESTON & WF
TM: 36 PARCEL: 233
ARROWHEAD
L. 665 / F. 402
LOT: 6
20,037 SF
USE: RESIDENTIAL
ZONED: R-20
CHRISTOPHER R. LONG
THERESA E. LONG T/E
TM: 36 PARCEL: 233
ARROWHEAD
L. 3548 / F. 593
LOT: 7
20,037 SF
USE: RESIDENTIAL
ZONED: R-20
RANDALL S. PHILLIPS
HANNELORE T. PHILLIPS T/E
TM: 36 PARCEL: 233
ARROWHEAD
L. 7898 / F. 570
LOT: 8
32,190 SF
USE: RESIDENTIAL
ZONED: R-20
LOT 11
20,375 SF
21,490 SF TOTAL
P/O LOT 12
2,053 SF
(F-15-105)
LOT 17
20,143 SF
20,817SF TOTAL
LOT 16
20,065 SF
21,148 SF TOTAL
P/O LOT 13
2,073 SF
(F-15-105)
LOT 15
20,940 SF
22,297 SF TOTAL
LOT 14
20,443 SF
22,272 SF TOTAL
N28°46'50"E 132.04'
N28°11'35"E 108.76'
N45°41'29"W 164.62'
S53°53'51"W
N20°16'52"W 235.18'
S55°47'52"W
N54°11'55"W 12.42'
N54°11'55"E 132.86'
N28°46'50"E 265.66'
E 1350650
N 555200
E 1349900
N 555200
PROP. PERVIOUS CONCRETE (A-2) 360 SF
EX. HOUSE
EX. GARAGE
EX. SHED
EX. POOL DECK
EX. WELL HO-998114 (TO BE ABANDONED)
EX. WELL HO-943306
EX. WETLANDS
EX. FOREST
EX. LAWN
EX. TREES
EX. FENCE
EX. WOOD FENCE
EX. METAL FENCE
EX. UTILITY POLE
EX. SEWER C/O
EX. WV
EX. SMH
EX. DRIVEWAY
EX. 8" PVC
EX. 6" SVC
EX. 18" RCP
EX. 24" RCP
EX. 30" RCP
EX. 36" RCP
EX. 42" RCP
EX. 48" RCP
EX. 54" RCP
EX. 60" RCP
EX. 72" RCP
EX. 8" PWL
EX. 12" PWL
EX. 24" PWL
EX. 8" PSL (DIP)
EX. 24" PSL (DIP)
EX. 30" PSL (DIP)
EX. 36" PSL (DIP)
EX. 42" PSL (DIP)
EX. 48" PSL (DIP)
EX. 54" PSL (DIP)
EX. 60" PSL (DIP)
EX. 72" PSL (DIP)
EX. 8" PSL (CONT. 24"x76")
EX. 24" PSL (CONT. 24"x76")
EX. 30" PSL (CONT. 24"x76")
EX. 36" PSL (CONT. 24"x76")
EX. 42" PSL (CONT. 24"x76")
EX. 48" PSL (CONT. 24"x76")
EX. 54" PSL (CONT. 24"x76")
EX. 60" PSL (CONT. 24"x76")
EX. 72" PSL (CONT. 24"x76")
EX. 8" PWL (CONT. 24"x76")
EX. 12" PWL (CONT. 24"x76")
EX. 24" PWL (CONT. 24"x76")
165 LF RIP-RAP SCOUR PROTECTION
PROP. 12" DI
PROP. 6" SVC
PROP. 8" PVC

NOTES:

1. ROAD AND CULVERT CONSTRUCTION AND THEIR CORRESPONDING EROSION AND SEDIMENT CONTROLS TO BE PERMITTED AND CONSTRCUTED UNDER F-14-049. THIS PLAN FOR HOUSE CONSTRUCTION ONLY.
2. SEE SHEETS 4 AND 5 OF 8 FOR ADDITIONAL DETAILS.
3. STOCKPILES EXCEEDING 15' IN HEIGHT MUST BE BENCHED.
4. EITHER PERMANENT OR TEMPORARY STABILIZATION IS TO BE PERFORMED AT THE DIRECTION OF THE SEDIMENT CONTROL INSPECTOR OR AT THE MINIMUM INTERVALS REQUIRED BY THE 2011MARYLAND STANDARDS AND SPECIFICATIONS FOR SOIL EROSION & SEDIMENT CONTROL, WHICHEVER IS MORE RESTRICTIVE.
5. ANY SEDIMENT CONTROLS THAT ARE DAMAGED OR INTERRUPTED BY CONTRUCTION SHALL BE REPAIRED IMMEDIATELY.

LEGEND:

- PROPERTY LINE
- RIGHT-OF-WAY LINE
- INTERIOR LOT LINE
- ADJACENT PROPERTY LINE
- EXISTING CURB AND GUTTER
- EXISTING EDGE OF PAVING
- EXISTING WETLANDS
- EXISTING WETLAND BUFFER
- PROP. VARIABLE WIDTH PRIVATE USE-IN-COMMON ACCESS EASEMENT FOR LOTS 1-7
- PROP. 30' PUBLIC SEWER, WATER, & UTILITY EASEMENT
- PROP. 20 PRIVATE DRAINAGE & UTILITY EASEMENT
- EX. PUBLIC SEWER & UTILITY EASEMENT PLAT MDR 9987
- EXISTING UTILITY POLE
- EXISTING LIGHT POLE
- EXISTING MAILBOX
- EXISTING SIGN
- EXISTING SANITARY MANHOLE
- EXISTING SANITARY LINE
- EXISTING CLEANOUT
- EXISTING FIRE HYDRANT
- EXISTING WATER LINE
- EXISTING TREELINE
- EXISTING TREES
- EXISTING FENCE
- PROPOSED STORMDRAIN
- PROPOSED SIDEWALK
- PROPOSED TREELINE
- EXISTING 10' CONTOUR
- EXISTING 2' CONTOUR
- SOILS
- PROPOSED 10' CONTOUR
- PROPOSED 2' CONTOUR
- PROPOSED SPOT ELEVATION
- EXISTING STEEP SLOPES (>25%)
- EXISTING MODERATE SLOPES (15-25%)
- PROPOSED SUPER SILT FENCE
- PROPOSED SILT FENCE
- PROPOSED CURB INLET PROTECTION
- PROPOSED LIMIT OF DISTURBANCE
- PROPOSED EROSION CONTROL MATTING
- PROPOSED SOD SLOPE/ CHANNEL PROTECTION
- PROPOSED STABILIZED CONSTRUCTION ENTRANCE
- PROPOSED TEST PIT
- PERVIOUS CONCRETE (A-2)
- ROOFTOP DISCONNECT
- PROPOSED RAIN GARDEN (M-7)
- PROPOSED GRASS SWALE (M-8)

NOTE:

ROAD AND CULVERT CONSTRUCTION AND THEIR CORRESPONDING EROSION AND SEDIMENT CONTROLS TO BE PERMITTED AND CONSTRCUTED UNDER F-14-049. THIS PLAN FOR HOUSE CONSTRUCTION ONLY.

OWNER

MARY THERESE PFAU
3675 PARK AVE., SUITE 301
ELLICOTT CITY, MD 21043
(410) 480-0023

DEVELOPER

TRINITY QUALITY HOMES, INC.
3675 PARK AVE., SUITE 301
ELLICOTT CITY, MD 21043
(410) 480-0023

NO.	REVISION	DATE
1	REVISE LOT LINES, BRL'S EASEMENTS AND HOUSES PER NEW LAYOUT	09/03/15

REVISED SITE DEVELOPMENT PLAN
GRADING, EROSION, AND SEDIMENT CONTROL PLAN & SOIL MAP
STELLA GLEN
LOTS 9-11 & 14-17 (FORMERLY LOTS 1-7) AND P/O LOTS 8, 12 & 13 (F-15-105)

RESIDENTIAL: SINGLE FAMILY DETACHED

TAX MAP: 36 GRID: 19 — ZONED: R-20
6TH ELECTION DISTRICT
DPZ REF'S: ECP-13-024, CONT.#24-3108, WP-13-138, SP-13-009 & F-14-049, F-15-105. — PARCELS: 57, 58 & 417; L.8293 / F.433
HOWARD COUNTY, MARYLAND

ROBERT H. VOGEL ENGINEERING, INC.
ENGINEERS • SURVEYORS • PLANNERS
8407 MAIN STREET
ELLICOTT CITY, MD 21043
TEL: 410.461.7666
FAX: 410.461.8961

STATE OF MARYLAND — ROBERT HARRIS VOGEL — NO.16193 — REGISTERED PROFESSIONAL ENGINEER — 5/10/16
ROBERT H. VOGEL, PE No.16193

DESIGN BY:	RHV
DRAWN BY:	JMR/GAH
CHECKED BY:	RHV
DATE:	DECEMBER 2015
SCALE:	AS SHOWN
W.O. NO.:	12-23

PROFESSIONAL CERTIFICATE

I HEREBY CERTIFY THAT THESE DOCUMENTS WERE PREPARED OR APPROVED BY ME, AND THAT I AM A DULY LICENSED PROFESSIONAL ENGINEER UNDER THE LAWS OF THE STATE OF MARYLAND, LICENSE NO. 16193 EXPIRATION DATE: 09-27-2016

SHEET 3 OF 8

BY THE ENGINEER:

"I CERTIFY THAT THIS PLAN FOR EROSION AND SEDIMENT CONTROL REPRESENTS A PRACTICAL AND WORKABLE PLAN BASED ON MY PERSONAL KNOWLEDGE OF THE SITE CONDITIONS, AND THAT IT WAS PREPARED IN ACCORDANCE WITH THE REQUIREMENTS OF THE HOWARD SOIL CONSERVATION DISTRICT."

SIGNATURE OF ENGINEER — DATE 5/10/16

APPROVED: HOWARD COUNTY DEPARTMENT OF PLANNING AND ZONING

CHIEF, DEVELOPMENT ENGINEERING DIVISION — DATE 5-13-16
CHIEF, DIVISION OF LAND DEVELOPMENT — DATE 5-17-16
DIRECTOR — DATE 5-17-16

BY THE DEVELOPER:

"I/WE CERTIFY THAT ALL DEVELOPEMENT AND CONSTRUCTION WILL BE DONE ACCORDING TO THIS PLAN FOR SEDIMENT AND EROSION CONTROL, AND THAT ALL RESPONSIBLE PERSONNEL INVOLVED IN THE CONSTRUCTION PROJECT WILL HAVE A CERTIFICATE OF ATTENDANCE AT A DEPARTMENT OF THE ENVIRONMENT APPROVED TRAINING PROGRAM FOR THE CONTROL OF SEDIMENT AND EROSION BEFORE BEGINNING THE PROJECT. I ALSO AUTHORIZE PERIODIC ON-SITE INSPECTION BY THE HOWARD SOIL CONSERVATION DISTRICT."

SIGNATURE OF DEVELOPER — DATE 5/10/16

THIS DEVELOPMENT PLAN IS APPROVED FOR SOIL EROSION AND SEDIMENT CONTROL BY THE HOWARD SOIL CONSERVATION DISTRICT.

HOWARD S.C.D. — DATE 5/13/16

NOTE: SEE SHEETS 4 AND 5 OF 8 FOR ADDITIONAL NOTES AND DETAILS.

NOTE: BASEMENT SEWER SERVICE FOR LOTS 16 & 17 PROVIDED BY EJECTOR PUMPS.

NOTE: STOCKPILING WILL BE PERMITTED ON EACH LOT ONLY.

GRADING, EROSION & SEDIMENT CONTROL PLAN

SCALE: 1"=30'

SCALE 1"=30'
15' 0' 30'

SOILS LEGEND

SYMBOL	NAME / DESCRIPTION	GROUP	K-FACTOR
GfB	GLADSTONE-URBAN LAND COMPLEX, 0 TO 8 PERCENT SLOPES	B	0.20
GuB	GLENVILLE-URBAN LAND-UDORTHENTS COMPLEX, 0 TO 8 PERCENT SLOPES	C	0.37
UoF	UDORTHENTS, HIGHWAY, 0 TO 65 PERCENT SLOPES	–	–

SDP-14-070

K:\Projects\12-23\BIDRelease\BIDPRES\REDLINES\3_RE_GRADING\SEDIMENT.dwg, 5/5/2016 8:39:51 AM

DETAIL C-1 EARTH DIKE

STANDARD SYMBOL



DIKE TYPE	A	B
a = DIKE HEIGHT	18 IN MIN.	30 IN MIN.
b = DIKE WIDTH	24 IN MIN.	36 IN MIN.
c = FLOW WIDTH	4 FT MIN.	6 FT MIN.
d = FLOW DEPTH	12 IN MIN.	24 IN MIN.

FLOW CHANNEL STABILIZATION

A-1	SEED WITH STRAW MULCH AND TACK, (NOT ALLOWED FOR CLEAR WATER DIVERSION.)
A-2/B-1	SOD WITH SOIL STABILIZATION MATTING OR LINE WITH SOD.
A-3/B-3	6 TO 7 INCH STONE OR EQUIVALENT RECYCLED CONCRETE, PRESSED INTO SOIL A MINIMUM OF 3 INCHES AND FLUSH WITH GROUND.

CONSTRUCTION SPECIFICATIONS

1. REMOVE AND DISPOSE OF ALL TREES, BRUSH, STUMPS, OBSTRUCTIONS, AND OTHER OBJECTIONABLE MATERIAL TO BE NOT TO INTERFERE WITH PROPER FUNCTION OF EARTHWORK.
2. EXCAVATE OR SHAPE EARTH SIDE TO LINE, GRADE, AND CROSS SECTION AS SPECIFIED. BANK PROJECTIONS OR OTHER IRREGULARITIES ARE NOT ALLOWED.
3. COMPACT FILL.
4. CONSTRUCT FLOW CHANNEL ON AN UNINTERRUPTED, CONTINUOUS GRADE, ADJUSTING THE LOCATION DUE TO FIELD CONDITIONS AS NECESSARY TO MAINTAIN POSITIVE DRAINAGE.
5. PROVIDE OUTLET PROTECTION AS REQUIRED ON APPROVED PLAN.
6. STABILIZE EARTH SIDE WITHIN THREE DAYS OF INSTALLATION. STABILIZE FLOW CHANNEL FOR CLEAR WATER DIVERSION WITHIN 24 HOURS OF INSTALLATION.
7. MAINTAIN LINE, GRADE, AND CROSS SECTION. REMOVE ACCUMULATED SEDIMENT AND DEBRIS, AND REPAIR DAMAGE TO DIKE AS NECESSARY. REMOVE AND DISPOSE OF ACCUMULATED SEDIMENT CONTINUOUSLY NEXT DOWNSLOPE FROM DIKE AS NECESSARY IN ACCORDANCE WITH SECTION B-4 "ESSENTIAL VEGETATIVE ESTABLISHMENT".
8. UPON REMOVAL OF EARTH DIKE, GRADE AREA FLUSH WITH EXISTING GROUND. WITHIN 24 HOURS OF REMOVAL STABILIZE DISTURBED AREA WITH TOPSOIL, SEED, AND MULCH, OR AS SPECIFIED ON APPROVED PLAN.

MARYLAND STANDARDS AND SPECIFICATIONS FOR SOIL EROSION AND SEDIMENT CONTROL

U.S. DEPARTMENT OF AGRICULTURE, NATURAL RESOURCES CONSERVATION SERVICE | 2011 | MARYLAND DEPARTMENT OF ENVIRONMENT, WATER MANAGEMENT ADMINISTRATION

C-3

B-6 STANDARDS AND SPECIFICATIONS FOR STOCKPILE AREA

Definition

A mound or pile of soil protected by appropriately designed erosion and sediment control measures.

Purpose

To provide a designated location for the temporary storage of soil that controls the potential for erosion, sedimentation, and changes to drainage patterns.

Conditions Where Practice Applies

Stockpile areas are utilized when it is necessary to salvage and store soil for later use.

Criteria

1. The stockpile location and all related sediment control practices must be clearly indicated on the erosion and sediment control plan.
2. The footprint of the stockpile must be sized to accommodate the anticipated volume of material and based on a side slope ratio no steeper than 2:1. Benching must be provided in accordance with Section B-3 Land Grading.
3. Runoff from the stockpile area must drain to a suitable sediment control practice.
4. Accent the stockpile area from the upgrade side.
5. Clear water runoff into the stockpile area must be minimized by use of a diversion device such as an earth dike, temporary swale or diversion fence. Provisions must be made for discharging concentrated flow in a non-erosive manner.
6. Where runoff concentrates along the toe of the stockpile fill, an appropriate erosion/sediment control practice must be used to intercept the discharge.
7. Stockpiles must be stabilized in accordance with the 3/7 day stabilization requirements as well as Standard B-4-1 Incremental Stabilization and Standard B-4-4 Temporary Stabilization.
8. If the stockpile is located on an impervious surface, a liner should be provided below the stockpile to facilitate cleanup. Stockpiles containing contaminated material must be covered with impermeable sheeting.

Maintenance

The stockpile area must continuously meet the requirements for Adequate Vegetative Establishment in accordance with Section B-4 Vegetative Stabilization. Side slopes must be maintained at no steeper than a 2:1 ratio. The stockpile area must be kept free of erosion. If the vertical height of a stockpile exceeds 30 feet for 2:1 slopes, 35 feet for 2.5:1 slopes, or 40 feet for 4:1 slopes, benching must be provided in accordance with Section B-3 Land Grading.

B-43

DETAIL D-4-1-C ROCK OUTLET PROTECTION III

STANDARD SYMBOL — RORIII

DESIGNATE TO ANY UNCONFINED AREA ON FLAT VOLS.



CLASS	DIAMETER (D)
I	16 IN
II	32 IN
III	48 IN

CONSTRUCTION SPECIFICATIONS

1. RIPRAP AND STONE MUST CONFORM TO THE SPECIFIED CLASS.
2. USE NONWOVEN GEOTEXTILE AS SPECIFIED IN SECTION H-1 MATERIALS. AND PROTECT FROM PUNCTURING, CUTTING, OR TEARING. REPAIR ANY DAMAGE EITHER THAN AN OCCASIONAL SMALL HOLE BY PLACING ANOTHER PIECE OF GEOTEXTILE OVER THE DAMAGED PART OR COMPLETELY REPLACING IT WITH UNDAMAGED MATERIAL. MINIMUM OVERLAP OF ONE FOOT OVERLAP FOR ALL REPAIRS AND FOR JOINING TWO PIECES OF GEOTEXTILE TOGETHER.
3. PREPARE THE SUBGRADE FOR GEOTEXTILE OR STONE FILTER TO THE LINES AND GRADES SHOWN ON THE PLANS. REMOVE ALL VEGETATION, ROOTS, AND OTHER OBJECTIONABLE MATERIAL. PREPARE ZONE FILL REQUIRED IN THE SUBGRADE TO A DENSITY OF APPROXIMATELY THAT OF THE SURROUNDING UNDISTURBED MATERIAL.
4. EXTEND GEOTEXTILE AT LEAST 6 INCHES BEYOND EDGES OF RIPRAP AND EMBED AT LEAST 4 INCHES AT SIDES OF RIPRAP.
5. CONSTRUCT OUTLET TO FULL COURSE THICKNESS IN ONE OPERATION AND IN SUCH A MANNER AS TO AVOID DISPLACEMENT OF UNDERLYING MATERIALS. PLACE STONE FOR RIPRAP OUTLET IN A MANNER TO PREVENT SEGREGATION OF THE VARIOUS SIZES OF STONE. REMOVE AND RELAY ANY STONE DISPLACED DURING CONSTRUCTION SO THAT THE FINISHED RIPRAP IS IN A UNIFORM CONDITION WITH THE ADJACENT UNDISTURBED AREA. REMOVE ANY SPALL AND FINES FROM THE FINISHED RIPRAP AND BROADCAST THE MATERIAL OVER THE FILTERED AREA.
6. WASTE 100 EXCESS FILL TO CONSTRUCT THE SPECIFIED END OF THE RIPRAP, SO THAT THE WIDTH IS TWO TIMES THE DIAMETER OF THE OUTLET PIPE, AND EXTEND THE STONE UNDER THE OUTLET BY A MINIMUM OF 18 INCHES.
7. CONSTRUCT RIPRAP WITH ONE SLOPE ALONG ITS LENGTH AND WITHOUT DEPRESSIONS. PLACE STONE SO THAT IT BLENDS WITH THE EXISTING GROUND.
8. MAINTAIN LINE, GRADE, AND CROSS SECTION. KEEP OUTLET FREE OF EROSION. REMOVE ACCUMULATED SEDIMENT AND DEBRIS. AFTER HIGH FLOWS INSPECT FOR SCOUR AND REPAIR ANY DISTURBED RIPRAP. MAKE NECESSARY REPAIRS IMMEDIATELY.

MARYLAND STANDARDS AND SPECIFICATIONS FOR SOIL EROSION AND SEDIMENT CONTROL

U.S. DEPARTMENT OF AGRICULTURE, NATURAL RESOURCES CONSERVATION SERVICE | 2011 | MARYLAND DEPARTMENT OF ENVIRONMENT, WATER MANAGEMENT ADMINISTRATION

D-22

DETAIL B-4-6-C PERMANENT SOIL STABILIZATION MATTING CHANNEL APPLICATION

STANDARD SYMBOL — PSSMC



CONSTRUCTION SPECIFICATIONS

1. INSTALL MATTING THAT HAS A DESIGN VALUE FOR SHEAR STRESS EQUAL TO OR GREATER THAN THE SHEAR STRESS EXPECTED FOR THE CHANNEL.
2. USE PERMANENT SOIL STABILIZATION MATTING MADE OF OPEN WEAVE SYNTHETIC NON-DEGRADABLE FIBERS OR ELEMENTS OF UNIFORM THICKNESS AND DISTRIBUTED MACHINE PRODUCED MESH. ONLY MATTING USED IN THE WET MUST BE NON-DEGRADABLE AND NON-TOXIC TO VEGETATION AND SEED GERMINATION AND NON-HARMFUL TO THE SKIN IF HANDLED BY CONSTRUCTION PERSONNEL. MATTING MUST BE CAPABLE OF ABSORBING RAINDROP IMPACT, HOLDING SEED IN CONTACT WITH THE SOIL, AND ALLOWING GERMINATING SEEDLINGS TO GROW UNIMPEDED THROUGH THE MATTING, TO PREVENT EROSION OF THE MATERIAL TO THE SURFACE OF THE MATTING, TO PREVENT SEPARATION OF THE NET FROM THE PARENT MATERIAL.
3. SECURE MATTING USING STEEL STAPLES OR WOOD STAKES. STAPLES MUST BE 3/4" OR 1" SHAPED STEEL WIRE HAVING A MINIMUM GAUGE OF NO. 11 AND NO. 8 RESPECTIVELY. STAPLES MUST BE U-SHAPED WITH 6 TO 8 INCH LEGS AND A 1 TO 2 INCH CROWN. USE WOOD STAKES AT LEAST 1 INCH BY 2 INCH SQUARE BY 6 INCHES LONG. WOOD STAKES MUST BE SOUND AND FREE OF KNOTS. USE EQUIVALENT HARDWOOD, 12 TO 24 INCHES IN LENGTH, 1/2 INCH IN CROSS SECTION, AND WEDGE SHAPE AT THE BOTTOM.
4. PERFORM FINAL GRADING, TOPSOIL APPLICATION, SEEDBED PREPARATION, AND PERMANENT SEEDING BEFORE INSTALLING MATTING. APPLY SEED AT THE RATE SPECIFIED ON THE APPROVED PLAN. APPLY LIME AND FERTILIZER UNLESS USE OF NORMALLY ESTABLISHED IS SPECIFIED ON THE APPROVED EROSION AND SEDIMENT CONTROL PLAN.
5. ANCHOR MATTING IN DIRECTION OF WATER FLOW, CENTERING THE FIRST ROLL ON THE CHANNEL CENTER LINE. WORK FROM CENTER OF CHANNEL OUTWARDS WHEN PLACING ROLLS. LAY MATTING SMOOTHLY AND FIRMLY UPON THE SOIL. DO NOT STRETCH. ADJUST TO FIT CHANNEL CONTOUR.
6. OVERLAP OR ABUT EDGES OF MATTING ROLLS FOR ADJACENT LANES. PLACE MATTING ROLL END OVERLAPS BY 6 INCHES MINIMUM. STAGGER ROLL END OVERLAPS. PLACE UPSTREAM ROLL ON TOP OF THE NEXT DOWNSTREAM MAT.
7. ADJ ACENT ROLLS MUST BE TIGHTLY BUTTED TOGETHER WITH EDGES OF ADJACENT ROLLS OVERLAPPED 4 INCHES TO 6 INCHES. SECURE THE OVERLAPPED EDGES AT 12 INCH INTERVALS.
8. STAPLE/STRIKE MAT IN A STAGGERED PATTERN ON 4 FOOT (MAXIMUM) CENTERS THROUGHOUT AND 2 FOOT (MAXIMUM) CENTERS ALONG SEAMS, JOINTS, AND ROLL ENDS.
9. IF SPECIFIED BY THE DESIGNER OR MANUFACTURER AND DEPENDING ON THE TYPE OF MAT BEING INSTALLED, BURY THE UPSTREAM END OF THE MATTING IN A TRENCH 6 INCHES DEEP AND 6 INCHES WIDE. BACKFILL AND COMPACT THE TRENCH AFTER INSTALLING MATTING AND STAPLING. DO NOT BURY DOWNSTREAM MAT.
10. ESTABLISH AND MAINTAIN VEGETATION SO THAT REQUIREMENTS FOR ADEQUATE VEGETATIVE ESTABLISHMENT ARE CONTINUALLY MET IN ACCORDANCE WITH SECTION B-4 VEGETATIVE STABILIZATION.

MARYLAND STANDARDS AND SPECIFICATIONS FOR SOIL EROSION AND SEDIMENT CONTROL

U.S. DEPARTMENT OF AGRICULTURE, NATURAL RESOURCES CONSERVATION SERVICE | 2011 | MARYLAND DEPARTMENT OF ENVIRONMENT, WATER MANAGEMENT ADMINISTRATION

D-10

DETAIL E-3 SUPER SILT FENCE

STANDARD SYMBOL — SSF



CONSTRUCTION SPECIFICATIONS

1. INSTALL 2% INCH DIAMETER GALVANIZED STEEL POSTS OF 0.065 INCH WALL THICKNESS AND SIX FOOT LENGTH SPACED NO FURTHER THAN 10 FEET APART. DRIVE THE POSTS A MINIMUM OF 36 INCHES INTO THE GROUND.
2. FASTEN 6 GAUGE OR HEAVIER GALVANIZED CHAIN LINK FENCE (2% INCH MAXIMUM OPENING) 42 INCHES IN HEIGHT SECURELY TO THE FENCE POSTS WITH WIRE TIES OR HOG RINGS.
3. FASTEN WOVEN SILT FILM GEOTEXTILE AS SPECIFIED IN SECTION H-1 MATERIALS SECURELY TO THE UPSLOPE SIDE OF CHAIN LINK FENCE WITH TIES SPACED EVERY 24 INCHES AT THE TOP AND MID SECTION. EMBED GEOTEXTILE AND CHAIN LINK FENCE A MINIMUM OF 8 INCHES INTO THE GROUND.
4. WHERE ENDS OF THE GEOTEXTILE COME TOGETHER, THE ENDS SHALL BE OVERLAPPED BY 6 INCHES, FOLDED, AND STAPLED TO PREVENT SEDIMENT BY PASS.
5. EXTEND BOTH ENDS OF THE SUPER SILT FENCE A MINIMUM OF FIVE HORIZONTAL FEET UPSLOPE AT 45 DEGREES TO THE MAIN FENCE ALIGNMENT TO PREVENT RUNOFF FROM GOING AROUND THE ENDS OF THE SILT FENCE.
6. REMOVE ACCUMULATED SEDIMENT AND DEBRIS WHEN BULGES DEVELOP IN SILT FENCE OR WHEN SEDIMENT REACHES 6 INCHES IN HEIGHT. REPLACE GEOTEXTILE IF TORN, IF UNDERMINING OCCURS, REINSTALL FENCE.

MARYLAND STANDARDS AND SPECIFICATIONS FOR SOIL EROSION AND SEDIMENT CONTROL

U.S. DEPARTMENT OF AGRICULTURE, NATURAL RESOURCES CONSERVATION SERVICE | 2011 | MARYLAND DEPARTMENT OF ENVIRONMENT, WATER MANAGEMENT ADMINISTRATION

E-7

DETAIL C-9 DIVERSION FENCE

STANDARD SYMBOL — DF

MAXIMUM DRAINAGE AREA = 2 ACRES



CONSTRUCTION SPECIFICATIONS

1. USE 42 INCH HIGH, 9 GAUGE OR THICKER CHAIN LINK FENCING (2% INCH MAXIMUM OPENING).
2. USE 2% INCH DIAMETER GALVANIZED STEEL POSTS OF 0.095 INCH WALL THICKNESS AND SIX FOOT LENGTH SPACED NO FURTHER THAN 10 FEET APART. DRIVE THE POSTS A MINIMUM OF 36 INCHES INTO THE GROUND.
3. FASTEN CHAIN LINK FENCE SECURELY TO THE FENCE POSTS WITH WIRE TIES.
4. SECURE 10 MIL OR THICKER UV RESISTANT, IMPERMEABLE SHEETING TO CHAIN LINK FENCE WITH TIES SPACED EVERY 24 INCHES AT TOP, MID SECTION, AND BOTTOM OF FENCE.
5. EXTEND SHEETING A MINIMUM OF 4 FEET ALONG FLOW SURFACE AND EMBED END A MINIMUM OF 8 INCHES INTO GROUND. SOIL STABILIZATION MATTING MAY BE USED IN LIEU OF IMPERMEABLE SHEETING ALONG FLOW SURFACE.
6. WHEN TWO SECTIONS OF SHEETING ADJOIN EACH OTHER, OVERLAP BY 6 INCHES AND FOLD WITH SEAM FACING DOWNGRADE.
7. KEEP FLOW SURFACE ALONG DIVERSION FENCE AND POINT OF DISCHARGE FREE OF EROSION. REMOVE ACCUMULATED SEDIMENT AND DEBRIS. MAINTAIN POSITIVE DRAINAGE. REPLACE IMPERMEABLE SHEETING IF TORN, IF UNDERMINING OCCURS, REINSTALL FENCE.

MARYLAND STANDARDS AND SPECIFICATIONS FOR SOIL EROSION AND SEDIMENT CONTROL

U.S. DEPARTMENT OF AGRICULTURE, NATURAL RESOURCES CONSERVATION SERVICE | 2011 | MARYLAND DEPARTMENT OF ENVIRONMENT, WATER MANAGEMENT ADMINISTRATION

E-8

TEMPORARY TRAFFIC CONTROL TYPICAL APPLICATION



SPECIFICATION	DIVISION/ CODE ITEM
104	

APPROVED

Maryland Department of Transportation
STATE HIGHWAY ADMINISTRATION
STANDARDS FOR HIGHWAYS AND INCIDENTAL STRUCTURES
SHOULDER WORK/2-LANE, 2-WAY EQUAL/LESS THAN 40 MPH

STANDARD NO. MD 104.02-02

TEMPORARY TRAFFIC CONTROL TYPICAL APPLICATION



SPECIFICATION	DIVISION/ CODE ITEM
104	

APPROVED

Maryland Department of Transportation
STATE HIGHWAY ADMINISTRATION
STANDARDS FOR HIGHWAYS AND INCIDENTAL STRUCTURES
FLAGGING OPERATIONS-LANE, 2-WAY EQUAL/LESS THAN 40 MPH

STANDARD NO. MD 104.03-10

DETAIL B-1 STABILIZED CONSTRUCTION ENTRANCE

STANDARD SYMBOL — SCE

50 FT MIN.



CONSTRUCTION SPECIFICATIONS

1. PLACE STABILIZED CONSTRUCTION ENTRANCE IN ACCORDANCE WITH THE APPROVED PLAN. VEHICLES MUST TRAVEL OVER THE ENTIRE LENGTH OF THE SCE. USE MINIMUM LENGTH OF 50 FEET FOR FIELD OR SINGLE RESIDENCE LOT. USE MINIMUM WIDTH OF 10 FEET. FLARE SCE 10 FEET MINIMUM AT THE EXISTING ROAD TO PROVIDE A TURNING RADIUS.
2. PIPE ALL SURFACE WATER FLOWING TO OR DIVERTED TOWARD THE SCE UNDER THE ENTRANCE. MAINTAIN GRADE TO ENSURE SURFACE WATER DOES NOT FLOW ONTO THE PUBLIC ROAD. IF MOUNTABLE BERM WITH 5:1 SLOPES WILL NOT PREVENT FLOW FROM ENTERING PUBLIC ROAD, INSTALL PIPE AS SPECIFIED ON APPROVED PLAN. WHEN THE SCE IS LOCATED AT A HIGH POINT AND HAS NO DRAINAGE TO CONVEY, A PIPE IS NOT NECESSARY. A MOUNTABLE BERM IS REQUIRED WHEN SCE IS NOT CONSTRUCTED AT A HIGH POINT.
3. PREPARE SUBGRADE AND PLACE NONWOVEN GEOTEXTILE, AS SPECIFIED IN SECTION H-1 MATERIALS.
4. PLACE CRUSHED AGGREGATE (2 TO 3 INCHES IN SIZE) OR EQUIVALENT RECYCLED CONCRETE (WITHOUT REBAR) AT LEAST 6 INCHES DEEP OVER THE LENGTH AND WIDTH OF THE SCE.
5. MAINTAIN ENTRANCE IN A CONDITION THAT MINIMIZES TRACKING OF SEDIMENT. AND STONE OR MAKE OTHER REPAIRS AS CONDITIONS DEMAND TO MAINTAIN CLEAR SURFACES FOR TRAVEL AND FOR SPECIFIED DIMENSIONS. IMMEDIATELY REMOVE STONE AND/OR SEDIMENT SPILLED, DROPPED, OR WASHED ONTO PUBLIC ROADS. SWEEP PAVEMENT AS NECESSARY. DO NOT WASH SEDIMENT INTO STORM DRAINS. DO NOT WASH SEDIMENT ONTO PAVEMENT IF DO NOT ACCEPTABLE UNLESS WASH WATER IS DIRECTED TO AN APPROVED SEDIMENT CONTROL PRACTICE.

MARYLAND STANDARDS AND SPECIFICATIONS FOR SOIL EROSION AND SEDIMENT CONTROL

U.S. DEPARTMENT OF AGRICULTURE, NATURAL RESOURCES CONSERVATION SERVICE | 2011 | MARYLAND DEPARTMENT OF ENVIRONMENT, WATER MANAGEMENT ADMINISTRATION

B-2

DETAIL E-1 SILT FENCE

STANDARD SYMBOL — SF



1 OF 2

MARYLAND STANDARDS AND SPECIFICATIONS FOR SOIL EROSION AND SEDIMENT CONTROL

U.S. DEPARTMENT OF AGRICULTURE, NATURAL RESOURCES CONSERVATION SERVICE | 2011 | MARYLAND DEPARTMENT OF ENVIRONMENT, WATER MANAGEMENT ADMINISTRATION

E-3

DETAIL E-1 SILT FENCE

STANDARD SYMBOL — SF

CONSTRUCTION SPECIFICATIONS

1. USE WOOD POSTS (1% x 1% x 4+ INCH DIAMETER) SQUARE CUT OF SOUND QUALITY HARDWOOD, AS AN ALTERNATIVE TO WOODEN POST USE STANDARD "T" OR "L" SECTION STEEL POSTS WEIGHING NOT LESS THAN 1 POUND PER LINEAR FOOT.
2. USE 36 INCH MINIMUM POSTS DRIVEN 16 INCH MINIMUM INTO GROUND NO MORE THAN 8 FEET APART.
3. USE WOVEN SILT FILM GEOTEXTILE AS SPECIFIED IN SECTION H-1 MATERIALS AND FASTEN GEOTEXTILE SECURELY TO UPSLOPE SIDE OF FENCE POSTS WITH WIRE TIES OR STAPLES AT TOP AND MID-SECTION.
4. PROVIDE MANUFACTURER CERTIFICATION TO THE AUTHORIZED REPRESENTATIVE OF THE ADMINISTRATION HAVING JURISDICTION UPON REQUEST STATING THAT THE GEOTEXTILE USED MEETS THE REQUIREMENTS OF AASHTO M288 CLASS C.
5. EMBED GEOTEXTILE A MINIMUM OF 8 INCHES VERTICALLY INTO THE GROUND. BACKFILL AND COMPACT THE SOIL ON BOTH SIDES OF GEOTEXTILE.
6. WEDGE TWO SECTIONS OF GEOTEXTILE ADJOIN: OVERLAP, TWIST, AND STAPLE TO POST IN ACCORDANCE WITH THIS DETAIL.
7. EXTEND BOTH ENDS OF THE SILT FENCE A MINIMUM OF FIVE HORIZONTAL FEET UPSLOPE AT 45 DEGREES TO THE MAIN FENCE ALIGNMENT TO PREVENT RUNOFF FROM GOING AROUND THE ENDS OF THE SILT FENCE.
8. REMOVE ACCUMULATED SEDIMENT AND DEBRIS WHEN BULGES DEVELOP IN SILT FENCE OR WHEN SEDIMENT REACHES 6 INCHES IN HEIGHT. REPLACE GEOTEXTILE IF TORN, IF UNDERMINING OCCURS, REINSTALL FENCE.

2 OF 2

MARYLAND STANDARDS AND SPECIFICATIONS FOR SOIL EROSION AND SEDIMENT CONTROL

U.S. DEPARTMENT OF AGRICULTURE, NATURAL RESOURCES CONSERVATION SERVICE | 2011 | MARYLAND DEPARTMENT OF ENVIRONMENT, WATER MANAGEMENT ADMINISTRATION

E-3

DETAIL E-3 CURB INLET PROTECTION

STANDARD SYMBOL — CIP

MAXIMUM DRAINAGE AREA = ¼ ACRE



CONSTRUCTION SPECIFICATIONS

1. USE NOMINAL 2 INCH x 4 INCH LUMBER
2. USE NONWOVEN GEOTEXTILE AS SPECIFIED IN SECTION H-1 MATERIALS.
3. MAX. THE 2x4 MEM TER 2 INCH LONG VERTICAL SPACERS (MAXIMUM 6 FEET APART).
4. ATTACH A CONTINUOUS PIECE OF ¼ INCH GALVANIZED HARDWARE CLOTH, WITH A MINIMUM WIDTH OF 33 INCHES AND A MINIMUM LENGTH OF 4 FEET LONGER THAN THE THROAT OPENING, TO THE 2x4 MEM. EXTENDING IT 2 FEET BEYOND THROAT ON EACH SIDE.
5. PLACE A CONTINUOUS PIECE OF NONWOVEN GEOTEXTILE OF THE SAME DIMENSIONS AS THE HARDWARE CLOTH OVER THE HARDWARE CLOTH AND SECURELY ATTACH TO 2x4 MEM.
6. PLACE THE ASSEMBLY AGAINST THE INLET THROAT AND NAIL TO 2x4 ANCHORS (MINIMUM 2 FEET LENGTH). EXTEND THE ANCHORS ACROSS THE INLET TOP AND HOLD IN PLACE BY SANDBAGS OR OTHER APPROVED ANCHORING METHOD.
7. INSTALL END SPACERS A MINIMUM OF 1 FOOT BEYOND THE ENDS OF THE THROAT OPENING.
8. FORM THE HARDWARE CLOTH AND GEOTEXTILE TO THE CONCRETE GUTTER AND FACE OF CURB TO SPAN THE INLET OPENING. COVER THE HARDWARE CLOTH AND GEOTEXTILE WITH CLEAN ¾ TO 1½ INCH STONE OR EQUIVALENT RECYCLED CONCRETE.
9. AT NON-SUMP LOCATIONS, INSTALL A TEMPORARY SANDBAG OR ASPHALT BERM TO PREVENT INLET BYPASS.
10. STORM DRAIN INLET PROTECTION REQUIRES FREQUENT MAINTENANCE. REMOVE ACCUMULATED SEDIMENT AFTER EACH RAIN EVENT TO MAINTAIN PROPER FUNCTION OF THE INLET. INSPECT SEDIMENT BARRIER AND REPAIR AS NEEDED. IF STONE BECOMES COMPLETELY CLOGGED WITH SEDIMENT, REMOVE AND REPLACE IT. REMOVE ACCUMULATED SEDIMENT AND CLEAN OR REPLACE HARDWARE CLOTH AND STONE.

MARYLAND STANDARDS AND SPECIFICATIONS FOR SOIL EROSION AND SEDIMENT CONTROL

U.S. DEPARTMENT OF AGRICULTURE, NATURAL RESOURCES CONSERVATION SERVICE | 2011 | MARYLAND DEPARTMENT OF ENVIRONMENT, WATER MANAGEMENT ADMINISTRATION

E-27

DETAIL E-4 CLEAR WATER PIPE THROUGH SILT FENCE OR SUPER SILT FENCE

STANDARD SYMBOL — CWP



CONSTRUCTION SPECIFICATIONS

1. INSTALL SILT FENCE OR SUPER SILT FENCE IN ACCORDANCE WITH DETAIL E-1 OR DETAIL E-3.
2. AT THE PIPE LOCATION, CUT AND PULL BACK THE WOVEN SILT FILM GEOTEXTILE AND CHAIN LINK FENCING. SECURE GEOTEXTILE TO PIPE WITH GASKET. INSTALL ADDITIONAL STAKES OR POSTS IF NECESSARY TO ACCOMMODATE THE INSTALLATION OF THE BAFFLE BOARD.
3. EXTENSION ¾ INCH PLYWOOD BAFFLE A MINIMUM OF 8 INCHES AND SECURE TO THE UPSLOPE SIDE OF THE FENCE STAKES OR POSTS. BAFFLE SHOULD BE AT LEAST THE HEIGHT OF THE FENCE.
4. PLACE ¾ TO 1½ INCH STONE OR EQUIVALENT RECYCLED CONCRETE BEHIND THE PLYWOOD BAFFLE ON NONWOVEN GEOTEXTILE AND EXTEND 12 INCH MIN. ALONG THE PIPE AND TO A HEIGHT OF 4 INCHES ABOVE THE TOP OF PIPE.
5. USE NONWOVEN AND WOVEN SILT FILM GEOTEXTILES AS SPECIFIED IN SECTION H-1 MATERIALS.
6. REMOVE ACCUMULATED SEDIMENT AND DEBRIS WHEN SEDIMENT REACHES

HOWARD SOIL CONSERVATION DISTRICT
STANDARD SEDIMENT CONTROL NOTES

1. A MINIMUM OF 48 HOURS NOTICE MUST BE GIVEN TO THE HOWARD COUNTY DEPARTMENT OF INSPECTIONS, LICENSES AND PERMITS, SEDIMENT CONTROL DIVISION PRIOR TO THE START OF ANY CONSTRUCTION, (313-1855).

2. ALL VEGETATIVE AND STRUCTURAL PRACTICES ARE TO BE INSTALLED ACCORDING TO THE PROVISIONS OF THIS PLAN AND ARE TO BE IN CONFORMANCE WITH THE MOST CURRENT "MARYLAND STANDARDS AND SPECIFICATIONS FOR SOIL EROSION AND SEDIMENT CONTROL", AND REVISIONS THERETO.

3. FOLLOWING INITIAL SOIL DISTURBANCE OR RE-DISTURBANCE, PERMANENT OR TEMPORARY STABILIZATION SHALL BE COMPLETED WITHIN: A) 3 CALENDAR DAYS FOR ALL PERIMETER SEDIMENT CONTROL STRUCTURES, DIKES, PERIMETER SLOPES AND ALL SLOPES GREATER THAN 3:1, B) 7 DAYS AS TO ALL OTHER DISTURBED OR GRADED AREAS ON THE PROJECT SITE.

4. ALL DISTURBED AREAS MUST BE STABILIZED WITHIN THE TIME PERIOD SPECIFIED ABOVE IN ACCORDANCE WITH THE 2011 MARYLAND STANDARDS AND SPECIFICATIONS FOR SOIL EROSION AND SEDIMENT CONTROL FOR PERMANENT SEEDING (SEC. B-4-5), TEMPORARY SEEDING (SEC. B-4-4) AND MULCHING (SEC. B-4-3). TEMPORARY STABILIZATION WITH MULCH ALONE CAN ONLY BE DONE WHEN RECOMMENDED SEEDING DATES DO NOT ALLOW FOR PROPER GERMINATION AND ESTABLISHMENT OF GRASSES.

5. ALL SEDIMENT CONTROL STRUCTURES ARE TO REMAIN IN PLACE AND ARE TO BE MAINTAINED IN OPERATIVE CONDITION UNTIL PERMISSION FOR THEIR REMOVAL HAS BEEN OBTAINED FROM THE HOWARD COUNTY SEDIMENT CONTROL INSPECTOR.

6. SITE ANALYSIS:

TOTAL SITE AREA	3.68 ACRES
AREA DISTURBED	2.64 ACRES
AREA TO BE ROOFED OR PAVED	0.86 ACRES
AREA TO BE VEGETATIVELY STABILIZED	1.78 ACRES
TOTAL CUT	3,300 CU. YDS*
TOTAL FILL	3,300 CU. YDS*
OFFSITE WASTE/BORROW LOCATION	**

*ESTIMATE ONLY. CONTRACTOR SHALL VERIFY QUANTITIES TO HIS OWN SATISFACTION.
**TO BE DETERMINED BY CONTRACTOR, WITH PRE-APPROVAL OF THE SEDIMENT CONTROL INSPECTOR, WITH AN APPROVED AND ACTIVE GRADING PERMIT.

7. ANY SEDIMENT CONTROL PRACTICE THAT IS DISTURBED BY GRADING ACTIVITY FOR PLACEMENT OF UTILITIES MUST BE REPAIRED ON THE SAME DAY OF DISTURBANCE.

8. ADDITIONAL SEDIMENT CONTROL MUST BE PROVIDED, IF DEEMED NECESSARY BY THE HOWARD COUNTY SEDIMENT CONTROL INSPECTOR.

9. ON ALL SITES WITH DISTURBED AREAS IN EXCESS OF 2 ACRES, APPROVAL OF THE INSPECTION AGENCY SHALL BE REQUESTED UPON COMPLETION OF INSTALLATION OF PERIMETER EROSION AND SEDIMENT CONTROLS, BUT BEFORE PROCEEDING WITH ANY OTHER EARTH DISTURBANCE OR GRADING. OTHER BUILDING OR GRADING INSPECTION APPROVALS MAY NOT BE AUTHORIZED UNTIL THIS INITIAL APPROVAL BY THE INSPECTION AGENCY IS MADE.

10. TRENCHES FOR THE CONSTRUCTION OF UTILITIES IS LIMITED TO THREE PIPE LENGTHS OR THAT WHICH CAN BE BACK FILLED AND STABILIZED BY THE END OF EACH WORKDAY, WHICHEVER IS SHORTER.

11. ANY CHANGES OR REVISIONS TO THE SEQUENCE OF CONSTRUCTION MUST BE REVIEWED AND APPROVED BY THE PLAN APPROVAL AUTHORITY PRIOR TO PROCEEDING WITH CONSTRUCTION.

12. A PROJECT IS TO BE SEQUENCED SO THAT GRADING ACTIVITIES BEGIN ON ONE GRADING UNIT (MAXIMUM ACREAGE OF 20 AC. PER GRADING UNIT) AT A TIME. WORK MAY PROCEED TO A SUBSEQUENT GRADING UNIT WHEN AT LEAST 50 PERCENT OF THE DISTURBED AREA IN THE PRECEDING GRADING UNIT HAS BEEN STABILIZED AND APPROVED BY THE ENFORCEMENT AUTHORITY. UNLESS OTHERWISE SPECIFIED AND APPROVED BY THE APPROVAL AUTHORITY, NO MORE THAN 30 ACRES CUMULATIVELY MAY BE DISTURBED AT A GIVEN TIME.

B-4-4 STANDARDS AND SPECIFICATIONS FOR TEMPORARY STABILIZATION

DEFINITION
TO STABILIZE DISTURBED SOILS WITH VEGETATION FOR UP TO 6 MONTHS.

PURPOSE
TO USE FAST GROWING VEGETATION THAT PROVIDES COVER ON DISTURBED SOILS.

CONDITIONS WHERE PRACTICE APPLIES
EXPOSED SOILS WHERE GROUND COVER IS NEEDED FOR A PERIOD OF 6 MONTHS OR LESS. FOR LONGER DURATION OF TIME, PERMANENT STABILIZATION PRACTICES ARE REQUIRED.

CRITERIA

1. SELECT ONE OR MORE OF THE SPECIES OR SEED MIXTURES LISTED IN TABLE 8.1 FOR THE APPROPRIATE PLANT HARDINESS ZONE (FROM FIGURE B.3), AND ENTER THEM IN THE TEMPORARY SEEDING SUMMARY BELOW ALONG WITH APPLICATION RATES, SEEDING DATES AND SEEDING DEPTHS. IF THIS SUMMARY IS NOT PUT ON THE PLAN AND COMPLETED, THEN TABLE 8.1 PLUS FERTILIZER AND LIME RATES MUST BE PUT ON THE PLAN.
2. FOR SITES HAVING SOIL TESTS PERFORMED, USE AND SHOW THE RECOMMENDED RATES BY THE TESTING AGENCY. SOIL TESTS ARE NOT REQUIRED FOR TEMPORARY SEEDING.
3. WHEN STABILIZATION IS REQUIRED OUTSIDE OF A SEEDING SEASON, APPLY SEED AND MULCH OR STRAW MULCH ALONE AS PRESCRIBED IN SECTION B-4-3.A.1.B AND MAINTAIN UNTIL THE NEXT SEEDING SEASON.

TEMPORARY SEEDING SUMMARY

HARDINESS ZONE (FROM FIGURE B.3): ZONE 6b
SEED MIXTURE (FROM TABLE B.1):

NO	SPECIES	APPLICATION RATE (LB/AC)	SEEDING DATES	SEEDING DEPTHS	FELIZER RATE (10-20-20)	LIME RATE
1	COOL SEASON ANNUAL RYEGRASS OR EQUAL	40 LB / AC	MAR 1 TO MAY 15 AUG 1 TO OCT 15	1/2 IN.	436 LB/AC (10 LB PER 1000 SF)	2 TONS/AC (90 LB PER 1000 SF)
2	WARM SEASON FOXTAIL MILLET OR EQUAL	30 LB / AC	MAY 16 TO JUL 31	1/2 IN.		

PERMANENT SEEDING SUMMARY

HARDINESS ZONE (FROM FIGURE B.3): ZONE 6b
SEED MIXTURE (FROM TABLE B.3): 9

NO	SPECIES	APPLICATION RATE (LB/AC)	SEEDING DATES	SEEDING DEPTHS	FELIZER RATE (10-20-20) N	P_2O_5	K_2O	LIME RATE
1	COOL SEASON TALL FESCUE & KENTUCKY BLUEGRASS OR EQUAL	T.F. 60 LB / AC K.B. 40 LB / AC	MAR 1 TO MAY 15 AUG 15 TO OCT 15	1/4-1/2 IN.	45 LB/AC (1 LB PER 1000 SF)	90 LB/AC (2 LB PER 1000 SF)	90 LB/AC (2 LB PER 1000 SF)	2 TONS/AC (90 LB PER 1000 SF)

B-4-5 STANDARDS AND SPECIFICATIONS FOR PERMANENT STABILIZATION

DEFINITION
TO STABILIZE DISTURBED SOILS WITH PERMANENT VEGETATION.

PURPOSE
TO USE LONG-LIVED PERENNIAL GRASSES AND LEGUMES TO ESTABLISH PERMANENT GROUND COVER ON DISTURBED SOILS.

CONDITIONS WHERE PRACTICE APPLIES
EXPOSED SOILS WHERE GROUND COVER IS NEEDED FOR 6 MONTHS OR MORE.

CRITERIA
A. SEED MIXTURES
I. GENERAL USE
A. SELECT ONE OR MORE OF THE SPECIES OR MIXTURES LISTED IN TABLE 8.3 FOR THE APPROPRIATE PLANT HARDINESS ZONE (FROM FIGURE 8.3) AND BASED ON THE SITE CONDITION OR PURPOSE FOUND ON TABLE 8.2. ENTER SELECTED MIXTURE(S), APPLICATION RATES, AND SEEDING DATES IN THE PERMANENT SEEDING SUMMARY. THE SUMMARY IS TO BE PLACED ON THE PLAN.
B. ADDITIONAL PLANTING SPECIFICATIONS FOR EXCEPTIONAL SITES SUCH AS SHORELINES, STREAM BANKS, OR DUNES OR FOR SPECIAL PURPOSES SUCH AS WILDLIFE OR AESTHETIC TREATMENT MAY BE FOUND IN USDA-NRCS TECHNICAL FIELD OFFICE GUIDE, SECTION 342 - CRITICAL AREA PLANTING.
C. FOR SITES HAVING DISTURBED AREA OVER 5 ACRES, USE AND SHOW THE RATES RECOMMENDED BY THE SOIL TESTING AGENCY.
D. FOR AREAS RECEIVING LOW MAINTENANCE, APPLY UREA FORM FERTILIZER (46-0-0) AT 3-1/2 POUNDS PER 1000 SQUARE FEET (150 POUNDS PER ACRE) AT THE TIME OF SEEDING IN ADDITION TO THE SOIL AMENDMENTS SHOWN IN THE PERMANENT SEEDING SUMMARY.

2. TURFGRASS MIXTURES
A. AREAS WHERE TURFGRASS MAY BE DESIRED INCLUDE LAWNS, PARKS, PLAYGROUNDS, AND COMMERCIAL SITES WHICH WILL RECEIVE A MEDIUM TO HIGH LEVEL OF MAINTENANCE.
B. SELECT ONE OR MORE OF THE SPECIES OR MIXTURES LISTED BELOW BASED ON THE SITE CONDITIONS OR PURPOSE. ENTER SELECTED MIXTURE(S), APPLICATION RATES, AND SEEDING DATES IN THE PERMANENT SEEDING SUMMARY. THE SUMMARY IS TO BE PLACED ON THE PLAN.
I. KENTUCKY BLUEGRASS: FULL SUN MIXTURE: FOR USE IN AREAS THAT RECEIVE INTENSIVE MANAGEMENT. IRRIGATION REQUIRED IN THE AREAS OF CENTRAL MARYLAND AND EASTERN SHORE. RECOMMENDED CERTIFIED KENTUCKY BLUEGRASS CULTIVARS SEEDING RATE: 1.5 POUNDS PER 1000 SQUARE FEET. CHOOSE A MINIMUM OF THREE KENTUCKY BLUEGRASS CULTIVARS WITH EACH RANGING FROM 10 TO 35 PERCENT OF THE TOTAL MIXTURE BY WEIGHT.
II. KENTUCKY BLUEGRASS/PERENNIAL RYE: FULL SUN MIXTURE: FOR USE IN FULL SUN AREAS WHERE RAPID ESTABLISHMENT IS NECESSARY AND WHEN TURF WILL RECEIVE MEDIUM TO INTENSIVE MANAGEMENT. CERTIFIED PERENNIAL RYEGRASS CULTIVARS/ CERTIFIED KENTUCKY BLUEGRASS SEEDING RATE: 2 POUNDS MIXTURE PER 1000 SQUARE FEET. CHOOSE A MINIMUM OF THREE KENTUCKY BLUEGRASS CULTIVARS WITH EACH RANGING FROM 10 TO 35 PERCENT OF THE TOTAL MIXTURE BY WEIGHT.
III. TALL FESCUE/KENTUCKY BLUEGRASS: FULL SUN MIXTURE: FOR USE IN DROUGHT PRONE AREAS AND/OR FOR AREAS RECEIVING LOW TO MEDIUM MANAGEMENT IN FULL SUN TO MEDIUM SHADE. RECOMMENDED MIXTURE INCLUDES; CERTIFIED TALL FESCUE CULTIVARS 95 TO 100 PERCENT, CERTIFIED KENTUCKY BLUEGRASS CULTIVARS 0 TO 5 PERCENT. SEEDING RATE: 5 TO 8 POUNDS PER 1000 SQUARE FEET. ONE OR MORE CULTIVARS MAY BE BLENDED.
IV. KENTUCKY BLUEGRASS/FINE FESCUE: SHADE MIXTURE: FOR USE IN AREAS WITH SHADE IN BLUEGRASS LAWNS. FOR ESTABLISHMENT IN HIGH QUALITY, INTENSIVELY MANAGED TURF AREA. MIXTURE INCLUDES; CERTIFIED KENTUCKY BLUEGRASS CULTIVARS 30 TO 40 PERCENT AND CERTIFIED FINE FESCUE AND 60 TO 70 PERCENT. SEEDING RATE: 1½ TO 3 POUNDS PER 1000 SQUARE FEET.

NOTES:
SELECT TURFGRASS VARIETIES FROM THOSE LISTED IN THE MOST CURRENT UNIVERSITY OF MARYLAND PUBLICATION, AGRONOMY MEMO #77, "TURFGRASS CULTIVAR RECOMMENDATIONS FOR MARYLAND" CHOOSE CERTIFIED MATERIAL. CERTIFIED MATERIAL IS THE BEST GUARANTEE OF CULTIVAR PURITY. THE CERTIFICATION PROGRAM OF THE MARYLAND DEPARTMENT OF AGRICULTURE, TURF AND SEED SECTION, PROVIDES A RELIABLE MEANS OF CONSUMER PROTECTION AND ASSURES A PURE GENETIC LINE

C. IDEAL TIMES OF SEEDING FOR TURF GRASS MIXTURES

- WESTEM MD: MARCH 15 TO JUNE 1, AUGUST ITO OCTOBER 1 (HARDINESS ZONES: 5B, 6A)
- CENTRAL MD: MARCH 1 TO MAY 15, AUGUST 15 TO OCTOBER 15 (HARDINESS ZONE: 6B)
- SOUTHERN MD, EASTERN SHORE: MARCH 1 TO MAY 15, AUGUST 15 TO OCTOBER 15 (HARDINESS ZONES: 7A, 7B)

D. TILL AREAS TO RECEIVE SEED BY DISKING OR OTHER APPROVED METHODS TO A DEPTH OF 2 TO 4 INCHES, LEVEL AND RAKE THE AREAS TO PREPARE A PROPER SEEDBED. REMOVE STONES AND DEBRIS OVER 1½ INCHES IN DIAMETER. THE RESULTING SEEDBED MUST BE IN SUCH CONDITION THAT FUTURE MOWING OF GRASSES WILL POSE NO DIFFICULTY.
E. IF SOIL MOISTURE IS DEFICIENT, SUPPLY NEW SEEDINGS WITH ADEQUATE WATER FOR PLANT GROWTH (1/2 TO 1 INCH EVERY 3 TO 4 DAYS DEPENDING ON SOIL TEXTURE) UNTIL THEY ARE FIRMLY ESTABLISHED. THIS IS ESPECIALLY TRUE WHEN SEEDINGS ARE MADE LATE IN THE PLANTING SEASON, IN ABNORMALLY DRY OR HOT SEASONS, OR ON ADVERSE SITES.

B. SOD: TO PROVIDE QUICK COVER ON DISTURBED AREAS (2:1 GRADE OR FLATTER).

1. GENERAL SPECIFICATIONS
A. CLASS OF TURFGRASS SOD MUST BE MARYLAND STATE CERTIFIED. SOD LABELS MUST BE MADE AVAILABLE TO THE JOB FOREMAN AND INSPECTOR.
B. SOD MUST BE MACHINE CUT AT A UNIFORM SOIL THICKNESS OF 3/4 INCH, PLUS OR MINUS ¼ INCH, AT THE TIME OF CUTTING. MEASUREMENT FOR THICKNESS MUST EXCLUDE TOP GROWTH AND THATCH. BROKEN PADS AND TOM OR UNEVEN ENDS WILL NOT BE ACCEPTABLE.
C. STANDARD SIZE SECTIONS OF SOD MUST BE STRONG ENOUGH TO SUPPORT THEIR OWN WEIGHT AND RETAIN THEIR SIZE AND SHAPE WHEN SUSPENDED VERTICALLY WITH A FIRM GRASP ON THE UPPER 10 PERCENT OF THE SECTION.
D. SOD MUST NOT BE HARVESTED OR TRANSPLANTED WHEN MOISTURE CONTENT (EXCESSIVELY DRY OR WET) MAY ADVERSELY AFFECT ITS SURVIVAL.
E. SOD MUST BE HARVESTED, DELIVERED, AND INSTALLED WITHIN A PERIOD OF 36 HOURS. SOD NOT TRANSPLANTED WITHIN THIS PERIOD MUST BE APPROVED BY AN AGRONOMIST OR SOIL SCIENTIST PRIOR TO ITS INSTALLATION.

2. SOD INSTALLATION
A. DURING PERIODS OF EXCESSIVELY HIGH TEMPERATURE OR IN AREAS HAVING DRY SUBSOIL, LIGHTLY IRRIGATE THE SUBSOIL IMMEDIATELY PRIOR TO LAYING THE SOD.
B. LAY THE FIRST ROW OF SOD IN A STRAIGHT LINE WITH SUBSEQUENT ROWS PLACED PARALLEL TO IT AND TIGHTLY WEDGED AGAINST EACH OTHER. STAGGER LATERAL JOINTS TO PROMOTE MORE UNIFORM GROWTH AND STRENGTH. ENSURE THAT SOD IS NOT STRETCHED OR OVERLAPPED AND THAT ALL JOINTS ARE BUTTED TIGHT IN ORDER TO PREVENT VOIDS WHICH WOULD CAUSE AIR DRYING OF THE ROOTS.
C. WHEREVER POSSIBLE, LAY SOD WITH THE LONG EDGES PARALLEL TO THE CONTOUR AND WITH STAGGERING JOINTS. ROLL AND TAMP, PEG OR OTHERWISE SECURE THE SOD TO PREVENT SLIPPAGE ON SLOPES. ENSURE SOLID CONTACT EXISTS BETWEEN SOD ROOTS AND THE UNDERLYING SOIL SURFACE.
D. WATER THE SOD IMMEDIATELY FOLLOWING ROLLING AND TAMPING UNTIL THE UNDERSIDE OF THE NEW SOD PAD AND SOIL SURFACE BELOW THE SOD ARE THOROUGHLY WET. COMPLETE THE OPERATIONS OF LAYING, TAMPING AND IRRIGATING FOR ANY PIECE OF SOD WITHIN EIGHT HOURS.

3. SOD MAINTENANCE
A. IN THE ABSENCE OF ADEQUATE RAINFALL, WATER DAILY DURING THE FIRST WEEK OR AS OFTEN AND SUFFICIENTLY AS NECESSARY TO MAINTAIN MOIST SOIL TO A DEPTH OF 4 INCHES. WATER SOD DURING THE HEAT OF THE DAY TO PREVENT WILTING.
B. AFTER THE FIRST WEEK, SOD WATERING IS REQUIRED AS NECESSARY TO MAINTAIN ADEQUATE MOISTURE CONTENT.
C. DO NOT MOW UNTIL THE SOD IS FIRMLY ROOTED. NO MORE THAN 1/3 OF THE GRASS LEAF MUST BE REMOVED BY THE INITIAL CUTTING OR SUBSEQUENT CUTTINGS. MAINTAIN A GRASS HEIGHT OF AT LEAST 3 INCHES UNLESS OTHERWISE SPECIFIED.

R-4-2 STANDARDS AND SPECIFICATIONS FOR SOIL PREPARATION, TOPSOILING AND SOIL AMENDMENTS

DEFINITION
THE PROCESS OF PREPARING THE SOILS TO SUSTAIN ADEQUATE VEGETATIVE STABILIZATION.

PURPOSE
TO PROVIDE A SUITABLE SOIL MEDIUM FOR VEGETATIVE GROWTH.

CONDITIONS WHERE PRACTICE APPLIES
WHERE VEGETATIVE STABILIZATION IS TO BE ESTABLISHED.

CRITERIA
A. SOIL PREPARATION

1. TEMPORARY STABILIZATION
A. SEEDBED PREPARATION CONSISTS OF LOOSENING SOIL TO A DEPTH OF 3 TO 5 INCHES BY MEANS OF SUITABLE AGRICULTURAL OR CONSTRUCTION EQUIPMENT, SUCH AS DISC HARROWS OR CHISEL PLOWS OR RIPPERS MOUNTED ON CONSTRUCTION EQUIPMENT. AFTER THE SOIL IS LOOSENED, IT MUST NOT BE ROLLED OR DRAGGED SMOOTH BUT LEFT IN THE ROUGHENED CONDITION. SLOPES 3:1 OR FLATTER ARE TO BE TRACKED WITH RIDGES RUNNING PARALLEL TO THE CONTOUR OF THE SLOPE.
B. APPLY FERTILIZER AND LIME AS PRESCRIBED ON THE PLANS.
C. INCORPORATE LIME AND FERTILIZER INTO THE TOP 3 TO 5 INCHES OF SOIL BY DISKING OR OTHER SUITABLE MEANS.

2. PERMANENT STABILIZATION
A. A SOIL TEST IS REQUIRED FOR ANY EARTH DISTURBANCE OF 5 ACRES OR MORE. THE MINIMUM SOIL CONDITIONS REQUIRED FOR PERMANENT VEGETATIVE ESTABLISHMENT ARE:
I. SOIL PH BETWEEN 6.0 AND 7.0.
II. SOLUBLE SALTS LESS THAN 500 PARTS PER MILLION (PPM).
III. SOIL CONTAINS LESS THAN 40 PERCENT CLAY BUT ENOUGH FINE GRAINED MATERIAL (GREATER THAN 30 PERCENT SILT PLUS CLAY) TO PROVIDE THE CAPACITY TO HOLD A MODERATE AMOUNT OF MOISTURE. AN EXCEPTION: IF LOVEGRASS WILL BE PLANTED, THEN A SANDY SOIL (LESS THAN 30 PERCENT SILT PLUS CLAY) WOULD BE ACCEPTABLE.
IV. SOIL CONTAINS 1.5 PERCENT MINIMUM ORGANIC MATTER BY WEIGHT.
V. SOIL CONTAINS SUFFICIENT PORE SPACE TO PERMIT ADEQUATE ROOT PENETRATION.
B. APPLICATION OF AMENDMENTS OR TOPSOIL IS REQUIRED IF ON-SITE SOILS DO NOT MEET THE ABOVE CONDITIONS.
C. GRADED AREAS MUST BE MAINTAINED IN A TRUE AND EVEN GRADE AS SPECIFIED ON THE APPROVED PLAN, THEN SCARIFIED OR OTHERWISE LOOSENED TO A DEPTH OF 3 TO 5 INCHES.
D. APPLY SOIL AMENDMENTS AS SPECIFIED ON THE APPROVED PLAN OR AS INDICATED BY THE RESULTS OF A SOIL TEST.
E. MIX SOIL AMENDMENTS INTO THE TOP 3 TO 5 INCHES OF SOIL BY DISKING OR OTHER SUITABLE MEANS. RAKE LAWN AREAS TO SMOOTH THE SURFACE, REMOVE LARGE OBJECTS LIKE STONES AND BRANCHES, AND READY THE AREA FOR SEED APPLICATION. LOOSEN SURFACE SOIL MUST BE DRAGGING WITH A HEAVY CHAIN OR OTHER EQUIPMENT TO ROUGHEN THE SURFACE WHERE SITE CONDITIONS WILL NOT PERMIT NORMAL SEEDBED PREPARATION. TRACK SLOPES 3:1 OR FLATTER WITH TRACKED EQUIPMENT LEAVING THE SOIL IN AN IRREGULAR CONDITION WITH RIDGES RUNNING PARALLEL TO THE CONTOUR OF THE SLOPE. LEAVE THE TOP 1 TO 3 INCHES OF SOIL LOOSE AND FRIABLE. SEEDBED LOOSENING MAY BE UNNECESSARY ON NEWLY DISTURBED AREAS.

B. TOPSOILING
I. TOPSOIL IS PLACED OVER PREPARED SUBSOIL PRIOR TO ESTABLISHMENT OF PERMANENT VEGETATION. THE PURPOSE IS TO PROVIDE A SUITABLE SOIL MEDIUM FOR VEGETATIVE GROWTH. SOILS OF CONCEM HAVE LOW MOISTURE CONTENT, LOW NUTRIENT LEVELS, LOW PH, MATERIALS TOXIC TO PLANTS, AND/OR UNACCEPTABLE SOIL GRADATION.
2. TOPSOIL SALVAGED FROM AN EXISTING SITE MAY BE USED PROVIDED IT MEETS THE STANDARDS AS SET FORTH IN THESE SPECIFICATIONS. TYPICALLY, THE DEPTH OF TOPSOIL TO BE SALVAGED FOR A GIVEN SOIL TYPE CAN BE FOUND IN THE REPRESENTATIVE SOIL PROFILE SECTION IN THE SOIL SURVEY PUBLISHED BY USDA-NRCS.
3. TOPSOILING IS LIMITED TO AREAS HAVING 2:1 OR FLATTER SLOPES WHERE:
A. THE TEXTURE OF THE EXPOSED SUBSOIL/PARENT MATERIAL IS NOT ADEQUATE TO PRODUCE VEGETATIVE GROWTH.
B. THE SOIL MATERIAL IS SO SHALLOW THAT THE ROOTNG ZONE IS NOT DEEP ENOUGH TO SUPPORT PLANTS OR FURNISH CONTINUING SUPPLIES OF MOISTURE AND PLANT NUTRIENTS.
C. THE ORIGINAL SOIL TO BE VEGETATED CONTAINS MATERIAL TOXIC TO PLANT GROWTH.
D. THE SOIL IS SO ACIDIC THAT TREATMENT WITH LIMESTONE IS NOT FEASIBLE.
4. AREAS HAVING SLOPES STEEPER THAN 2:1 REQUIRE SPECIAL CONSIDERATION AND DESIGN.
5. TOPSOIL SPECIFICATIONS: SOIL TO BE USED AS TOPSOIL MUST MEET THE FOLLOWING CRITERIA:
A. TOPSOIL MUST BE A LOAM, SANDY LOAM, CLAY LOAM, SILT LOAM, SANDY CLAY LOAM, OR LOAMY SAND. OTHER SOILS MAY BE USED IF RECOMMENDED BY AN AGRONOMIST OR SOIL SCIENTIST AND APPROVED BY THE APPROPRIATE APPROVAL AUTHORITY. TOPSOIL MUST NOT BE A MIXTURE OF CONTRASTING TEXTURED SUBSOILS AND MUST CONTAIN LESS THAN 5 PERCENT BY VOLUME OF CINDERS, STONES, SLAG, COARSE FRAGMENTS, GRAVEL, STICKS, ROOTS, TRASH, OR OTHER MATERIALS LARGER THAN 1½ INCHES IN DIAMETER.
B. TOPSOIL MUST BE FREE OF NOXIOUS PLANTS OR PLANT PARTS SUCH AS BERMUDA GRASS, QUACK GRASS, JOHNSON GRASS, NUT SEDGE, POISON IVY, THISTLE, OR OTHERS AS SPECIFIED.
C. TOPSOIL SUBSTITUTES OR AMENDMENTS, AS RECOMMENDED BY A QUALIFIED AGRONOMIST OR SOIL SCIENTIST AND APPROVED BY THE APPROPRIATE APPROVAL AUTHORITY, MAY BE USED IN LIEU OF NATURAL TOPSOIL.
6. TOPSOIL APPLICATION
A. EROSION AND SEDIMENT CONTROL PRACTICES MUST BE MAINTAINED WHEN APPLYING TOPSOIL.
B. UNIFORMLY DISTRIBUTE TOPSOIL IN A 5 TO 8 INCH LAYER AND LIGHTLY COMPACT TO A MINIMUM THICKNESS OF 4 INCHES. SPREADING IS TO BE PERFORMED IN SUCH A MANNER THAT SODDING OR SEEDING CAN PROCEED WITH A MINIMUM OF ADDITIONAL SOIL PREPARATION AND TILLAGE, ANY IRREGULARITIES IN THE SURFACE RESULTING FROM TOPSOILING OR OTHER OPERATIONS MUST BE CORRECTED IN ORDER TO PREVENT THE FORMATION OF DEPRESSIONS OR WATER POCKETS.
C. TOPSOIL MUST NOT BE PLACED IF THE TOPSOIL OR SUBSOIL IS IN A FROZEN OR MUDDY CONDITION, WHEN THE SUBSOIL IS EXCESSIVELY WET OR IN A CONDITION THAT MAY OTHERWISE BE DETRIMENTAL TO PROPER GRADING AND SEEDBED PREPARATION.

C. SOIL AMENDMENTS (FERTILIZER AND LIME SPECIFICATIONS)
I. SOIL TESTS MUST BE PERFORMED TO DETERMINE THE EXACT RATIOS AND APPLICATION RATES FOR BOTH LIME AND FERTILIZER ON SITES HAVING DISTURBED AREAS OF 5 ACRES OR MORE. SOIL ANALYSIS MAY BE PERFORMED BY A RECOGNIZED PRIVATE OR COMMERCIAL LABORATORY. SOIL SAMPLES TAKEN FOR ENGINEERING PURPOSES MAY ALSO BE USED FOR CHEMICAL ANALYSES.
2. FERTILIZERS MUST BE UNIFORM IN COMPOSITION, FREE FLOWING AND SUITABLE FOR ACCURATE APPLICATION BY APPROPRIATE EQUIPMENT. MANURE MAY BE SUBSTITUTED FOR FERTILIZER WITH PRIOR APPROVAL FROM THE APPROPRIATE APPROVAL AUTHORITY. FERTILIZERS MUST ALL BE DELIVERED TO THE SITE FULLY LABELED ACCORDING TO THE APPLICABLE LAWS AND MUST BEAR THE NAME, TRADE NAME OR TRADEMARK AND WARRANTY OF THE PRODUCER.
3. LIME MATERIALS MUST BE GROUND LIMESTONE (HYDRATED OR BURNT LIME MAY BE SUBSTITUTED EXCEPT WHEN HYDROSEEDING) WHICH CONTAINS AT LEAST 50 PERCENT TOTAL OXIDES (CALCIUM OXIDE PLUS MAGNESIUM OXIDE). LIMESTONE MUST BE GROUND TO SUCH FINENESS THAT AT LEAST 50 PERCENT WILL PASS THROUGH A #100 MESH SIEVE AND 98 TO 100 PERCENT WILL PASS THROUGH A #20 MESH SIEVE.
4. LIME AND FERTILIZER ARE TO BE EVENLY DISTRIBUTED AND INCORPORATED INTO THE TOP 3 TO 5 INCHES OF SOIL BY DISKING OR OTHER SUITABLE MEANS.
5. WHERE THE SUBSOIL IS EITHER HIGHLY ACIDIC OR COMPOSED OF HEAVY CLAYS, SPREAD GROUND LIMESTONE AT THE RATE OF 4 TO 8 TONS/ACRE (200-400 POUNDS PER 1,000 SQUARE FEET) PRIOR TO THE PLACEMENT OF TOPSOIL.

B-4-3 STANDARDS AND SPECIFICATIONS FOR SEEDING AND MULCHING

DEFINITION
THE APPLICATION OF SEED AND MULCH TO ESTABLISH VEGETATIVE COVER.

PURPOSE
TO PROTECT DISTURBED SOILS FROM EROSION DURING AND AT THE END OF CONSTRUCTION.

CONDITIONS WHERE PRACTICE APPLIES
TO THE SURFACE OF ALL PERIMETER CONTROLS, SLOPES, AND ANY DISTURBED AREA NOT UNDER ACTIVE GRADING.

CRITERIA
A. SEEDING
1. SPECIFICATIONS
A. ALL SEED MUST MEET THE REQUIREMENTS OF THE MARYLAND STATE SEED LAW. ALL SEED MUST BE SUBJECT TO RE-TESTING BY A RECOGNIZED SEED LABORATORY. ALL SEED USED MUST HAVE BEEN TESTED WITHIN THE 6 MONTHS IMMEDIATELY PRECEDING THE DATE OF SOWING SUCH MATERIAL ON ANY PROJECT. REFER TO TABLE B.4 REGARDING THE QUALITY OF SEED. SEED TAGS MUST BE AVAILABLE UPON REQUEST TO THE INSPECTOR TO VERIFY TYPE OF SEED AND SEEDING RATE.
B. MULCH ALONE MAY BE APPLIED BETWEEN THE FALL AND SPRING SEEDING DATES ONLY IF THE GROUND IS FROZEN. THE APPROPRIATE SEEDING MIXTURE MUST BE APPLIED WHEN THE GROUND THAWS.
C. INOCULANTS: THE INOCULANT FOR TREATING LEGUME SEED IN THE SEED MIXTURES MUST BE A PURE CULTURE OF NITROGEN FIXING BACTERIA PREPARED SPECIFICALLY FOR THE SPECIES. INOCULANTS MUST NOT BE USED LATER THAN THE DATE INDICATED ON THE CONTAINER. ADD FRESH INOCULANTS AS DIRECTED ON THE PACKAGE. USE FOUR TIMES THE RECOMMENDED RATE WHEN HYDROSEEDING. NOTE: IT IS VERY IMPORTANT TO KEEP INOCULANT AS COOL AS POSSIBLE UNTIL USED. TEMPERATURES ABOVE 75 TO 80 DEGREES FAHRENHEIT CAN WEAKEN BACTERIA AND MAKE THE INOCULANT LESS EFFECTIVE.
D. SOD OR SEED MUST NOT BE PLACED ON SOIL WHICH HAS BEEN TREATED WITH SOIL STERILANTS OR CHEMICALS USED FOR WEED CONTROL UNTIL SUFFICIENT TIME HAS ELAPSED (14 DAYS MIN.) TO PERMIT DISSIPATION OF PHYTO-TOXIC MATERIALS.
2. APPLICATION
A. DRY SEEDING: THIS INCLUDES USE OF CONVENTIONAL DROP OR BROADCAST SPREADERS.
I. INCORPORATE SEED INTO THE SUBSOIL AT THE RATES PRESCRIBED ON TEMPORARY SEEDING TABLE 8.1, PERMANENT SEEDING TABLE 8.3, OR SITE-SPECIFIC SEEDING SUMMARIES.
II. APPLY SEED IN TWO DIRECTIONS, PERPENDICULAR TO EACH OTHER. APPLY HALF THE SEEDING RATE IN EACH DIRECTION. ROLL THE SEEDED AREA WITH A WEIGHTED ROLLER TO PROVIDE GOOD SEED TO SOIL CONTACT.
B. DRILL OR CULTIPACKER SEEDING: MECHANIZED SEEDERS THAT APPLY AND COVER SEED WITH SOIL.
I. CULTIPACKING SEEDERS ARE REQUIRED TO BURY THE SEED IN SUCH A FASHION AS TO PROVIDE AT LEAST 1/4 INCH OF SOIL COVERING. SEEDBED MUST BE FIRM AFTER PLANTING.
II. APPLY SEED IN TWO DIRECTIONS, PERPENDICULAR TO EACH OTHER. APPLY HALF THE SEEDING RATE IN EACH DIRECTION.
C. HYDROSEEDING: APPLY SEED UNIFORMLY WITH HYDROSEEDER (SLURRY INCLUDES SEED AND FERTILIZER).
I. IF FERTILIZER IS BEING APPLIED AT THE TIME OF SEEDING, THE APPLICATION RATES SHOULD NOT EXCEED THE FOLLOWING: NITROGEN, 100 POUNDS PER ACRE TOTAL OF SOLUBLE NITROGEN; P205 (PHOSPHOROUS), 200 POUNDS PER ACRE; K20 (POTASSIUM), 200 POUNDS PER ACRE.
II. LIME: USE ONLY GROUND AGRICULTURAL LIMESTONE (UP TO 3 TONS PER ACRE MAY BE APPLIED BY HYDROSEEDING). NORMALLY, NOT MORE THAN 2 TONS ARE APPLIED BY HYDROSEEDING AT ANY ONE TIME. DO NOT USE BURNT OR HYDRATED LIME WHEN HYDROSEEDING.
III. MIX SEED AND FERTILIZER ON SITE AND SEED IMMEDIATELY AND WITHOUT INTERRUPTION.
IV. WHEN HYDROSEEDING DO NOT INCORPORATE SEED INTO THE SOIL.

B. MULCHING
I. MULCH MATERIALS (IN ORDER OF PREFERENCE)
A. STRAW CONSISTING OF THOROUGHLY THRESHED WHEAT, LYE, OAT, OR BARLEY AND REASONABLY BRIGHT IN COLOR. STRAW IS TO BE FREE OF NOXIOUS WEED SEEDS AS SPECIFIED IN THE MARYLAND SEED LAW AND NOT MUSTY, MOLDY, CA

A-2. PERMEABLE PAVEMENTS

CONSTRUCTION CRITERIA:

THE FOLLOWING ITEMS SHOULD BE ADDRESSED DURING CONSTRUCTION OF PROJECTS WITH PERMEABLE PAVEMENT:

- EROSION AND SEDIMENT CONTROL: FINAL GRADING FOR INSTALLATION SHOULD NOT TAKE PLACE UNTIL THE SURROUNDING SITE IS STABILIZED. IF THIS CANNOT BE ACCOMPLISHED, RUNOFF FROM DISTURBED AREAS SHALL BE DIVERTED AROUND PROPOSED PAVEMENT LOCATIONS.
- SOIL COMPACTION: SUB SOILS SHALL NOT BE COMPACTED. CONSTRUCTION SHOULD BE PERFORMED WITH LIGHTWEIGHT, WIDE TRACKED EQUIPMENT TO MINIMIZE COMPACTION. EXCAVATED MATERIALS SHOULD BE PLACED IN A CONTAINED AREA.
- DISTRIBUTION SYSTEMS: OVERDRAIN, UNDERDRAIN, AND DISTRIBUTION PIPES SHALL BE CHECKED TO ENSURE THAT BOTH THE MATERIAL AND PERFORATIONS MEET SPECIFICATIONS (SEE APPENDIX B. 4). THE UPSTREAM ENDS OF PIPES SHOULD BE CAPPED PRIOR TO INSTALLATION. ALL UNDERDRAIN OR DISTRIBUTION PIPES USED SHOULD BE INSTALLED FLAT ALONG THE BED BOTTOM.
- SUBBASE INSTALLATION: SUBBASE AGGREGATE SHALL BE CLEAN AND FREE OF FINES. THE SUBBASE SHALL BE PLACED IN LIFTS AND LIGHTLY ROLLED ACCORDING TO THE SPECIFICATIONS (SEE APPENDIX B.4).

INSPECTION:

REGULAR INSPECTIONS SHALL BE MADE DURING THE FOLLOWING STAGES OF CONSTRUCTION:

- DURING EXCAVATION TO SUB GRADE.
- DURING PLACEMENT AND BACKFILL OF ANY DRAINAGE OR DISTRIBUTION SYSTEM(S).
- DURING PLACEMENT OF THE CRUSHED STONE SUBBASE MATERIAL.
- DURING PLACEMENT OF THE SURFACE MATERIAL.
- UPON COMPLETION OF FINAL GRADING AND ESTABLISHMENT OF PERMANENT STABILIZATION.

MAINTENANCE CRITERIA:

THE FOLLOWING PROCEDURES SHOULD BE CONSIDERED ESSENTIAL FOR MAINTAINING PERMEABLE PAVEMENT SYSTEMS:

- PAVEMENTS SHOULD BE USED ONLY WHERE REGULAR MAINTENANCE CAN BE PERFORMED. MAINTENANCE AGREEMENTS SHOULD CLEARLY SPECIFY HOW TO CONDUCT ROUTINE TASKS TO ENSURE LONG-TERM PERFORMANCE.
- PAVEMENT SURFACES SHOULD BE SWEPT AND VACUUMED TO REDUCE SEDIMENT ACCUMULATION AND ENSURE CONTINUED SURFACE POROSITY. SWEEPING SHOULD BE PERFORMED AT LEAST TWICE ANNUALLY WITH A COMMERCIAL CLEANING UNIT. WASHING SYSTEMS AND COMPRESSED AIR UNITS SHOULD NOT BE USED TO PERFORM SURFACE CLEANING.
- DRAINAGE PIPES, INLETS, STONE EDGE DRAINS, AND OTHER STRUCTURES WITHIN OR DRAINING TO THE SUBBASE SHOULD BE CLEANED OUT AT REGULAR INTERVALS.
- TRUCKS AND OTHER HEAVY VEHICLES CAN GRIND DIRT AND GRIT INTO THE POROUS SURFACES, LEADING TO CLOGGING AND PREMATURE FAILURE. THESE VEHICLES SHOULD BE PREVENTED FROM TRACKING AND SPILLING MATERIAL ONTO THE PAVEMENT.
- DEICERS SHOULD BE USED IN MODERATION. WHEN USED, DEICERS SHOULD BE NON-TOXIC AND ORGANIC AND CAN BE APPLIED EITHER AS CALCIUM MAGNESIUM ACETATE OR AS PRETREATED SALT. SNOW PLOWING SHOULD BE DONE CAREFULLY WITH BLADES SET ONE-INCH HIGHER THAN NORMAL. PLOWED SNOW PILES AND SNOW MELT SHOULD NOT BE DIRECTED TO PERMEABLE PAVEMENT.

N-1. DISCONNECTION OF ROOFTOP RUNOFF

CONSTRUCTION CRITERIA:

THE FOLLOWING ITEMS SHOULD BE ADDRESSED DURING THE CONSTRUCTION OF PROJECTS WITH PLANNED ROOFTOP DISCONNECTIONS:

- EROSION AND SEDIMENT CONTROL: EROSION AND SEDIMENT CONTROL PRACTICES (E.G., SEDIMENT TRAPS) SHALL NOT BE LOCATED IN VEGETATED AREAS RECEIVING DISCONNECTED RUNOFF
- SITE DISTURBANCE: CONSTRUCTION VEHICLES AND EQUIPMENT SHOULD AVOID AREAS RECEIVING DISCONNECTED RUNOFF TO MINIMIZE DISTURBANCE AND COMPACTION. SHOULD AREAS RECEIVING DISCONNECTED RUNOFF BECOME COMPACTED, SCARIFYING THE SURFACE OR ROTOTILLING THE SOIL TO A DEPTH OF FOUR TO SIX INCHES SHALL BE PERFORMED TO ENSURE PERMEABILITY.

ADDITIONALLY,
AMENDMENTS MAY BE NEEDED FOR TIGHT, CLAYEY SOILS.

INSPECTION:

A FINAL INSPECTION SHALL BE CONDUCTED BEFORE USE AND OCCUPANCY APPROVAL TO ENSURE THAT PLANTING FOR TREATMENT AREAS HAVE BEEN NET AND PERMANENT STABILIZATION HAS BEEN ESTABLISHED.

MAINTENANCE CRITERIA:

MAINTENANCE OF AREAS RECEIVING DISCONNECTED RUNOFF IS GENERALLY NO DIFFERENT THAN THAT REQUIRED FOR OTHER LAWN OR LANDSCAPED AREAS. THE AREAS RECEIVING RUNOFF SHOULD BE PROTECTED FROM FUTURE COMPACTION (E.G., BY PLANTING TREES OR SHRUBS ALONG THE PERIMETER). IN COMMERCIAL AREAS, FOOT TRAFFIC SHOULD BE DISCOURAGED AS WELL.

N-2. DISCONNECTION OF NON-ROOFTOP RUNOFF

CONSTRUCTION CRITERIA:

THE FOLLOWING SHOULD BE ADDRESSED DURING CONSTRUCTION OF PROJECTS WITH NON-ROOFTOP DISCONNECTIONS:

- EROSION AND SEDIMENT CONTROL: EROSION AND SEDIMENT CONTROL PRACTICES (E.G., SEDIMENT TRAPS) SHALL NOT BE LOCATED IN AREAS DESIGNATED FOR NON-ROOFTOP DISCONNECTIONS.
- SITE DISTURBANCE: TO MINIMIZE DISTURBANCE AND COMPACTION, CONSTRUCTION VEHICLES AND EQUIPMENT SHOULD AVOID AREAS RECEIVING DISCONNECTED RUNOFF. SHOULD AREAS RECEIVING DISCONNECTED RUNOFF BECOME COMPACTED, SCARIFYING THE SURFACE OR ROTOTILLING THE SOIL TO A DEPTH OF FOUR TO SIX INCHES SHALL BE PERFORMED TO ENSURE PERMEABILITY. ADDITIONALLY, AMENDMENTS MAY BE NEEDED FOR TIGHT, CLAYEY SOILS.

INSPECTION:

A FINAL INSPECTION SHALL BE CONDUCTED BEFORE USE AND OCCUPANCY APPROVAL TO ENSURE THAT ADEQUATE TREATMENT AREAS AND PERMANENT STABILIZATION HAS BEEN ESTABLISHED.

MAINTENANCE CRITERIA:

MAINTENANCE OF AREAS RECEIVING DISCONNECTED RUNOFF IS GENERALLY NO DIFFERENT THAN THAT REQUIRED FOR OTHER LAWN OR LANDSCAPED AREAS. THE OWNER SHALL ENSURE THE AREAS RECEIVING RUNOFF ARE PROTECTED FROM FUTURE COMPACTION OR DEVELOPMENT OF IMPERVIOUS AREA. IN COMMERCIAL AREAS, FOOT TRAFFIC SHOULD BE DISCOURAGED AS WELL.

HOWARD COUNTY – OPERATION AND MAINTENANCE SCHEDULE FOR PRIVATELY OWNED AND MAINTAINED DISCONNECTION OF ROOFTOP RUNOFF (N-1). DISCONNECTION OF NON-ROOFTOP RUNOFF (N-2)

A. MAINTENANCE OF AREAS RECEIVING DISCONNECTED RUNOFF IS GENERALLY NO DIFFERENT THAN THAT REQUIRED FOR OTHER LAWN OR LANDSCAPED AREAS. THE OWNER SHALL ENSURE THE AREAS RECEIVING RUNOFF ARE PROTECTED FROM FUTURE COMPACTION OR DEVELOPMENT OF IMPERVIOUS AREA. IN COMMERCIAL AREAS, FOOT TRAFFIC SHOULD BE DISCOURAGED AS WELL.

PROJECT STELLA GLEN
DESIGNER RHV
DATE 03/07/14

ROBERT H. VOGEL ENGINEERING, INC.

ENVIRONMENTAL SITE DESIGN PRACTICE

DRAINAGE AREA #	AREA TREATED	FACILITY NUMBER	ROOFTOP DISCONNECT N-1	NONROOFTOP DISCONNECT N-2	GRASS SWALE M-8	RAIN GARDEN M-7	PERVIOUS CONCRETE A-2	X	X	X	ESDv VOLUME
A	13454	1	64	73	0	79	282	0	0	0	498
B	13970	2	64	0	0	196	245	0	0	0	475
C	11000	3	120	92	0	140	0	0	0	0	352
D	10817	4	160	0	0	158	158	0	0	0	476
E	12210	5	79	0	0	159	199	0	0	0	437
F	11781	6	112	0	0	106	253	0	0	0	471
TOTAL AREA	73232 SF								TOTAL ESDv PROVIDED		2699
	1.68 AC										

PROJECT:	STELLA GLEN	
TOTAL AREA:	3.68	AC
NET DEVELOPABLE AREA	3.36	AC
TARGET Pe:	1.20	IN

DRAINAGE AREA	IMPERVIOUS AREA	GRASS AREA	TOTAL AREA	PERCENT IMPERVIOUS	RV	ESDv MIN	ESDv MAX	ESDv COMPUTED
A	4789	8665	13454	0.36	0.37	415	1080	498
B	4405	9565	13970	0.32	0.33	389	1010	466
C	3326	7674	11000	0.30	0.32	295	768	354
D	2700	8117	10817	0.25	0.27	248	644	297
E	4125	8085	12210	0.34	0.35	360	937	432
F	4545	7236	11781	0.39	0.40	390	1014	468
		TOTAL AREA	73232 SF					2516 CF
			1.68 AC					

SOILS LEGEND

SYMBOL	NAME / DESCRIPTION	GROUP	K-FACTOR
GfB	GLADSTONE–URBAN LAND COMPLEX, 0 TO 8 PERCENT SLOPES	B	0.20
GuB	GLENVILLE–URBAN LAND–UDORTHENTS COMPLEX, 0 TO 8 PERCENT SLOPES	C	0.37
UoF	UDORTHENTS, HIGHWAY, 0 TO 65 PERCENT SLOPES	–	–

APPROVED: HOWARD COUNTY DEPARTMENT OF PLANNING AND ZONING

CHIEF, DEVELOPMENT ENGINEERING DIVISION — DATE 5.13.16

CHIEF, DIVISION OF LAND DEVELOPMENT — DATE 5-17-16

DIRECTOR — DATE 5-17-16

DA-F 0.26 AC
DA-E 0.37 AC
DA-D 0.24 AC.
DA-A 0.32 AC.
DA-B 0.31 AC.
DA-C 0.26 AC.
E 1349900
N 555600
E 1350650
N 555600
N 555050
LOT 9 20,820 SF
LOT 11 20,375 SF 21,490 SF TOTAL
LOT 12 2,653 SF (F-15-105)
P/O LOT 12 2,653 SF (F-15-105)
LOT 13 2,073 SF
LOT 14 20,443 SF 22,272 SF TOTAL
LOT 15 20,940 SF 22,297 SF TOTAL
LOT 16 20,065 SF 21,148 SF TOTAL
LOT 17 20,143 SF 20,817 SF TOTAL
P/O LOT 13 (F-15-105)
EX. 30' PUBLIC SEWER, WATER, & UTILITY EASEMENT (PLAT 22836)
VARIABLE WIDTH PRIVATE USE-IN-COMMON ACCESS EASEMENT FOR LOTS 9–17 (PLAT 22836) (TO BE ABANDONED)
EX. VARIABLE WIDTH PRIVATE USE-IN-COMMON ACCESS EASEMENT FOR LOTS 9–17 (PLAT 22836)
EX. PUBLIC SEWER & UTILITY EASEMENT PLAT MDR 9987
EXISTING 12' PRIVATE R/W L.8295 F.433
CHRIST MEMORIAL PRESBYTERIAN, INC TM 36 PARCEL 54 L. 5239 F. 655
CHRIST MEMORIAL PRESBYTERIAN, INC LOT 12
CHARLES W. EASTER TM 36 PARCEL 483 L. 14201 F. 483 1.47 AC USE: RESIDENTIAL ZONED: R-20
CHARLES I. AHN KYONG SOOK AHN TM 36 PARCEL 55 L. 12459 F. 213 31,973 SF USE: RESIDENTIAL ZONED: R-20
DAVID N. ELLIOTT JASMIN D. ELLIOTT TM 36 PARCEL 941 L. 25147 F. 268 LOT 1 20,005 SF USE: RESIDENTIAL ZONED: R-20
THOMAS E. SMITH EVA MAY E. SMITH TM 36 PARCEL 20 L. 21957 F. 138 PLAT 17258 21,403 SF USE: RESIDENTIAL ZONED: R-20
DAVID N. ELLIOTT JASMIN D. ELLIOTT TM 36 PARCEL 55 L. 23914 F. 432 LOT 2 21,453 SF USE: RESIDENTIAL ZONED: R-20
RANDOLPH J. OSTLIE CAROLYN R. OSTLIE TM 36 PARCEL 56 ARROWHEAD L. 837 F. 600 LOT 4 21,959 SF USE: RESIDENTIAL ZONED: R-20 FARM
CAROLYN B. EDWARDS BRANDON D. FREEMAN TM 36 PARCEL 233 ARROWHEAD L. 10163 F. 692 LOT 5 20,051 SF USE: RESIDENTIAL ZONED: R-20
JERRY A. TESTON &WF TM 36 PARCEL 225 ARROWHEAD L. 3948 F. 603 LOT 7 20,017 SF USE: RESIDENTIAL ZONED: R-20
CHRISTOPHER R. LONG THERESA E. LONG TM 36 PARCEL 229 ARROWHEAD L. 3948 F. 603 LOT 8 20,017 SF USE: RESIDENTIAL ZONED: R-20
COLUMBIA PIKE MD ROUTE 29 PROPERTY LINES BEFORE WIDENING
COLUMBIA PIKE MD ROUTE 29 PROPERTY LINES AFTER WIDENING
SHANGER DR
EX. 24" WATER MAIN
EX. 8" SEWER MAIN
EX. 12" WATER MAIN
EX. 8" SEWER MAIN
EX. 8" WATER MAIN
EX. 6" WATER MAIN
EX. 6" SEWER MAIN
EX. 10" WATER MAIN
EX. 8" WATER MAIN
EX. 12" WATER MAIN
EX. 8" SEWER MAIN
EX. 6" SEWER MAIN
EX. 8" WATER MAIN
EX. 6

Maryland State Grid Meridian
E 1349850
N 555600
E 1350700
N 555600
E 1349850
N 555050
PERIMETER-1 TYPE 'A' BUFFER 699 LF
PERIMETER-2 TYPE 'A' BUFFER 264 LF
PERIMETER-3 TYPE 'A' BUFFER 136 LF
PERIMETER-4 TYPE 'A' BUFFER 231 LF
PERIMETER-5 TYPE 'A' BUFFER 165 LF
PERIMETER-6 TYPE 'A' BUFFER 241 LF
PERIMETER-7 TYPE 'A' BUFFER 223 LF
CREDIT-103 LF EX. VEGETATION
CREDIT-26 LF EX. VEGETATION
CREDIT-28 LF EX. VEGETATION
CREDIT-50 LF EX. VEGETATION
CREDIT-264 LF EX. VEGETATION
CREDIT-105 LF EX. VEGETATION
CREDIT-36 LF EX. VEGETATION
CREDIT-50 LF EX. VEGETATION
LOT 9 20,820 SF 5JV
LOT 10 20,000 SF 10 SFA
LOT 11 20,375 SF 21,490 SF TOTAL
LOT 12 2,053 SF (F-15-105)
LOT 13 20,949 SF 22,297 SF TOTAL
LOT 14 20,949 SF 22,297 SF TOTAL
LOT 15 20,949 SF 22,297 SF TOTAL
LOT 16 20,065 SF 21,148 SF TOTAL
LOT 17 20,153 SF 20,875 SF TOTAL
P/O LOT 12 2,073 SF (F-15-105)
VARIABLE WIDTH PRIVATE USE-IN-COMMON ACCESS EASEMENT FOR LOTS 9-17 (PLAT 22836)
EX. VARIABLE WIDTH PRIVATE USE-IN-COMMON ACCESS EASEMENT FOR LOTS 1-7 (PLAT 22836) (TO BE ABANDONED)
30' PUBLIC SEWER, WATER, & UTILITY EASEMENT (PLAT 22836)
EX. PUBLIC SEWER & UTILITY EASEMENT PLAT MDR 9987
JUSTICE PLACE
SHAKER DR.
COLUMBIA PIKE MD ROUTE 29
N81°04'31"W 224.34'
N08°41'35"E 189.76'
N45°41'29"W 164.62'
N08°45'09"E 132.04'
N53°03'51"W 135.16'
N53°47'52"W 263.66'
N08°45'09"E 132.04'
BG&E GREEN ZONE
BG&E YELLOW ZONE
EX. HOUSE
EX. SHED
EX. GARAGE
EX. FENCE
EX. TREE LINE
EX. WETLAND
EX. WETLAND BUFFER
EX. STEEP SLOPES
EX. MODERATE SLOPES
EX. WOODS TO REMAIN
EX. WOODS TO BE REMOVED
PROP. 10' WATER
PROP. 8" SEWER
PROP. 12" STORM DRAIN
PROP. INLET
PROP. MANHOLE
PROP. SWM POND
PROP. SWM FACILITY
PROP. SWM OUTFALL
PROP. SWM ACCESS
PROP. SWM FENCE
PROP. SWM GRADING
PROP. SWM LANDSCAPING
PROP. SWM SIGN
PROP. SWM SAFETY BENCH
PROP. SWM TREE PLANTING
PROP. SWM SHRUB PLANTING
PROP. SWM SEEDING
PROP. SWM SODDING
PROP. SWM RIP-RAP
PROP. SWM STONE
PROP. SWM STONE FILTER
PROP. SWM STONE FILTER OUTLET
PROP. SWM STONE FILTER INLET



RAIN GARDEN #1 - PLANTING DETAIL
SCALE: 1"=10'

RAIN GARDEN #1 PLANTING SCHEDULE				
	QTY	BOTANICAL NAME/COMMON NAME	SIZE	REMARKS
VT	2	VIBURNUM TRILOBUM AMERICAN HIGHBUSH CRANBERRY	5 GALLON	CONT
IG	2	ILEX GLABRA "COMPACTA" COMPACT INKBERRY	3 GALLON	CONT
LB	2	LINDEN BENZOIN SPICEBUSH	3 GALLON	CONT
	8	CONVALLANRIA MAJALIS LILY-OF-THE-VALLEY	1 QT.	12" O.C.
	8	ACORUS GRAMINEUS 'OGON' GOLDEN VARIEGATED SWEET FLAG	1 QT.	12" O.C.

79 SF X 75% X .0229 STEMS PER SQUARE FOOT = 2 PLANTS REQUIRED
2 PROVIDED



RAIN GARDEN #2 - PLANTING DETAIL
SCALE: 1"=10'

RAIN GARDEN #2 PLANTING SCHEDULE				
	QTY	BOTANICAL NAME/COMMON NAME	SIZE	REMARKS
VT	2	VIBURNUM TRILOBUM AMERICAN HIGHBUSH CRANBERRY	5 GALLON	CONT
IG	2	ILEX GLABRA "COMPACTA" COMPACT INKBERRY	3 GALLON	CONT
LB	2	LINDEN BENZOIN SPICEBUSH	3 GALLON	CONT
	12	CONVALLANRIA MAJALIS LILY-OF-THE-VALLEY	1 QT.	12" O.C.
	12	ACORUS GRAMINEUS 'OGON' GOLDEN VARIEGATED SWEET FLAG	1 QT.	12" O.C.

118 SF X 75% X .0229 STEMS PER SQUARE FOOT = 2 PLANTS REQUIRED
2 PROVIDED



RAIN GARDEN #3 - PLANTING DETAIL
SCALE: 1"=10'

RAIN GARDEN #3 PLANTING SCHEDULE				
	QTY	BOTANICAL NAME/COMMON NAME	SIZE	REMARKS
VT	2	VIBURNUM TRILOBUM AMERICAN HIGHBUSH CRANBERRY	5 GALLON	CONT
IG	2	ILEX GLABRA "COMPACTA" COMPACT INKBERRY	3 GALLON	CONT
LB	2	LINDEN BENZOIN SPICEBUSH	3 GALLON	CONT
	12	CONVALLANRIA MAJALIS LILY-OF-THE-VALLEY	1 QT.	12" O.C.
	12	ACORUS GRAMINEUS 'OGON' GOLDEN VARIEGATED SWEET FLAG	1 QT.	12" O.C.

140 SF X 75% X .0229 STEMS PER SQUARE FOOT = 3 PLANTS REQUIRED
3 PROVIDED



RAIN GARDEN #4 - PLANTING DETAIL
SCALE: 1"=10'

RAIN GARDEN #4 PLANTING SCHEDULE				
	QTY	BOTANICAL NAME/COMMON NAME	SIZE	REMARKS
VT	2	VIBURNUM TRILOBUM AMERICAN HIGHBUSH CRANBERRY	5 GALLON	CONT
IG	2	ILEX GLABRA "COMPACTA" COMPACT INKBERRY	3 GALLON	CONT
LB	2	LINDEN BENZOIN SPICEBUSH	3 GALLON	CONT
	10	CONVALLANRIA MAJALIS LILY-OF-THE-VALLEY	1 QT.	12" O.C.
	10	ACORUS GRAMINEUS 'OGON' GOLDEN VARIEGATED SWEET FLAG	1 QT.	12" O.C.

100 SF X 75% X .0229 STEMS PER SQUARE FOOT = 2 PLANTS REQUIRED
2 PROVIDED



RAIN GARDEN #5 - PLANTING DETAIL
SCALE: 1"=10'

RAIN GARDEN #5 PLANTING SCHEDULE				
	QTY	BOTANICAL NAME/COMMON NAME	SIZE	REMARKS
VT	2	VIBURNUM TRILOBUM AMERICAN HIGHBUSH CRANBERRY	5 GALLON	CONT
IG	2	ILEX GLABRA "COMPACTA" COMPACT INKBERRY	3 GALLON	CONT
LB	2	LINDEN BENZOIN SPICEBUSH	3 GALLON	CONT
	8	CONVALLANRIA MAJALIS LILY-OF-THE-VALLEY	1 QT.	12" O.C.
	8	ACORUS GRAMINEUS 'OGON' GOLDEN VARIEGATED SWEET FLAG	1 QT.	12" O.C.

79 SF X 75% X .0229 STEMS PER SQUARE FOOT = 2 PLANTS REQUIRED
2 PROVIDED



RAIN GARDEN #6 - PLANTING DETAIL
SCALE: 1"=10'

RAIN GARDEN #6 PLANTING SCHEDULE				
	QTY	BOTANICAL NAME/COMMON NAME	SIZE	REMARKS
VT	2	VIBURNUM TRILOBUM AMERICAN HIGHBUSH CRANBERRY	5 GALLON	CONT
IG	2	ILEX GLABRA "COMPACTA" COMPACT INKBERRY	3 GALLON	CONT
LB	2	LINDEN BENZOIN SPICEBUSH	3 GALLON	CONT
	8	CONVALLANRIA MAJALIS LILY-OF-THE-VALLEY	1 QT.	12" O.C.
	8	ACORUS GRAMINEUS 'OGON' GOLDEN VARIEGATED SWEET FLAG	1 QT.	12" O.C.

79 SF X 75% X .0229 STEMS PER SQUARE FOOT = 2 PLANTS REQUIRED
2 PROVIDED



RAIN GARDEN #7 - PLANTING DETAIL
SCALE: 1"=10'

RAIN GARDEN #7 PLANTING SCHEDULE				
	QTY	BOTANICAL NAME/COMMON NAME	SIZE	REMARKS
VT	2	VIBURNUM TRILOBUM AMERICAN HIGHBUSH CRANBERRY	5 GALLON	CONT
IG	2	ILEX GLABRA "COMPACTA" COMPACT INKBERRY	3 GALLON	CONT
LB	2	LINDEN BENZOIN SPICEBUSH	3 GALLON	CONT
	10	CONVALLANRIA MAJALIS LILY-OF-THE-VALLEY	1 QT.	12" O.C.
	10	ACORUS GRAMINEUS 'OGON' GOLDEN VARIEGATED SWEET FLAG	1 QT.	12" O.C.

95 SF X 75% X .0229 STEMS PER SQUARE FOOT = 2 PLANTS REQUIRED
2 PROVIDED



RAIN GARDEN #8 - PLANTING DETAIL
SCALE: 1"=10'

RAIN GARDEN #8 PLANTING SCHEDULE				
	QTY	BOTANICAL NAME/COMMON NAME	SIZE	REMARKS
VT	2	VIBURNUM TRILOBUM AMERICAN HIGHBUSH CRANBERRY	5 GALLON	CONT
IG	2	ILEX GLABRA "COMPACTA" COMPACT INKBERRY	3 GALLON	CONT
LB	2	LINDEN BENZOIN SPICEBUSH	3 GALLON	CONT
	10	CONVALLANRIA MAJALIS LILY-OF-THE-VALLEY	1 QT.	12" O.C.
	10	ACORUS GRAMINEUS 'OGON' GOLDEN VARIEGATED SWEET FLAG	1 QT.	12" O.C.

95 SF X 75% X .0229 STEMS PER SQUARE FOOT = 2 PLANTS REQUIRED
2 PROVIDED

"RAIN GARDEN" PLANTING SCHEDULE NOTES:

1. ALL PLANT MATERIALS SHALL BE FULL AND HEAVY, BE WELL FORMED AND SYMMETRICAL, CONFORM TO THE MOST CURRENT AAN SPECIFICATIONS AND BE INSTALLED IN ACCORDANCE WITH HOWARD COUNTY PLANTING SPECIFICATIONS.
2. CONTRACTOR SHALL VERIFY LOCATION OF ALL UNDERGROUND UTILITIES PRIOR TO DIGGING.
3. FINAL LOCATION OF PLANT MATERIAL MAY NEED TO VARY TO MEET FINAL FIELD CONDITIONS. TREES SHALL NOT BE PLANTED IN THE BOTTOM OF DRAINAGE SWALES.
4. CONTRACTOR SHALL VERIFY PLANT QUANTITIES PRIOR TO BIDDING. IF PLAN DIFFERS FROM LANDSCAPE SCHEDULE, THE PLAN SHALL GOVERN.
5. RAIN GARDEN AREAS ARE TO BE PLANTED BASED ON A MINIMUM DENSITY OF 1000 STEMS PER PLANTED ACRE (.0229 STEMS PER SQUARE FOOT). ABOVE PLANTING RATIOS ARE TO BE APPLIED TO THE AREAS PROVIDED IN THE ESDv SUMMARY.
6. FILTER AREA SHALL BE 50% COVERED BY PLANTINGS AT FULL GROWTH

APPROVED: HOWARD COUNTY DEPARTMENT OF PLANNING AND ZONING

CHIEF, DEVELOPMENT ENGINEERING DIVISION	DATE 10.30.14
CHIEF, DIVISION OF LAND DEVELOPMENT	DATE 10-31-14
DIRECTOR	DATE 10/31/14

SCALE 1"=10'
5' 0' 10'

NOTE:
SEE SHEET 6 FOR RAIN GARDEN SECTION DETAIL.

OWNER
MARY THERESE PFAU
3675 PARK AVE., SUITE 301
ELLICOTT CITY, MD 21043
(410) 480-0023

DEVELOPER
TRINITY QUALITY HOMES, INC.
3675 PARK AVE., SUITE 301
ELLICOTT CITY, MD 21043
(410) 480-0023

NO.	REVISION	DATE
1	REVISE PLAN PER LAYOUT ON F-15-105	11-12-15

SITE DEVELOPMENT PLAN
RAIN GARDEN PLANTING DETAILS
STELLA GLEN
LOTS 9-11 & 14-17 (FORMERLY LOTS 1-7) AND P/O LOTS 8,12,& 18 (F-15-105)
RESIDENTIAL - SINGLE FAMILY DETACHED

TAX MAP: 36 GRID: 19 ZONED: R-20
6TH ELECTION DISTRICT
DPZ REF'S: ECP-13-024, CONT.#24-3108, PARCELS: 57, 58 & 417; L.8293 / F.433
WP-13-138, SP-13-009 & F-14-049, F-15-105 HOWARD COUNTY, MARYLAND

ROBERT H. VOGEL ENGINEERING, INC.
ENGINEERS • SURVEYORS • PLANNERS
8407 MAIN STREET ELLICOTT CITY, MD 21043
TEL: 410.461.7666 FAX: 410.461.8961

STATE OF MARYLAND — ROBERT HARRIS VOGEL — No. 16193 — PROFESSIONAL ENGINEER — 10/30/14
ROBERT H. VOGEL, PE No.16193

DESIGN BY: RHV
DRAWN BY: JMR/GAH
CHECKED BY: RHV
DATE: SEPTEMBER 2014
SCALE: AS SHOWN
W.O. NO.: 12-23

PROFESSIONAL CERTIFICATE
I HEREBY CERTIFY THAT THESE DOCUMENTS WERE PREPARED OR APPROVED BY ME, AND THAT I AM A DULY LICENSED PROFESSIONAL ENGINEER UNDER THE LAWS OF THE STATE OF MARYLAND, LICENSE NO. 16193 EXPIRATION DATE: 09-27-2014

SHEET 8 OF 8

SDP-14-070

K:\Projects\12-23\ENGR\dwg\SDP\GN_MICRO PLANTING.dwg, 9/15/2014 1:27:03 PM