- UNLESS WAIVERS HAVE BEEN APPROVED. THE EXISTING TOPOGRAPHY SHOWN HEREON IS BASED ON A TOPOGRAPHIC SURVEY PREPARED BY ROBERT H. VOGEL ENGINEERING, INC., PERFORMED IN JUNE, 2018.
- OFFSITE TOPOGRAPHY FROM HOWARD COUNTY GIS.

 3. THE PROJECT BOUNDARY IS BASED ON A BOUNDARY SURVEY PREPARED BY ROBERT H. VOGEL ENGINEERING, INC., DATED MAY, 2018.

 4. THE COORDINATES SHOWN HEREON ARE BASED UPON THE HOWARD COUNTY GEODETIC
- CONTROL WHICH IS BASED UPON THE MARYLAND STATE PLANE COORDINATE SYSTEM HOWARD COUNTY MONUMENT NOS. 17GA AND 17GB WERE USED FOR THIS PROJECT THE SUBJECT PROPERTY IS ZONED "R-20" IN ACCORDANCE WITH THE OCTOBER 6, 2013
- THIS PROPERTY IS LOCATED WITHIN THE METROPOLITAN DISTRICT. PUBLIC WATER IS PROVIDED BY CONTRACT 71-W. PUBLIC SEWER IS PROVIDED BY THERE IS A 100-YEAR FLOODPLAIN WHICH CROSSES THROUGH THE PROPERTY WEST OF THE DEVELOPABLE AREA. THE FLOOPLAIN IS SHOWN ON THESE PLANS IS PER THE MAY
- 6, 2013 FEMA DIGITAL FLOOD INSURANCE RATE MAP (DFIRM). THERE ARE NO STEEP SLOPES OVER 25% WITH A CONTIGUOUS AREA OF 20,000SF LOCATED ONSITE.

 O. WETLANDS DELINEATION AND FOREST STAND DELINEATION REPORT PREPARED BY ECO—SCIENCE PROFESSIONALS, INC. ON SEPTEMBER 10, 2018.

 1. THERE ARE NO WETLANDS OR STREAMS WITHIN THE LOD. IN ACCORDANCE WITH SECTION
- 16.116(c) OF THE HOWARD COUNTY SUBDIVISIONS AND LAND DEVELOPMENT REGULATIONS A "NECESSARY DISTURBANCE" FOR STORM DRAIN OUTFALL AND SEWER CONSTRUCTION IN THE STREAM BUFFER WILL BE SUBMITTED AT A LATER PLAN STAGE.

 2. FOREST CONSERVATION OBLIGATIONS FOR THIS PROJECT SHALL BE ADDRESSED BY A FOREST CONSERVATION PLAN SUBMITTED WITH THE SUBDIVISION OR SITE DEVELOPMENT
- GERMAN ROAD IS CLASSIFIED AS A LOCAL ROAD.

 TO THE BEST OF THE OWNERS KNOWLEDGE, THERE ARE NO BURIAL GROUNDS OR CEMETERIES ON THIS PROPERTY. THERE ARE NO HISTORIC HOUSES LOCATED ON THIS STORMWATER MANAGEMENT FOR THE PROJECT IS PROVIDED BY NINE
- MICRO-BIORETENTION FACILITIES (M-6) AND 26 DRY WELL FACILITIES (M-5). THESE FACILITIES SHALL BE PRIVATELY OWNED AND MAINTAINED, EXCEPT FOR MICRO-BIORETENTION FACILITY NUMBER 8, WHICH SHALL BE PUBLICLY OWNED AND
- THE LIMITS OF DISTURBANCE (LOD) SHOWN ON THE PLAN IS ENTIRELY ON THE SITE. APPROVAL OF THIS ENVIRONMÈNTAL CONCEPT PLAN (ECP) DOES NOT CONSTITUTE AN APPROVAL OF ANY SUBSEQUENT AND ASSOCIATED SUBDIVISION PLAN/PLAT AND/OR SITI DEVELOPMENT PLAN AND/OR REDLINE REVISION PLAN. REVIEW OF THIS PROJECT FOR COMPLIANCE WITH THE HOWARD COUNTY SUBDIVISION AND LAND DEVELOPMENT REGULATIONS AND THE HOWARD COUNTY ZONING REGULATIONS SHALL OCCUR AT THE SUBDIVISION PLAN/PLAT AND/OR SITE DEVELOPMENT PLAN AND/OR REDLINE REVISION PROCESS. THE APPLICANT AND CONSULTANT SHOULD EXPECT ADDITIONAL AND MORE DETAILED REVIEW COMMENTS (INCLUDING COMMENTS THAT MAY ALTER THE OVERALL SI
- DESIGN) AS THIS PROJECT PROGRESSES THROUGH THE PLAN REVIEW PROCESS. APPROVAL OF THIS ENVIRONMENTAL CONCEPT PLAN (ECP) BY THE HOWARD SOIL CONSERVATION DISTRICT DOES NOT GRANT APPROVAL OF THE PROPOSED SEDIMENT CONTROL SCHEME. THE FINAL PLAN SHALL INCLUDE A SEQUENCE OF CONSTRUCTION WHICH SHALL DETAIL SEDIMENT & EROSION CONTROLS AND PHASING AND ADDRESS THI PROJECT TEMPORARY STORMWATER MANAGEMENT REQUIREMENTS.

ENVIRONMENTAL SITE DESIGN NARRATIVE:

THE ENVIRONMENTAL AREAS FOR THIS SITE ARE LOCATED IN THE SOUTH AND WEST PORTION OF THE SITE INCLUDING PERENNIAL STREAMS AND NON-TIDAL WETLANDS. THERE I A MINOR DISTURBANCE TO THE STREAM BUFFER REQUIRED FOR STORM DRAIN OUTFALL CONSTRUCTION AND A DISTURBANCE ASSOCIATED WITH SEWER CONSTRUCTION TO THE FLOODPLAIN AND STREAM BUFFER. THESE ARE CONSIDERED "NECESSARY DISTURBANCES" OUTLINED IN SECTION 16.116(c) OF THE HOWARD COUNTY SUBDIVISION AND LAND DEVELOPMENT REGULATIONS. THERE IS APPROXIMATELY 0.8 AC. OF FOREST LOCATED WITHIN THE NET TRACT AREA. DISTURBANCES TO ENVIRONMENTAL FEATURES AND NATURAL RESOURCES WILL BE MINIMIZED TO THE GREATEST EXTENT POSSIBLE.

2. THE SITE NATURALLY SLOPES FROM NORTHEAST TO SOUTHEAST. THE SITE HAS BEEN DESIGNED TO MAINTAIN THE NATURAL DRAINAGE PATTERNS, WITH NO DRAMATIC CHANGES TO

3. THE CONCEPTUAL REDUCTION IN IMPERVIOUS AREA THROUGH BETTER SITE DESIGN IS ACHIEVED THROUGH THE ENVIRONMENTAL SITE DESIGN (ESD) FOR THE PROJECT TO THE MAXIMUM EXTENT PRACTICABLE (MEP). THE RESULTS OF THE ENVIRONMENTAL SITE DESIGN FOR THIS PROJECT WILL REFLECT "WOODS IN GOOD CONDITION". THE ESD CONCEPT INCLUDES THE USE OF MICRO-BIORETENTION FACILITIES (M-6) AND DRYWELLS (M-5).

SEDIMENT CONTROL FOR THIS SPECIFIC SITE PLAN WILL BE PROVIDED THROUGH THE US OF A PROPOSED STONE OUTLET SEDIMENT TRAP, FARTH DIKE, CLEAR WATER DIKE, AND SUPER SILT FENCE PERIMETER CONTROLS. SEDIMENT CONTROL SHALL BE IN ACCORDANCE WITH CURRENT REQUIREMENTS AND SHALL BE APPROVED BY THE HOWARD SOIL CONSERVATION DISTRICT DURING THE FUTURE SITE DEVELOPMENT PLAN PHASE OF THE

5. STORMWATER MANAGEMENT FOR THE PROJECT SHALL BE MET THROUGH THE USE OF MICRO-BIORETENTION FACILITIES (M-6) AND DRYWELLS (M-5). THE PROPOSED PRACTICES HAVE BEEN MAXIMIZED TO THE EXTENT PRACTICAL. THE CALCULATED RAINFALL TARGET (PE) FOR THIS PROJECT IS 1.59", AND THE TOTAL RUNOFF VOLUME (ESDv) REQUIRED IS 5,359

6. AN ALTERNATIVE COMPLIANCE REQUEST FOR REMOVAL OF SPECIMEN TREES IS REQUIRED IN ORDER FOR THE PROPOSED DESIGN TO BE DEVELOPED, SUBMISSION OF THE ALTERNATIVE COMPLIANCE REQUEST WILL OCCUR AT THE SKETCH PLAN STAGE, SIGNIFICANT DESIGN CHANGES MAY OCCUR BASED ON THE REVIEW OF THE SKETCH PLAN AND THE ALTERNATIVE COMPLIANCE REQUEST.

PRESENT ZONING: R-20

LOCATION: ELLICOTT CITY, MD.; TAX MAP 17, BLOCK 20, PARCEL 0385 2ND ELECTION DISTRICT

- PROJECT AREA: 7.54 AC. DPZ REFERENCES: L.314/F.315 & L.343/F.316 USE OF STRUCTURES: RESIDENTIAL
- TOTAL BUILDING COVERAGE: 15,045 SF (0.5 AC. OR 4.58% OF GROSS AREA) PAVED AREA ON SITE: 22,537 SF (0.52 AC. OR 6.86% OF GROSS AREA) LIMIT OF DISTURBED AREA: 3.43 AC WETLANDS WITHIN LOD: 0.00 AC.
- WETLAND BUFFERS WITHIN LOD: 0.00 AC. STREAMS AND THEIR BUFFERS WITHIN LOD: 0.04 AC
- AREA OF ON-SITE 100 YEAR FLOODPLAIN: 2.1 AC AREA OF ON-SITE 100 YEAR FLOODPLAIN WITHIN LOD: 0.02 AC AREA OF EXISTING FOREST ON-SITE: 1.8 AC
- AREA OF EXISTING FOREST WITHIN LOD: 0,00 AC. AREA OF ON-SITE NCRS/MDE/HSCD STEEP SLOPES (20% OR GREATER): 0.81 AC AREA OF ON-SITE STEEP SLOPES (25% OR GREATER): 0.13 AC
- AREA OF ERODIBLE SOILS: 5.06 AC. AREA MANAGED BY ESDV (THIS PLAN): 0.91 AC.
- IMPERVIOUS AREA (MANAGED BY ESDv): 0.50 AC. GREEN AREA (MANAGED BY ESDv): 0.41 AC.


APPROVED: HOWARD COUNTY DEPARTMENT OF PLANNING AND ZONING

ENVIRONMENTAL CONCEPT PLAN RIVER BIRCH MANOR


10039 GERMAN ROAD HOWARD COUNTY, MD

BENCHMARKS

HOWARD COUNTY BENCHMARK - 17GA (CONC. MONUMENT) N 591048.52 E 1352732.11 ELEV. 432.03 LOCATION: NORTHWEST CORNER OF BETHANY LANE AND GERMAN ROAD HOWARD COUNTY BENCHMARK - 17GB (CONC. MONUMENT) N 592656.77 E 1353019.98 ELEV. 441.52



VICINITY MAP SCALE: 1"=2000'





MINIMUM LOT SIZE CHART KEY (X#) | SPECIES | SIZE (IN. DBH) CRZ (FEET RADIUS) | COMMENTS 0 SF D BE REMOVED 0 SF D BE REMOVED 290 SF | 18,006 SF | 18,000 SF 18,297 SF 717 SF 18,005 SF 18,000 SF TO REMAIN 5 19,273 SF 1,217 SF | 18,056 SF | 18,000 SF AIR CONDITION, SOME 1,628 SF | 18,042 SF | 18,000 SF TO REMAIN 6 19,670 SF DIEBACK NOTED 7 19,830 SF 1,809 SF 18,021 SF 18,000 SF GOOD CONDITION

SPECIMEN TREE CHART

46.5

46.5

SILVER MAPLE

PIN OAK

4 TULIP POPLAR


5 SILVER MAPLE

6 BLACK OAK


ESDv CONCEPT PLAN

18,003 SF | 18,000 SI

18,005 SF | 18,000 SF



SHEET INDEX DESCRIPTION SHEET NO. COVER SHEET AND ESDV CONCEPT PLAN 1 OF 2 STORMWATER MANAGEMENT DRAINAGE AREA MAP & DETAILS 2 OF 2



DESIGN BY: CHECKED BY: RHV DATE: DECEMBER 2018 SCALE: AS SHOWN W.O. NO.: 41656

3300 N. RIDGE ROAD, SUITE 110 TEL: 410.461.7666 ELLICOTT CITY, MD 21043 FAX: 410.461.8961 PROFESSIONAL CERTIFICATE

ROBERT H. VOGEL

ENGINEERING, INC.

ENGINEERS · SURVEYORS · PLANNERS

SHEET



SYMBOL NAME / DESCRIPTION GROUP | K FACTOR | ERODIBLE | ACREAGE 0.49 YES GLENVILLE-BAILE SILT LOAMS, O TO 8 PERCENT SLOPES 0.32 YES 0.43 NO 0.43 NO MANOR LOAM, 15 TO 25 PERCENT SLOPES HATBORO-CODORUS SILT LOAMS, O TO 3 PERCENT SLOPES

B 0.37 NO

SOILS NOTES 1. TAKEN FROM USDA, SCS-WEB SOIL SURVEY, HOWARD COUNTY 2. HIGHLY ERODIBLE SOILS ARE THOSE SOILS WITH A SLOPE GREATER THAN 15 PERCENT OR THOSE SOILS WITH A SOIL ERODIBILITY FACTOR K GREATER THAN 0.35 AND WITH A SLOPE GREATER THAN 5

- SILT FENCE IS TO BE REPLACED WITH SUPER SILT FENCE AT THE DIRECTION OF THE SEDIMENT CONTROL INSPECTOR. - SUPER SILT FENCE SHALL BE CURLED UPHILL NO MORE THAN 35 FEET APART. - DOUBLE ROWS OF SUPER SILT FENCE

SHALL BE INSTALLED AT THE DIRECTION OF

THE SEDIMENT CONTROL INSPECTOR.


GLENELG LOAM, 8 TO 15 PERCENT SLOPES

GLENELG LOAM, 3 TO 8 PERCENT SLOPES

APPROVED: HOWARD COUNTY DEPARTMENT OF PLANNING AND ZONING

GRADING PLAN

SCALE 1"=50' SCALE: 1"=50'



			3. THIS SITE HAS STRE										
	SITE DEVELOPABLE AREA: 3.43 AC 149453 SF TARGET Pe: 1.59 IN SITE INPERVIOUS: 24.491348 PERCENT SITE RV: 0.2704 SITE ESDV: 5359 CF 4/-									ON THE PROPERTY. BUFFERS CONSTRIAIN SOUTH.			
Rv=0.05+0.009X													LAYOUT OPTION 1
DA g	% IMPERV	Rv	DA (SF)	DA (AC)	MINIMUM VOLUME	MAXIMUM VOLUME	1.59" VOLUME	VOLUME PROVIDED*	IMPERV (SF)	IMPERV (AC)	GREEN	REMARKS	INSIGE TRENCH AREA ONLY OGSERANTA CLEANCY GETALS 11
LOT 1 DA# 1 DRIVEWAY & 1/4 HOUSE	22.60	0.2534	6429	0.15	136	353	219	CS.	1453	0.03	0.11	MICROSCALE MICRO-BIO RETENTION (M-6) 154 115.25 SF MUICH AREA	10' MIN
LOT 1 DA# 2 HOUSE	100,00	0.9500	1057	0.04	130	V. L		To the state of th	26 G G	0.64	0.00	D <u>Dywell 3 @ 5 Wy551x3 D</u> 360 120 CF EA	DOWNSPOUT
DA #3 ROW	85.99	0.8239	11634	0.27	799	2077	1285	1 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	10004	0.23	0.04	MICROSCALE MICRO-BIO RETENTION (M-5) 925 69S SF MUICH AREA	SOLD PVC TO OTHER DOWNSPOUT LOCATIONS. EXACT LUTOUT WARES. SEE HOUSE PLANS. NO SEE PLAN I PERFORATED PRE EVIC SCH NO 3/8" NOLES 4" O/C SO DEGREES ANOUND TYPICAL DOW
LOT 2 DA# 4 DRIVEWAY	31.98	0.3378	4025	0.09	P 4 P P P P P P P P P P P P P P P P P P	295	182	general 294	1287	0.03	0.06	MICROSCALE MICRO-BIO RETENTION (M-6) 294 222 SF MULCH AREA	
LOT 2 DA# 5 HOUSE	100.00	0.9500	2090	0.05	170	The second secon	892	And the state of t	2 (54)	0.05	0.00	Drowell 4@ 5'Wx51x3'D 480 120 CF EA	PVC DOWNERS WY REMOVES
LOT 3 DA# 6 DRIVEWAY	11.20	0.1508	6391	0.15	80	209	129	CONTRACTOR BETTER B	715	0.02	0.13	MICROSCALE MICRO-BIO RETENTION (M-6) 320 240 SF MULCH AREA	SPLASH BL
LOT 3 DA# 7 HOUSE	100,00	0.9500	250	0.05	170			4.24	2.5.50	0.05	0.00	Drywell	LEAF SCREEN
LOT 4 DAS 8 DRIVEWAY	35.18	0.3666	5847	0.13	179	454	282	and the desired and the second and t	2057	9.65	0.09	MICROSCALE MICRO-BIO RETENTION (M-6) 210 158 SF MULCH AREA	(IE RECOUNCE)
LOT 4 DA# 9 HOUSE	100.00	0.9500	2:50	0.05	170		38	manufacture and a construction of the construc	7 x 7 x 1	0.05	0.00	Drywell	FVC BUILDING COUPLING
LOT 5 DAM 10 DRIVEWAY	32.57	0.3431	3712	0.09	106	276	171	Programmanumations	1209	0.03	0.06	MICROSCALE MICRO-BIO RETENTION (M-6) 210 158 SF MULCH AREA	12° SAND FILTER LAYER
LOT S DA# 11 HOUSE	100.00	0.9500	25%	0.05	170	e et al a probabilità discolo	<i>7</i> 0.	1 25	7195	0.65	0.00	90vweii 4 @ SVWsTx3*D 480 120 CF EA	ASTM C33 CLEM, FINE WISHED ACCRECATE SAND, ROTOTEL 1' BELOW TRENCH BOTTOM
LOT 6 DA# 12 DRIVEWAY	22.75	0.2548	4263	0.30	91	235	146	Additional and additional addit	970	0,02	0.08	MICROSCALE MICRO-BIO RETENTION (M-S) 147 110.25 SF MULCH AREA	NOTES I, MANUFACTURED SAND IS NOT ACCEPTABLE IN
LOT 6 DA# 13 HOUSE	100.00	0.9500	2357	0.05	170		The state of the s		2338	0.05	0.00	Drywell	DETWELLS SHOULD BE SON 40 PVC 4" MIN X 1/2" 3. DITWELLS MUST BE A MINNEM OF STELL FOOT -10" FROM BULDING FOUNDMENT PLATE -00" FROM SPECE FELLO -00" FROM SPECE FELLO
LOT 7 DA# 14 DRIVEWAY	49.54	0.4959	2935	0.07	121	335	195	C C C	2454	0.03	0.03	MICROSCALE MICRO-BIO RETENTION (M-6) 330 247.5 SF MUICH AREA	-55 PROW WELL LOCATION AND SHOULD BE LOCATION DIMENSIZE ANY BASEMENT SEPPRE. 4. HISSUEN HUMBER OF PERFORATIONS SHALL BE 5 TIMES PERFORATION.
LOT 7 DA# 15 HOUSE	24.30	0.9500	2750	0.05	170	479	297	200.	250	0.05	0.00	Drywell 1@5"Wx51x3"D	5. THEMEN MAY NOT BE INSTALLED IN FILL HOWARD County, Maryland
DRIVEWAY	24.30	15.2087	25729	3	185	77 77 77 77 77 77 77 77 77 77 77 77 77	231		ESSET.	0.05	U.19	MHL ROSCALE WILLEN LEW REIEN ROW IN-ES 434 325 SF MULCH AREA	Department of Public Works
TOTALS	52.5	and the second	68001	1.56			<u> </u>	5890	35686	0.82	0.74		Approved Chief, Burnou of Engineering

ANY SUBSEQUENT AND ASSOCIATED BUILDING AND/OR GRADING

2. REVIEW OF THIS PLAN FOR COMPLETE COMPLIANCE WITH ZONING AND SUBDIVISION AND LAND DEVELOPMENT REGULATIONS SHALL OCCUR AT THE SITE DEVELOPMENT STAGE AND THEREFORE, THIS PLAN IS SUBJECT TO ADDITIONAL AND MORE DETAILED COMMENTS AS THE PLAN PROGRESSES THROUGH THE SITE DEVELOPMENT

3. THIS SITE HAS STREAMS, WETLANDS, AND A 100YR FLOODPLAIN ON THE PROPERTY. THESE FEATURES AND THEIR ASSOCIATED BUFFERS CONSTRIAIN THE DEVELOPABLE AREA ON THE WEST AND

ERFORATED PVC INSIDE TRENCH AREA ONLY

OBSERVATION WELL

/ CLEANOUT, SEE

DETAILS THIS SHEET

PVC WYE TO SPLASH BLOCK

PVC P/PE PVC P/PE

GROUND WATER 6" PVC COUPLING


Roof Drain

LAYOUT OPTION 2


-08SERVATION WELL / CLEANOR SELF FLUSH WITH PROPOSED EXISTING GRADE

D-9.01

10. WW



Martin B. Covington III, PE ORIGINALLY EFFECTIVE APRIL, 2006 REVISED MARCH 19, 2006 DISTRIBUTED AT C.C. SURVEYORS MTG



APPENDIX B.4.C SPECIFICATIONS FOR MICRO-BIORETENTION. RAIN GARDEN, LANDSCAPE INFILTRATION &

THE SOIL SHALL BE A UNIFORM MIX, FREE OF STONES, STUMPS, ROOTS OR OTHER SIMILAR OBJECTS LARGER THAN TWO INCHES. NO OTHER

* ORGANIC CONTEN - MINIMUM 10% BY DRY WEIGHT (ASTM D 2974). IN GENERAL, THIS CAN BE MET WITH A MIXTURE OF LOAMY SAND

* PH RANGE - SHOULD BE BETWEEN 5.5 - 7.0. AMENDMENTS (E.G., LIME, IRON SULFATE PLUS SULFUR) MAY BE MIXED IN TO THE SOIL

THERE SHALL BE AT LEAST ONE SOIL TEST PER PROJECT. EACH TEST SHALL CONSIST OF BOTH THE STANDARD SOIL TEST FOR PH, AND ADDITIONAL TESTS OF ORGANIC MATTER, AND SOLUBLE SALTS. A TEXTURAL ANALYSIS IS REQUIRED FROM THE SITE STOCKPILED TOPSOIL. IF

POSSIBLE, USE EXCAVATION HOES TO REMOVE ORIGINAL SOIL. IF PRACTICES ARE EXCAVATED USING LOADER, THE CONTRACTOR SHOULD USE WIDE TRACK OR MARSH TRACK EQUIPMENT, OR LIGHT EQUIPMENT WITH TURF TYPE TIRES. USE OF EQUIPMENT WITH NARROW TRACKS OR

NARROW TIRES, RUBBER TIRES WITH LARGE LUGS, OR HIGH-PRESSURE TIRES WILL CAUSE EXCESSIVE COMPACTION RESULTING IN REDUCED

COMPACTION CAN BE ALLEVIATED AT THE BASE OF THE BIORETENTION FACILITY BY USING A PRIMARY TILLING OPERATION SUCH AS CHISEL PLOW, RIPPER, OR SUBSOILER. THESE TILLING OPERATIONS ARE TO REFRACTURE THE SOIL PROFILE THROUGH THE 12 INCH COMPACTION ZONE. SUBSTITUTE METHODS MUST BE APPROVED BY THE ENGINEER. ROTOTILLERS TYPICALLY DO NOT TILL DEEP ENOUGH TO REDUCE THE

ROTOTILL 2 TO 3 INCHES OF SAND INTO THE BASE OF THE BIORETENION FACILITY BEFORE BACKFILLING THE OPTIONAL SAND LAYER. PUMP ANY PONDED WATER BEFORE PREPARING (ROTOTILLING) BASE. WHEN BACKFILLING THE TOPSOIL OVER THE SAND LAYER, FIRST PLACE 3 TO 4 INCHES OF TOPSOIL OVER THE SAND, THEN ROTOTILL THE SAND/TOPSOIL TO CREATE A GRADATION ZONE. BACKFILL THE REMAINDER OF THE

TOPSOIL TO FINAL GRADE. WHEN BACKFILLING THE BIORETENTION FACILITY, PLACE SOIL IN LIFTS 12" TO 18". DO NOT USE HEAVY EQUIPMENT WITHIN THE BIORETENTION BASIN. HEAVY EQUIPMENT CAN BE USED AROUND THE PERIMETER OF THE BASIN TO SUPPLY SOILS AND SAND. GRADE BIORETENTION MATERIALS WITH LIGHT EQUIPMENT SUCH AS A COMPACT LOADER OR A DOZER/LOADER WITH MARSH TRACKS.

COMPOST IS A BETTER ORGANIC MATERIAL SOURCE, IS LESS LIKELY TO FLOAT, AND SHOULD BE PLACED IN THE INVERT AND OTHER LOW

AREAS. MULCH SHOULD BE PLACED IN SURROUNDING TO A UNIFORM THICKNESS OF 2" TO 3". SHREDDED OR CHIPPED HARDWOOD MULCH IS

THE ONLY ACCEPTED MULCH. PINE MULCH AND WOOD CHIPS WILL FLOAT AND MOVE TO THE PERIMETER OF THE BIORETENTION AREA. DURING

ROOTSTOCK OF THE PLANT MATERIAL SHALL BE KEPT MOIST DURING TRANSPORT AND ON-SITE STORAGE. THE PLANT ROOT BALL SHOULD BE

PLANTED SO 1/8TH OF THE BALL IS ABOVE FINAL GRADE SURFACE. THE DIAMETER OF THE PLANTING PIT SHALL BE AT LEAST SIX INCHES LARGER THAN THE DIAMETER OF THE PLANTING BALL. SET AND MAINTAIN THE PLANT STRAIGHT DURING THE ENTIRE PLANTING PROCESS. THOROUGHLY WATER GROUND BED COVER AFTER INSTALLATION. TREES SHALL BE BRACED USING 2" BY 2" STAKES ONLY AS NECESSARY AND

GRASSES AND LEGUME SEED SHOULD BE DRILLED INTO THE SOIL TO A DEPTH OF AT LEAST ONE INCH. GRASS AND LEGUME PLUGS SHALL BE PLANTED FOLLOWING THE NON-GRASS GROUND COVER PLANTING SPECIFICATIONS.

THE TOPSOIL SPECIFICATIONS PROVIDE ENOUGH ORGANIC MATERIAL TO ADEQUATELY SUPPLY NUTRIENTS FROM NATURAL CYCLING. THE PRIMARY

FUNCTION OF THE BIORETENTION STRUCTURE IS TO IMPROVE WATER QUALITY. ADDING FERTILIZERS DEFEATS, OR AT A MINIMUM, IMPEDES THIS GOAL. ONLY ADD FERTILIZER IF WOOD CHIPS OR MULCH ARE USED TO AMEND THE SOIL. ROTOTILL UREA FERTILIZER AT A RATE OF 2

* PIPE - SHOULD BE 4" TO 6" DIAMETER, SLOTTED OR PERFORATED RIGID PLASTIC PIPE (ASTMF 758, TYPE PS 28, OR AASHTO-M-278)

* PERFORATIONS - IF PERFORATED PIPE IS USED, PERFORATIONS SHOULD BE 3/8" DIAMETER LOCATED 6" ON CENTER WITH A MINIMUM

* A RIGID, NON-PERFORATED OBSERVATION WELL MUST BE PROVIDED (ONE PER EVERY 1,0000 SQUARE FEET) TO PROVIDE A CLEAN-OUT

* A 4" LAYER OF PEA GRAVEL (1/8" TO 3/8" STONE) SHALL BE LOCATED BETWEEN THE FILTER MEDIA AND UNDERDRAIN TO PREVENT MIGRATION OF FINES IN TO THE UNDERDRAIN. THIS LAYER MAY BE CONSIDERED PART OF THE FILTER BED WHEN BED THICKNESS

THIS MAIN COLLECTOR PIPE FOR UNDERDRAIN SYSTEMS SHALL BE CONSTRUCTED AT A MINIMUM SLOPE OF 0.5%. OBSERVATION WELLS AND/OR

Notes

plantings are site-specific

PE Type 1 nonwoven

galvanized hardware cloth

USDA soil types loamy sand or sandy loam; clay content < 5%

Slotted or perforated pipe; 3/8" perf. @ 6" on center, 4 holes per

inderneath pipes. Perforated pipe shall be wrapped with 1/4-inch

28 day strength and slump test; all concrete design (cast-in-place

professional structural engineer licensed in the State of Maryland

design to include meeting ACI Code 350.R/89; vertical loading

standards requires design drawings sealed and approved by a

[H-10 or H-20]; allowable horizontal loading (based on soil

Sand substitutions such as Diabase and Graystone (AASHTO)

#10 are not acceptable. No calcium carbonated or dolomitic sand

substitutions are acceptable. No "rock dust" can be used for sand,

row; minimum of 3" of gravel over pipes; not necessary

or pre-cast) not using previously approved State or local

on-site testing of poured-in-place concrete required

pressures); and analysis of potential cracking

aged 6 months, minimum; no pine or wood chips

OF FOUR HOLES PER ROW. PIPE SHALL BE WRAPPED WITH A 1/4" (NO. 4 OR 4x4) GALVANIZED HARDWARE CLOTH. * GRAVEL - THE GRAVEL LAYER (NO. 57 STONE PREFERRED) SHALL BE AT LEAST 3" THICK ABOVE AND BELOW THE UNDERDRAIN.

TOPSOIL IS IMPORTED, THEN A TEXTURE ANALYSIS SHALL BE PERFORMED FOR EACH LOCATION WHERE THE TOPSOIL WAS EXCAVATED.

IT IS VERY IMPORTANT TO MINIMIZE COMPACTION OF BOTH THE BASE OF BIORETENTION PRACTICES AND THE REQUIRED BACKFILL. WHEN

MATERIALS OR SUBSTANCES SHALL BE MIXED OR DUMPED WITHIN THE MICRO-BIORETENTION PRACTICE THAT MAY BE HARMFUL TO PLANT GROWTH, OR PROVE A HINDRANCE TO THE PLANTING OR MAINTENANCE OPERATIONS. THE PLANTING SOIL SHALL BE FREE OF BERMUDA GRASS, QUACKGRASS, JOHNSON GRASS, OR OTHER NOXIOUS WEEDS AS SPECIFIED UNDER COMAR 15.08.01.05. THE PLANTING SOIL SHALL BE

(60%-65%) AND COMPOST (35% TO 40%) OR SANDY LOAM (30%), COARSE SAND (30%), AND COMPOST (40%).

THE ALLOWABLE MATERIALS TO BE USED IN THESE PRACTICES ARE DETAILED IN TABLE B.4.1.

* CLAY CONTENT - MEDIA SHALL HAVE A CLAY CONTENT OF LESS THAN 5%.

* SOIL COMPONENT - LOAMY SAND OR SANDY LOAM (USDA SOIL TEXTURAL CLASSIFICATION).

INFILTRATION RATES AND IS NOT ACCEPTABLE. COMPACTION WILL SIGNIFICANTLY CONTRIBUTE TO DESIGN FAILURE.

RECOMMENDED PLANT MATERIAL FOR MICRO-BIORETENTION PRACTICES CAN BE FOUND IN APPENDIX A, SECTION A.2.3.

FOR THE FIRST GROWING SEASON ONLY. STAKES ARE TO BE EQUALLY SPACED ON THE OUTSIDE OF THE TREE BALL.

IN A GRAVEL LAYER. THE PREFERRED MATERIAL IS SLOTTED, 4" RIGID PIPE (E.G., PVC OF HDPE).

CLEAN-OUT PIPES MUST BE PROVIDED (ONE MINIMUM PER EVERY 1000 SQUARE FEET OF SURFACE AREA).

THESE PRACTICES MAY NOT BE CONSTRUCTED UNTIL ALL CONTRIBUTING DRAINAGE AREA HAS BEEN STABILIZED.

NO. 8 OR NO. 9 (1/8" TO 3/8")

stone: 2" to 5"

NO. 57 OR NO. 6

AGGREGATE

PVC or SDR35

F 758, Type PS 28 or AASHTO 4" to 6" rigid schedule 40

A STORM EVENT AND ARE NOT ACCEPTABLE. SHREDDED MULCH MUST BE WELL AGED (6 TO 12 MONTHS) FOR ACCEPTANCE.

1. MATERIAL SPECIFICATIONS

2. FILTERING MEDIA OR PLANTING SOIL

TESTED AND SHALL MEET THE FOLLOWING CRITERIA:

TO INCREASE OR DECREASE PH.

EFFECTS OF COMPACTION FROM HEAVY EQUIPMENT

4. PLANT MATERIAL

POUNDS PER 1000 SQUARE FEET.

UNDERDRAINS SHOULD MEET THE FOLLOWING CRITERIA:

Specification

see Appendix A, Table A.4

loamy sand (60 - 65%) &

Min. 10% by dry weight

pea gravel: ASTM-D-448

ornamental stone: washed

MSHA Mix No. 3; $f'_c = 3500$

AASHTO-M-6 or ASTM-C-33 | 0.02" to 0.04"

psi @ 28 days, normal weight,

air-entrained; reinforcing to

meet ASTM-615-60

(ASTM D 2974) shredded hardwood

M-278

compost (35 - 40%) sandy loam (30%), coarse sand (30%) & compost (40%)

* THE MAIN COLLECTOR PIPE SHALL BE AT A MINIMUM 0.5% SLOPE.

PORT AND MONITOR PERFORMANCE OF THE FILTER.

MICRO BIORETENTION (UNDERDRAIN) (M-6) NOT TO SCALE

*ADDITIONAL STONE PROVIDED FOR 10 YEAR ATTENUATION/Rev MICRO BIORETENTION NOTES:

. ONLY THE SIDES OF MICRO BIORETENTION ARE TO BE WRAPPED IN FILTER FABRIC. FILTER FABRIC BETWEEN LAYER OR AT THE BOTTOM OF THE MICRO BIORETENTION

WILL CAUSE THE MBR TO FAIL, AND THEREFORE SHALL NOT BE INSTALLED. 2. WRAP THE PERFORATED MBR UNDERDRAIN PIPE WITH 1/4" MESH (4x4) OR SMALLER GALVANIZED HARDWARE CLOTH. SEE APPENDIX B.4.C.6. 3. PROVIDE 5' MINIMUM SPACING BETWEEN UNDER DRAIN AND PERFORATED PIPE THROUGH STONE RESERVOIR OR SPACE PIPE EQUALLY ACROSS BOTTOM FOR SMALL BIOS. (SEE PLANS)

- - - - - 398 - - - EXISTING CONTOUR

LEGEND:

PROPOSED CONTOUR PROPOSED SPOT ELEVATION EXISTING SPOT ELEVATION - EXISTING PAVING EXISTING UTILITY EXISTING SANITARY MANHOLE - EXISTING SANITARY LINE EXISTING WATER LINE

PROPOSED STORM DRAIN EXISTING TREE EXISTING SPECIMEN TREES

. EXISTING TREELINE EXISTING FENCE PROPERTY LINE TO BE ABANDONED PROPERTY LINE CONTRACTOR CONTRACTOR

SOILS BOUNDARY balantie manne manne manne manne manne manne imming MICRO-BIORETENTION (M-6)

AND UTILITY EASEMENT PLAT# 5708 ______ AND UTILITY EASEMENT LIMIT OF DISTURBANCE

ENTRANCE SUPER SILT FENCE • CLEAR WATER DIVERSION / EARTHDIKE

TREE PROTECTION FENCE

STABILIZED CONSTRUCTION

EXISTING WETLAND EXISTING WETLAND BUFFER ensurance construction and a construction of the construction of t

EXISTING STREAM BUFFER DRAINAGE AREA

HIGHLY ERODIBLE SOILS

OPERATION AND MAINTENANCE SCHEDULE FOR LANSCAPE INFILTRATION (M-3), MICRO-BIORETENTION (M-6), RAIN GARDENS (M-7), BIORETENTION SWALE (M-8), AND ENHANCED FILTERS (M-9)

1. THE OWNER SHALL MAINTAIN THE PLANT MATERIAL, MULTCH LAYER AND SOIL LAYER ANNUALLY. MAINTENANCE OF MULCH AND SOIL IS LIMITED TO CORRECTING AREAS OF EROSION OR WASH OUT. ANY MULCH REPLACEMENT SHALL BE DONE IN THE SPRING, PLANT MATERIAL SHALL BE CHECKED FOR DISEASE AND INSECT INFESTATION AND MAINTENANCE WILL ADDRESS DEAD MATERIAL PRUNING. ACCEPTABLE REPLACEMENT PLANT MATERIAL IS LIMITED TO THE FOLLOWING: 2000 MARYLAND STORMWATER DESIGN MANUAL, VOLUME II, TABLE A.4.1 AND 2.

2. THE OWNER SHALL PERFORM A PLANT IN THE SPRING AND IN THE FALL OF EACH YEAR. DURING THE INSPECTION, THE OWNER SHALL REMOVE DEAD AND DISEASED VEGETATION CONSIDERED BEYOND TREATMENT, REPLACE DEAD PLANT MATERIAL WITH ACCEPTABLE REPLACEMENT PLANT MATERIAL, TREAT DISEASED TREES

AND SHRUBS, AND REPLACE ALL DEFICIENT STAKES AND WIRES. 3. THE OWNER SHALL INSPECT THE MULCH EACH SPRING. THE MULCH SHALL BE REPLACED EVERY TWO TO THREE YEARS. THE PREVIOUS MULCH LAYER SHALL BE

4. THE OWNER SHALL CORRECT SOIL EROSION ON AN AS NEEDED BASIS, WITH A MINIMUM OF ONCE PER MONTH AND AFTER EACH HEAVY STORM.

REMOVED BEFORE THE NEW LAYER IS APPLIED.

DEVELOPER TRINITY HOMES MARY LAND, LLC 3675 PARK AVE., SUITE 301 ELLICOTT CITY, MD 21043 (410) 480-0023

ENVIRONMENTAL CONCEPT PLAN

LOTS 1-7 AND OPEN SPACE LOT 8

REVISION

STORMWATER MANAGEMENT DRAINAGE AREA MAP & DETAILS RIVER BIRCH MANOR


L 314 / F. 315 TAX MAP: 17 GRID: 20 2ND ELECTION DISTRICT

ELLICOTT CITY, MD 21042

HOWARD COUNTY, MARYLAND



ENGINEERING, INC. ENGINEERS · SURVEYORS · PLANNERS 3300 N. RIDGE ROAD, SUITE 110 Tel: 410.461.7666 ELLIGOTT CITY, MD 21043 FAX: 410.461.8961



DESIGN BY: DRAWN BY: CHECKED BY: DATE: DECEMBER 2018 AS SHOWN SCALE:

PROFESSIONAL CERTIFICATE

SHEET