

MICROBIORETENTION NOTES:

1. ONLY THE SIDES OF MICROBIORETENTION ARE TO BE WRAPPED IN FILTER FABRIC. FILTER FABRIC BETWEEN LAYER OR AT THE BOTTOM OF THE MICROBIORETNTION WILL CAUSE THE MBR TO FAIL, AND THEREFORE SHALL NOT BE INSTALLED.


2. WRAP THE PERFORATED MBR UNDERDRAIN PIPE WITH 1/4" MESH (4x4) OR SMALLER GALVANIZED HARDWARE CLOTH

3. PROVIDE 5' MINIMUM SPACING BETWEEN UNDER DRAIN AND PERFORATED PIPE THROUGH STONE RESIVOIR OR SPACE PIPE EQUALLY ACROSS BOTTOM FOR SMALL BIOS. (SEE PLANS)


OPERATION AND MAINTENANCE SCHEDULE FOR LANSCAPE INFILTRATION (M-3), MICRO-BIORETENTION (M-6), RAIN GARDENS (M-7), BIORETENTION SWALE (M-8). AND ENHANCED FILTERS (M-9)

1. THE OWNER SHALL MAINTAIN THE PLANT MATERIAL, MULTCH LAYER AND SOIL LAYER ANNUALLY. MAINTENANCE OF MULCH AND SOIL IS LIMITED TO CORRECTING AREAS OF EROSION OR WASH OUT. ANY MULCH REPLACEMENT SHALL BE DONE IN THE SPRING. PLANT MATERIAL SHALL BE CHECKED FOR DISEASE AND INSECT INFESTATION AND MAINTENANCE WILL ADDRESS DEAD MATERIAL PRUNING. ACCEPTABLE REPLACEMENT PLANT MATERIAL IS LIMITED TO THE FOLLOWING: 2000 MARYLAND STORMWATER DESIGN MANUAL, VOLUME II, TABLE A.4.1 AND 2.
2. THE OWNER SHALL PERFORM A PLANT IN THE SPRING AND IN THE FALL OF EACH YEAR. DURING THE INSPECTION, THE OWNER SHALL REMOVE DEAD AND DISEASED VEGETATION CONSIDERED BEYOND TREATMENT, REPLACE DEAD PLANT MATERIAL WITH ACCEPTABLE REPLACEMENT PLANT MATERIAL, TREAT DISEASED TREES AND SHRUBS, AND REPLACE ALL DEFICIENT STAKES AND WIRES. 3. THE OWNER SHALL INSPECT THE MULCH EACH SPRING. THE MULCH SHALL BE REPLACED EVERY TWO TO THREE YEARS. THE PREVIOUS MULCH LAYER SHALL BE REMOVED BEFORE THE NEW LAYER IS APPLIED.

4. THE OWNER SHALL CORRECT SOIL EROSION ON AN AS NEEDED BASIS, WITH A MINIMUM OF ONCE PER MONTH AND AFTER EACH HEAVY STORM.





DETAIL B-4-6-0	STABIL	ANENT SOIL LIZATION MAT REL APPLICATI	ING ON	STANDARD SYMBOL PSSMC — *().117 lb/rt² (* NOLUCE SHEAR STRESS)
OVERLAP OR ABI EDGES (TYP.) 8 IN MIN. OVERLAP AT ROLL END (TYP.)			SEN PRESIDENT	KEY IN UPPER ROLL END FILL MAT VOIDS IF SPECIFIED (SEE NOTE 9) (MIN.)
PREPARED FLOW-CHANNEL WITH SEED	,	ISOMETRIC		PE ROLL. (TYP.)
1. USE MATTING THAT HAS A DESIGNATED ON APPROVED	DESIGN VALUE F	OR SHEAR STRESS EQU	NL TO OR HIGH	ER THAN THE SHEAR STRESS
2. USE PERMANENT SOIL STAI ELEMENTS OF UNIFORM THI NON-LEACHING AND NON- PRESENT, NETTING MIST B SUFFICIENTLY BONDED OR: PREVENT SEPARATION OF 1		NG MADE OF OPEN WEAT TRIBUTION THROUGHOUT. ITON AND SEED GERMIN STIC WITH A MAJORIM IN CENTERS ALONG LONG HE PARENT MATERIAL.	E SYNTHETIC, I CHEMICALS U ATION AND HON ESH OPENING I TUDINAL AXIS O	NON-DEGRADABLE FIBERS OR ISED IN THE MAT MUST BE I-NAURIOUS TO THE SIGN. IF OF 21/2 INCHES AND IF THE MATERIAL TO
3. SECURE MATTING USING ST WIRE HAVING A LINIMAN G. 1 TO 1 X INCHES WIDE AN 8 INCH MAIN LER, A MINIM ROUGH-SAWN HARDWOOD, THE BOTTOM.	EEL STAPLES OR AUGE OF NO. 11 DEE A MINIMUM UM 1 INCH SECO 12 TO 24 INCHES	WOOD STAKES. STAPL AND NO. 8 RESPECTIVE OF 6 BICHES LONG. " MDARY LEQ. AND MINIMU 5 BI LENGTH, 1x3 INCH	ES MUST BE "U Y. "V" SHAPE " SHAPED STA M 4 INCH HEAE N CROSS SECTI	OR "T" SHAPED STEEL D STAPLES MUST AVERAGE PLES MUST HAVE A MINIMUM D. WOOD STAKES MUST BE ON, AND WEDGE SHAPE AT
4. PERFORM FINAL GRADING, ACCORDANCE WITH SPECIFIC UNLESS END OF WORKDAY PLAN.	TOPSOIL APPLICATIONS, PLACE STABILIZATION IS	TION, SEEDBED PREPAR/ MATTING WITHIN 48 HOU SPECIFIED ON THE APT	ITION, AND PER RS OF COMPLE ROYED EROSION	MANENT SEEDING IN TING SEEDING OPERATIONS, I AND SEDIMENT CONTROL
5. UNROLL MATTING IN DIRECT WORK FROM CENTER OF CH THE SEEDED SURFACE, AVC	TON OF WATER F LANNEL OUTWARD ND STRETCHING T	LOW, CENTERING THE FI WHEN PLACING ROLLS. THE MATTING.	EST ROLL ON T LAY MATTING !	HE CHANNEL CENTER LINE. SMOOTHLY AND FIRMLY UPON
6. OVERLAP OR ABUT EDGES BY 6 INCHES (MINIMUM), W	OF MATTING ROLL	LS PER MANUFACTURER NM MAT OVERLAPPING O	RECOMMENDATI N TOP OF THE	ONS. OVERLAP ROLL ENDS NEXT DOWNSTREAM MAT.
7. KEY IN THE TOP OF SLOPE ROLL END IN THE TRENCH, TO SECURE THE MAT END	END OF MAT 6 STAPLING THE M IN THE KEY.	INCHES (WINIMUM) BY D (AT IN PLACE, REPLACIN	G THE EXCAVA	CH, PLACING THE MATTING TED MATERIAL, AND TAMPING
8. STAPLE/STAKE MAT IN A S 2 FOOT (MAXIMUM) CENTER	TAGGERED PATTI	ERN ON 4 FOOT (MAXIM	M) CENTERS T	HROUGHOUT AND
9. IF SPECIFIED BY THE DESIG ONCE THE MATTING IS KEY MATERIAL AND LIGHTLY CO	NER OR MANUFA ED AND STAPLED MPACT OR ROLL	CTURER AND DEPENDING IN PLACE, FILL THE MA TO MAXIMIZE SOIL/MAT	ON THE TYPE IT VOIDS WITH CONTACT WITH	OF MAT BEING INSTALLED, TOP SOIL OR GRANULAR OUT CRUSHING MAT.
10. ESTABLISH AND MAINTAIN ARE CONTINUOUSLY MET IN	EGETATION SO T ACCORDANCE W	HAT REQUIREMENTS FOR ITH SECTION B-4 VEGET	ADEQUATE VE	GETATIVE ESTABLISHMENT ATION.
MARYLAND STANDA	RDS AND SPECIF	FICATIONS FOR SOIL ER	OSION AND SE	DIMENT CONTROL
U.S. DEPARTMENT OF AGRI NATURAL RESOURCES CONSERVA		2011		EPARTMENT OF ENVIRONMENT NAGEMENT ADMINISTRATION



C = 0.15 $I_2 = 5.90$ In/h $I_{10} = 8.50$ In/h A = 0.041 AC. n = 0.03 SLOPE = 11% + /-

 $Q_2 = 0.036 \text{ cf/s}$ $V_2 = 1.04 \text{ fps}$ Max Shear Stress = 0.117 lb/ft2 $Q_{10} = 0.052$ cf/s $V_{10} = 1.21$ fps Max Shear Stress = 0.144 lb/ft2





Appendix B.4. Construction Specifications for Environmental Site Design Practices


Material	Specification	Size	Notes
Plantings	see Appendix A, Table A.4	n/s	plantings are site-specific
Planting soil [2' to 4' deep]	loamy sand (60 - 65%) & compost (35 - 40%) or sandy loam (30%), coarse sand (30%) & compost (40%)	n∕a	USDA soil types loamy sand or sandy loam; clay content < 5%
Organic content	Min. 10% by dry weight (ASTM D 2974)		
Mulch	shredded hardwood		aged 6 months, minimum; no pine or wood chips
Pea gravel diaphragm	pea gravel: ASTM-D-448	NO. 8 OR NO. 9 (1/8" TO 3/8")	
Curtain drain	ornamental stone: washed cobbles	stone: 2" to 5"	
Geotextile		n/a	PE Type 1 nonwoven
Gravel (underdrains and infiltration berms)	AASHTO M-43	NO. 57 OR NO. 6 AGGREGATE (3/8" to 3/4")	
Underdrain piping	F 758, Type PS 28 or AASHTO M-278	4" to 6" rigid schedule 40 PVC or SDR35	Slotted or perforated pipe; 3/8" perf. @ 6" on center, 4 holes per row; minimum of 3" of gravel over pipes; not necessary underneath pipes. Perforated pipe shall be wrapped with 1/4-inch galvanized hardware cloth
Poured in place concrete (if required)	MSHA Mix No. 3; f' _o = 3500 psi @ 28 days, normal weight, air-entrained; reinforcing to meet ASTM-615-60	n/a	on-site testing of poured-in-place concrete required: 28 day strength and slump test; all concrete design (cast-in-place or pre-cast) not using previously approved State or local standards requires design drawings sealed and approved by a professional structural engineer licensed in the State of Marylan - design to include meeting ACI Code 350.R/89; vertical loading [H-10 or H-20]; allowable horizontal loading (based on soil pressures); and analysis of potential cracking
Sand	AASHTO-M-6 or ASTM-C-33	0.02" to 0.04"	Sand substitutions such as Diabase and Graystone (AASHTO) #10 are not acceptable. No calcium carbonated or dolomitic san substitutions are acceptable. No "rock dust" can be used for san


ON-LOT DRYWELL - SIZING CHART									
and the commence of the second second second	NUMBER	SURFACE SIZE			STONE	SAND	OWNER	MAINTENANC	
	OF DW'S		FTxFT		DEPTH (FT)	DEPTH(FT)			
1	1 1	8.00	X	8.00	4	1	PRIVATE	PRIVATE	
2	1 1	8.00	X	8.00	4	1	PRIVATE	PRIVATE	

OPERATION AND MAINTENANCE SCHEDULE FOR PRIVATELY OWNED AND MAINTAINED STORMWATER DRY WELLS (M-5)

1. THE MONITORING WELLS AND STRUCTURES SHALL BE INSPECTED QUARTERLY BASIS AND AFTER EVERY LARGE STORM EVENT. 2. WATER LEVELS AND SEDIMENT BUILD UP IN THE MONITORING WELLS SHALL BE RECORDED OVER A PERIOD OF SEVERAL DAYS TO INSURE TRENCH DRAINAGE. 3. A LOG BOOK SHALL BE MAINTAINED TO DETERMINE THE RATE AT WHICH THE FACILITY DRAINS.

4. WHEN THE FACILITY BECOMES CLOGGED SO THAT IT DOES NOT DRAIN DOWN WITHIN THE 72 HOUR TIME PERIOD, CORRECTIVE ACTION SHALL BE TAKEN. 5. THE MAINTENANCE LOG BOOK SHALL BE AVAILABLE TO HOWARD COUNTY FOR INSPECTION TO INSURE COMPLIANCE WITH OPERATION AND MAINTENANCE CRITERIA. 6. ONCE THE PERFORMANCE CHARACTERISTICS OF THE INFILTRATION FACILITY HAVE BEEN VERIFIED, THE MONITORING SCHEDULE CAN BE REDUCED TO AN ANNUAL BASIS UNLESS THE PERFORMANCE DATA INDICATES THAT A MORE FREQUENT SCHEDULE IS REQUIRED.





VOGEL ENGINEERING (+) TIMMONS GROUP

3300 North Ridge Road, Suite 110, Ellicott City, MD 21043 P 410.461.7666 F 410.461.8961 www.timmons.com

INDIVIDUAL PRACTICE ESDV DESIGN COMPUTATIONS


Project: Furry Friends Fa	m				
Property Area:	5.03 Ac.		ESDv=(PexRvxA)/12	Rev =(((Sw)(Rv)(A))/1	2)*43560
LOD Area:	0.28 Ac.		Rv=0.05+0.009xI		
Post Development Impervious:	0.14 Ac.		Vmin 1yr rainfall = 1"	(1.0x0.95xA)/12	
Site % Impervious:	47.64 %		Vmax 1yr rainfall = 2.6"	(2.6x0.95xA)/12	100
Total wighted Pe:	1.80 Inches				

ESDv Provided:

Target ESDv Reguired

10/23/2023 Checked By: RHV

RACTICE DA#	PRACTICE DA (SF)	PRACTICE DA (AC)	IMPERVIOUS (SF)	IMPERVIOUS (AC)	PERVIOUS (SF)	PERVIOUS AREA	PRACTICE % IMPERV	PRACTICE Rv	PRACTICE 1" TARGET VOLUME	PRACTICE 2.6" MAX VOLUME	Rev REQUIRED	Rev PROVIDED	TOTAL VOLUME PROVIDED	Depth Porosity
DA #1	763	0.02	763	0.02	0	0.00	100	0.95	60	157	N/A	23	128	MICROSCALE DRYWELL (M-5)
DW #1									·			· .		Length Width Depth Porosity 8.0 8.0 5.0 0.4
DA #2 DW #2	763	0.02	763	0.02	0	0.00	100	0.95	60	157	N/A	23		MICROSCALE DRYWELL (M-5) Length Width Depth Porosity 8.0 8.0 5.0 0.4
DA #3	5,068	0.12	2,639	0.06	2,429	0.06	52	0.52	219	570	100	100	590	CF SF
MBR	encontraction and an encourage and an en		The action and the end of the action and the action and the action and the action and the action action and the action ac		: + : : : : : : : : : : : : : : : : : :									400 300 Surface Area of MBR @ 1.0 ponding (75% above) 100 300 Rev Recharge 0.83 x 0.4 (Recharge Vol Req. = 25% of total volume provided below) 90 300 ADDITIONAL STONE 1.00 x 0.3
	490 DOFTOP INNECT	0.01	490	0.01	0	0.00	100	0.95	39	101	N/A	15	39	NON STRUCTURAL PRACTICE - ROOFTOP DISCONNECT (PexRvxA)/12x43560 Pe=1"
See Page	2 Of ESDv SW	M Computa	tions.							TOTALS	*184	161	884	



SWALE DRAINAGE AREA PLAN SCALE: 1"=20'

APPENDIX B.4.C SPECIFICATIONS FOR MICRO-BIORETENTION. RAIN GARDEN, LANDSCAPE INFILTRATION & INFILTRATION BERMS

. MATERIAL SPECIFICATIONS THE ALLOWABLE MATERIALS TO BE USED IN THESE PRACTICES ARE DETAILED IN TABLE B.4.1. 2. FILTERING MEDIA OR PLANTING SOIL

THE SOIL SHALL BE A UNIFORM MIX, FREE OF STONES, STUMPS, ROOTS OR OTHER SIMILAR OBJECTS LARGER THAN TWO INCHES. NO OTHER MATERIALS OR SUBSTANCES SHALL BE MIXED OR DUMPED WITHIN THE MICRO-BIORETENTION PRACTICE THAT MAY BE HARMFUL TO PLANT GROWTH, OR PROVE A HINDRANCE TO THE PLANTING OR MAINTENANCE OPERATIONS. THE PLANTING SOIL SHALL BE FREE OF BERMUDA GRASS, QUACKGRASS, JOHNSON GRASS, OR OTHER NOXIOUS WEEDS AS SPECIFIED UNDER COMAR 15.08.01.05. THE PLANTING SOIL SHALL BE TESTED AND SHALL MEET THE FOLLOWING CRITERIA:

* SOIL COMPONENT - LOAMY SAND OR SANDY LOAM (USDA SOIL TEXTURAL CLASSIFICATION). * ORGANIC CONTEN - MINIMUM 10% BY DRY WEIGHT (ASTM D 2974). IN GENERAL, THIS CAN BE MET WITH A MIXTURE OF LOAMY

SAND (60%-65%) AND COMPOST (35% TO 40%) OR SANDY LOAM (30%), COARSE SAND (30%), AND COMPOST (40%).

* CLAY CONTENT - MEDIA SHALL HAVE A CLAY CONTENT OF LESS THAN 5%. * PH RANGE - SHOULD BE BETWEEN 5.5 - 7.0. AMENDMENTS (E.G., LIME, IRON SULFATE PLUS SULFUR) MAY BE MIXED IN TO THE SOIL TO INCREASE OR DECREASE PH. THERE SHALL BE AT LEAST ONE SOIL TEST PER PROJECT. EACH TEST SHALL CONSIST OF BOTH THE STANDARD SOIL TEST FOR PH, AND ADDITIONAL TESTS OF ORGANIC MATTER, AND SOLUBLE SALTS. A TEXTURAL ANALYSIS IS REQUIRED FROM THE SITE STOCKPILED TOPSOIL. IF

COMPACTION IT IS VERY IMPORTANT TO MINIMIZE COMPACTION OF BOTH THE BASE OF BIORETENTION PRACTICES AND THE REQUIRED BACKFILL. WHEN POSSIBLE, USE EXCAVATION HOES TO REMOVE ORIGINAL SOIL. IF PRACTICES ARE EXCAVATED USING LOADER, THE CONTRACTOR SHOULD USE WIDE TRACK OR MARSH TRACK EQUIPMENT, OR LIGHT EQUIPMENT WITH TURF TYPE TIRES. USE OF EQUIPMENT WITH NARROW TRACKS OR NARROW TIRES, RUBBER TIRES WITH LARGE LUGS, OR HIGH-PRESSURE TIRES WILL CAUSE EXCESSIVE COMPACTION RESULTING IN REDUCED INFILTRATION RATES AND IS NOT ACCEPTABLE. COMPACTION WILL SIGNIFICANTLY CONTRIBUTE TO DESIGN FAILURE.

TOPSOIL IS IMPORTED, THEN A TEXTURE ANALYSIS SHALL BE PERFORMED FOR EACH LOCATION WHERE THE TOPSOIL WAS EXCAVATED.

COMPACTION CAN BE ALLEVIATED AT THE BASE OF THE BIORETENTION FACILITY BY USING A PRIMARY TILLING OPERATION SUCH AS CHISEL PLOW, RIPPER, OR SUBSOILER. THESE TILLING OPERATIONS ARE TO REFRACTURE THE SOIL PROFILE THROUGH THE 12 INCH COMPACTION ZONE. SUBSTITUTE METHODS MUST BE APPROVED BY THE ENGINEER. ROTOTILLERS TYPICALLY DO NOT TILL DEEP ENOUGH TO REDUCE THE EFFECTS OF COMPACTION FROM HEAVY EQUIPMENT.

ROTOTILL 2 TO 3 INCHES OF SAND INTO THE BASE OF THE BIORETENION FACILITY BEFORE BACKFILLING THE OPTIONAL SAND LAYER. PUMP ANY PONDED WATER BEFORE PREPARING (ROTOTILLING) BASE. WHEN BACKFILLING THE TOPSOIL OVER THE SAND LAYER, FIRST PLACE 3 TO 4 INCHES OF TOPSOIL OVER THE SAND, THEN ROTOTILL THE SAND/TOPSOIL TO CREATE A GRADATION ZONE. BACKFILL THE REMAINDER OF THE TOPSOIL TO FINAL GRADE. WHEN BACKFILLING THE BIORETÉNTION FACILITY, PLACE SOIL IN LIFTS 12" TO 18". DO NOT USE HEAVY EQUIPMENT WITHIN THE BIORETENTION BASIN. HEAVY EQUIPMENT CAN BE USED AROUND THE PERIMETER OF THE BASIN TO SUPPLY SOILS AND SAND. GRADE BIORETENTION MATERIALS WITH LIGHT EQUIPMENT SUCH AS A COMPACT LOADER OR A DOZER/LOADER WITH MARSH

4. PLANT MATERIAL RECOMMENDED PLANT MATERIAL FOR MICRO-BIORETENTION PRACTICES CAN BE FOUND IN APPENDIX A, SECTION A.2.3.

5. PLANT INSTALLATION

COMPOST IS A BETTER ORGANIC MATERIAL SOURCE, IS LESS LIKELY TO FLOAT, AND SHOULD BE PLACED IN THE INVERT AND OTHER LOW AREAS. MULCH SHOULD BE PLACED IN SURROUNDING TO A UNIFORM THICKNESS OF 2" TO 3". SHREDDED OR CHIPPED HARDWOOD MULCH IS THE ONLY ACCEPTED MULCH, PINE MULCH AND WOOD CHIPS WILL FLOAT AND MOVE TO THE PERIMETER OF THE BIORETENTION AREA DURING A STORM EVENT AND ARE NOT ACCEPTABLE. SHREDDED MULCH MUST BE WELL AGED (6 TO 12 MONTHS) FOR ACCEPTANCE. ROOTSTOCK OF THE PLANT MATERIAL SHALL BE KEPT MOIST DURING TRANSPORT AND ON-SITE STORAGE. THE PLANT ROOT BALL SHOULD BE PLANTED SO 1/8TH OF THE BALL IS ABOVE FINAL GRADE SURFACE. THE DIAMETER OF THE PLANTING PIT SHALL BE AT LEAST SIX INCHES LARGER THAN THE DIAMETER OF THE PLANTING BALL. SET AND MAINTAIN THE PLANT STRAIGHT DURING THE ENTIRE PLANTING PROCESS. THOROUGHLY WATER GROUND BED COVER AFTER INSTALLATION. TREES SHALL BE BRACED USING 2" BY 2" STAKES ONLY AS NECESSARY AND FOR THE FIRST GROWING SEASON ONLY. STAKES ARE TO BE EQUALLY SPACED ON THE OUTSIDE OF THE TREE BALL GRASSES AND LEGUME SEED SHOULD BE DRILLED INTO THE SOIL TO A DEPTH OF AT LEAST ONE INCH. GRASS AND LEGUME PLUGS SHALL BE PLANTED FOLLOWING THE NON-GRASS GROUND COVER PLANTING SPECIFICATIONS. THE TOPSOIL SPECIFICATIONS PROVIDE ENOUGH ORGANIC MATERIAL TO ADEQUATELY SUPPLY NUTRIENTS FROM NATURAL CYCLING. THE

PRIMARY FUNCTION OF THE BIORETENTION STRUCTURE IS TO IMPROVE WATER QUALITY. ADDING FERTILIZERS DEFEATS, OR AT A MINIMUM, IMPEDES THIS GOAL. ONLY ADD FERTILIZER IF WOOD CHIPS OR MULCH ARE USED TO AMEND THE SOIL. ROTOTILL UREA FERTILIZER AT A 6. UNDERDRAINS UNDERDRAINS SHOULD MEET THE FOLLOWING CRITERIA:

* PIPE - SHOULD BE 4" TO 6" DIAMETER, SLOTTED OR PERFORATED RIGID PLASTIC PIPE (ASTMF 758, TYPE PS 28, OR

- AASHTO-M-278) IN A GRAVEL LAYER. THE PREFERRED MATERIAL IS SLOTTED, 4" RIGID PIPE (E.G., PVC OF HDPE). * PERFORATIONS - IF PERFORATED PIPE IS USED, PERFORATIONS SHOULD BE 3/8" DIAMETER LOCATED 6" ON CENTER WITH A MINIMUM OF FOUR HOLES PER ROW. PIPE SHALL BE WRAPPED WITH A 1/4" (NO. 4 OR 4x4) GALVANIZED HARDWARE CLOTH. * GRAVEL - THE GRAVEL LAYER (NO. 57 STONE PREFERRED) SHALL BE AT LEAST 3" THICK ABOVE AND BELOW THE UNDERDRAIN.
- * THE MAIN COLLECTOR PIPE SHALL BE AT A MINIMUM 0.5% SLOPE. * A RIGID, NON-PERFORATED OBSERVATION WELL MUST BE PROVIDED (ONE PER EVERY 1,0000 SQUARE FEET) TO PROVIDE A CLEAN-OUT PORT AND MONITOR PERFORMANCE OF THE FILTER.
- * A 4" LAYER OF PEA GRAVEL (1/8" TO 3/8" STONE) SHALL BE LOCATED BETWEEN THE FILTER MEDIA AND UNDERDRAIN TO PREVENT MIGRATION OF FINES IN TO THE UNDERDRAIN, THIS LAYER MAY BE CONSIDERED PART OF THE FILTER BED WHEN BED THICKNESS EXCEEDS 24" THIS MAIN COLLECTOR PIPE FOR UNDERDRAIN SYSTEMS SHALL BE CONSTRUCTED AT A MINIMUM SLOPE OF 0.5%. OBSERVATION WELLS

AND/OR CLEAN-OUT PIPES MUST BE PROVIDED (ONE MINIMUM PER EVERY 1000 SQUARE FEET OF SURFACE AREA). 7. MISCELLANEOUS THESE PRACTICES MAY NOT BE CONSTRUCTED UNTIL ALL CONTRIBUTING DRAINAGE AREA HAS BEEN STABILIZED.

DISCONNECTION OF NON-ROOFTOP RUNOFF

CONSTRUCTION CRITERIA:

THE FOLLOWING SHOULD BE ADDRESSED DURING CONSTRUCTION OF PROJECTS WITH NON-ROOFTOP DISCONNECTIONS:

- EROSION AND SEDIMENT CONTROL: EROSION AND SEDIMENT CONTROL PRACTICES (E.G., SEDIMENT TRAPS) SHALL NOT BE LOCATED IN AREAS DESIGNATED FOR DISCONNECTIONS.

- SITE DISTURBANCE: TO MINIMIZE DISTURBANCE AND COMPACTION, CONSTRUCTION VEHICLES AND EQUIPMENT SHOULD AVOID AREAS RECEIVING DISCONNECTED RUNOFF. SHOULD AREAS RECEIVING DISCONNECTED RUNOFF BECOME COMPACTED, SCARIFYING THE SURFACE OR ROTOTILLING THE SOIL TO A DEPTH OF FOUR TO SIX INCHES SHALL BE PERFORMED TO ENSURE PERMEABILITY.

ADDITIONALLY, AMENDMENTS MAY BE NEEDED FOR TIGHT, CLAYEY SOILS.

A FINAL INSPECTION SHALL BE CONDUCTED BEFORE USE AND OCCUPANCY APPROVAL ENSURE THAT ADEQUATE TREATMENT AREAS AND PERMANENT STABILIZATION HAS BEEN ESTABLISHED.

MAINTENANCE CRITERIA:

MAINTENANCE OF AREAS RECEIVING DISCONNECTED RUNOFF IS GENERALLY NO THAT REQUIRED FOR OTHER LAWN OR LANDSCAPED AREAS. THE AREAS RECEIVING SHOULD BE PROTECTED FROM FUTURE COMPACTION (E.G., BY PLANTING TREES OR ALONG THE PERIMETER). IN COMMERCIAL AREAS, HIGH FOOT TRAFFIC SHOULD BE

		FURRY FI 11762 CARF ELLICOTT C	ELOPER RIENDS FARI ROLL MILL R HTY, MD 210 461-5760	CAD	OWNER GARY & SUSAN WITT 11762 CARROLL MILL RO ELLICOTT CITY, MD 2104 410-461-5760				
							-		
								DATE	
	*			4 1	٠				
NO.			REVISION						


ENVIRONMENTAL CONCEPT PLAN STORMWATER MANAGEMENT DETAILS

FURRY FRIENDS FARM

PET DAYCARE FACILITY 11762 CARROLL MILL ROAD, ELLICOTT CITY, MD 21042

ZONE: RC-DEC PARCEL 146 HOWARD COUNTY, MARYLAND TAX MAP 23 BLOCK 14 3RD ELECTION DISTRICT **VOGEL ENGINEERING**

TIMMONS GROUP 3300 NORTH RIDGE ROAD, SUITE 110, ELLICOTT CITY, MD 21043



CHECKED BY: JANUARY 2024 AS SHOWN SCALE: W.O. NO.: 44194

P: 410.461.7666 F: 410.461.8961 www.timmons.com I HEREBY CERTIFY THAT THESE DOCUMENTS WERE PREPARED OR APPROVED BY ME, AND THAT I AM A DULY LICENSED PROFESSIONAL ENGINEER UNDER THE LAWS OF THE STATE OF MARYLAND, LICENSE NO, 16193 EXPIRATION DATE: 09-27-2024

SHEET OF _

ECP-24-01: