HOWARD COUNTY DEPARTMENT OF PUBLIC WORKS CORROSION CONTROL TEST STATION FIELD DATA SURVEY FORM

Location:	Date Survey	/ed:	05/31/	05/31//2007					
	(113+50)			Surveyed b		AS/MJ			
T/S #: 3				<u></u>			3218		
T/S Type:						16"			
Was the T/S I	S/NO	YES							
TEST STATION CONDITION									
Test Box: Above ground PVC - Good									
		rminal - Good							
		Good							
Other:		<u> </u>							
SURVEY DATA									
Test Wire			P/Cu-CuSO ₄ (V)			P/Zn (V)		Anode	
Size/Description		Color		'On""Off"	_	"On	""Off"	(mA)	
1. #10 A		Black		-0.23					
2. #12 A	WG	Black		-0.23	38				
3.					_				
4. #10 A		Black		-0.23					
5. #12 A	WG	Black		-0.23	38				
6.									
7.									
8.									
P/Cu-CuSO ₄ = Pipe to Copper-Copper Sulfate Reference Electrode P/Zn = Pipe to Zinc Reference Electrode "On" = Reading with Anode(s) connected "Off" = Reading with Anode(s) disconnected Anode = Current output Anode(s) TESTING THE EFFECTIVENESS OF INSULATING JOINTS									
Groundbed:									
Connected to (B/W):									
		rent (A)		Voltage (V)			Resistance (ohms)		
ON:					` '			,	
OFF:									
DELTA:									
TESTING IR DROP									
IR Drop						ſ	Between	Resistance	
Calibrations	I (A)	E (m	1V)	$K = \Delta I (m)$ $\Delta E (n)$		A)	Terminals	(ohms)	
INITIAL:						V)		-	
FINAL:				1					
DELTA:				Direction:					
REPAIRS MADE									
Test Box:									
Terminal Boa	ırd:								
Wires:									
Other:	_								
Comments/R	ecommenda	ations:							



Figure 113 - Location of Test Station 3218-3



Figure 114 - - Location of Test Station 3218 -3 - close up