## SHEET INDEX

NO	TITLE
1	COVER SHEET
2	ROAD PLAN, PROFILE AND TYPICAL SECTION
3	ROAD IMPROVEMENT PLAN, SECTIONS AND DETAILS
4	SOIL MAP AND GRADING AND SEDIMENT CONTROL PLAN, STAGE 1
5	FINAL GRADING AND SEDIMENT CONTROL PLAN
6	SEDIMENT CONTROL NOTES AND DETAILS
7	STORM DRAIN PROFILES
8	STORM DRAIN DRAINAGE AREA MAP
9	STORMWATER MANAGEMENT PLAN
10	STORMWATER MANAGEMENT DETAILS AND SOIL BORINGS
11	FOREST CONSERVATION PLAN
12	LANDSCAPING PLAN

# <u>LEGEND</u>

¿SP# SPECIMEN TREE EX. TREE LINE

PROP. TREE LINE AREA OF 100 YEAR FLOODPLAIN AREA OF WETLANDS

AREA OF 15%-25% SLOPES

AREA OF FOREST CONSERVATION EASEMENT

AREA OF RECREATIONAL OPEN SPACE

OHE EX. OVERHEAD POWER LINE AREA OF ROAD DEDICATON

# VICIN<u>ITY MAP</u>

SCALE: 1"=1000" ADC MAP: 35 GRID A-1

FINAL ROAD CONSTRUCTION PLAN

PINH ACRES

LOTS 1 THRU 21, AND

OPEN SPACE LOTS 22 THRU 28

FIRST ELECTION DISTRICT

HOWARD COUNTY, MARYLAND

	ENGINEER'S CERTIFICATE
	I CERTIFY THAT THIS PLAN FOR EROSION AND SEDIMENT CONTROL REPRESENTS A PRACTICAL AND WORKABLE PLAN BASED ON MY PERSONAL KNOWLEDGE OF THE SITE CONDITIONS AND THAT IT WAS PREPARED IN ACCORDANCE WITH THE REQUIREMENTS OF THE HOWARD SOIL CONSERVATION DISTRICT.
	8/4/16
ı	SIGNATURE OF ENGINEER DATE
	R. JACOB HIKMAT, PE.
	PRINTED NAME OF ENGINEER
	DEVELOPERS CERTIFICATE
	I CERTIFY THAT ALL DEVELOPMENT AND CONSTRUCTION WILL BE DONE ACCORDING TO THIS PLAN, AND THAT ANY RESPONSIBLE PERSONNEL INVOLVED IN THE CONSTRUCTION PROJECT WILL HAVE A CERTIFICATE OF ATTENDANCE AT A DEPARTMENT OF THE ENVIRONMENT APPROVED TRAINING PROGRAM FOR THE CONTROL OF SEDIMENT AND EROSION BEFORE BEGINNING THE PROJECT. HOWARD SOIL CONSERVATION DISTRICT IS AUTHORIZED TO CONDUCT PERIODIC ON—SITE INSPECTION.  SIGNATURE OF DEVELOPER  DATE  PRINTED NAME OF DEVELOPER
	THIS DEVELOPMENT PLAN IS APPROVED FOR SOIL EROSION AND SEDIMENT CONTROL BY THE HOWARD SOIL CONSERVATION DISTRICT.
JACION	HOWARD SOIL CONSERVATION DISTRICT BATE
< 1	

CHIEF, BUREAU OF HIGHWAYS

APPROVED: DEPARTMENT OF PLANNING AND ZONING

Commission

CHIEF, DEVELOPMENT ENGINEERING DIVISION

CHIEF, DIVISION OF LAND DEVELOPMENT

# <u>DEVELOPER</u>

R. JACOB HIKMAT P.F.

8/24/16


11-08-1

C/O DORSEY FAMILY HOMES, INC. 10717-B BIRMINGHAM WAY WOODSTOCK, MARYLAND 21163 (410)465-7200

						ST	<i>ORMWATE</i>	'R MANA	GEMENT	PRACTI	CES					,
LOT #	ADDRESS	A-1	PAVEMENTS A-2	A-3	RUNOFF N-1	OF NON-ROOFTOP RUNOFF N-2	AREAS N-3	M-1	SUBMERGED GRAVEL WETLANDS M-2	LANDSCAPE INFILTRATION M-3	INFILTRATION BERMS M-4	WELLS M-5	MICRO-BIORETENTION M-6	RAIN GARDENS M-7	SWALES M-8	ENHANCED FILTERS M-9
1	6203 AUSTIN WAY	(Y/N) N	(Y/N) N	(Y/N) N	(NUMBER)	(Y/N)	(Y/N) N	(NUMBER)	(NUMBER)	(NUMBER)	(NUMBER)	(NUMBER)	(NUMBER) MB-1	(NUMBER)	(NOMBER)	(NUMBER)
2	6207 AUSTIN WAY	N	N	N	0	N	N	0	0	0	0	0	MB-1	0	0	0
3	6211 AUSTIN WAY	N	N	N	0	N	N	0	0	0	0	2	MB-2	0	0	0
4	6215 AUSTIN WAY	N	N N	N	0	N	N	0	0	0	0	2	MB-2	0	0	0
5	6219 AUSTIN WAY	N	N	N	0	N	N	0	0	0	0	2	MB-4	0	0	0
6	6223 AUSTIN WAY	N	N	N	0	N	N -	0	0	0	0	2	MB-4	0	0	0
7	6227 AUSTIN WAY	N	N	N	0	N	N	0	0	0	0	2	MB-4	0	0	0
8	6231 AUSTIN WAY	N	N	N	0	N	N	0	0	0	0	2	MB-4	0	0	0
9	6235 AUSTIN WAY	N	N	N	0	N	N	0	0	0	0	2	MB-3	0	0	0
10	6239 Austin WAY	N	N	N	0	N	N	0	0	0	0	2	MB-3	0	0	0
11	6244 AUSTIN WAY	N	N	N	0	Υ	N	0	0	0	0	2	0	0	0	0
12	6240 <b>austin</b> way	N	N	N	0	Υ	N	0	0	0	0	2	0	0	0	0
13	6236 AUSTIN WAY	N	N	N	0	N	N	0	0	0	0	2	MB-3	0	0	0
14	6232 AUSTIN WAY	N	- N	N	0	N	N	0	0	0	0	2	MB-2	0	0	0
15	6228 AUSTIN WAY	N	N	N	0	N	N	0	0	0	0	2	MB-2	0	0	0
16	6224 AUSTIN WAY	N	N	N	0	N	N ·	0	0	0	0	2	MB-2	0	0	0
17	6220 AUSTIN WAY	N	N	N	0	* N	N	0	0	0	. 0	2	MB-2	0	0	0
18	6216 Austin WW	N	N	N	0	N	N	0	0	0	0	2	MB-2	0	0	0
19	6212 AUSTIN WAY	N	N	N	0	. N	N	0	0	0	0	2	MB-2	0	0	0
20	6208 AUSTIN WAY	N	N	N	0	N	N	0	0	0	0	0	MB-1	0	0	0
21	6204 AUSTIN WAY	N	N	N	0	N .	N -	0	0	0	0	0	MB-1	0	<b>∞</b> 0 ∘	0

HEREBY CERTIFY THAT THESE DOCUMENTS WERE PREPARED OR APPROVED BY ME AND THAT I AM A DULY LICENSED PROFESSIONAL ENGINEER UNDER THE LAWS OF THE STATE OF MARYLAND, LICENSE NO. 17942, EXP DATE 09/03/16





HOUSES ARE NOT ALLOWED TO BE BUILT USING THIS FINAL PLAN DRAWING.

# GENERAL NOTES:

- THIS SUBJECT PROPERTY IS ZONED R-20 PER THE OCTOBER 6, 2013 COMPREHENSIVE ZONING PLAN.
- THE PROJECT IS IN CONFORMANCE WITH THE LATEST HOWARD COUNTY STANDARDS UNLESS WAIVERS HAVE
- TOPOGRAPHY WITHIN 200' OF SITE BOUNDARY SHOWN HEREON IS BASED ON FIELD RUN SURVEY PERFORMED BY MILDENBERG, BOENDER & ASSOC., INC. ON OR ABOUT MARCH 2014. OTHER TOPOGRAPHY SHOWN IS
- BOUNDARY SHOWN HEREON IS BASED ON A FIELD RUN MONUMENTED BOUNDARY SURVEY PERFORMED ON
- COORDINATES BASED ON NAD '83 (HORIZONTAL) AND NAVD '88 (VERTICAL) MARYLAND COORDINATE SYSTEM AS PROJECTED BY HOWARD COUNTY GEODETIC CONTROL STATIONS STA. No. 37BA N 563785.618 E 1376343.172 ELEV. 373.014 STA. No. 37BB N 563663.415 E 1378040.471 ELEV. 393.935
- PROJECT BACKGROUNGD: ADDRESS: 6249 MONTGOMERY ROAD, ELKRIDGE, MD 21075 LOCATION: TAX MAP: 37 PARCEL: 49 AND 50 GRID: 5 **ELECTION DISTRICT: FIRST** DEED REFERENCE: PARCEL 49- 6776/184, PARCEL 50- 4043/703 PREVIOUS PROJECT NUMBERS: ECP-15-001, SP-15-011

OR ABOUT MARCH 2014 BY MILDENBERG, BOENDER & ASSOC.


SITE AREA TABULATION TOTAL AREA: 12.03 AC.± AREA OF 100 YEAR FLOODPLAIN: 0.1 AC± MINIMUM LOT SIZE PROPOSED: NUMBER OF BUILDABLE LOTS: 21 NUMBER OF OPEN SPACE LOTS: 6 TYPE OF PROPOSED UNIT: SFD

- AREA OF OPEN SPACE REQUIRED: 3.61 AC±
  AREA OF OPEN SPACE PROVIDED: 3.89 AC±
  AREA OF RECREATIONAL OPEN SPACE REQUIRED: (200 S.F./UNIT
  AREA OF RECREATIONAL OPEN SPACE PROVIDED: 4.200 S.F.±
- 9. SEWER IS PUBLIC, CONTRACT NO. 14-4904-D.
- 10. STORMWATER MANAGEMENT IS PROVIDED BY N-2 NON-ROOFTOP DISCONNECTIONS, M-6 MICRO-BIORETENTION FACILITIES, AND M-5 DRYWELLS IN ACCORDANCE WITH THE 2007 MARYLAND STORMWATER DESIGN MANUAL. NONROOFTOP DISCONNECTIONS (N-2) AND DRYWELLS (M-5) WILL BE PRIVATELY OWNED AND MAINTAINED BY THE PROPERTY OWNERS. MICRO-BIORETENTION FACILITIES (M-6) WILL BE JOINTLY OWNED BY HOWARD
- 11. FLOODPLAIN EXISTS ON SITE AS CERTIFIED IN THE FLOODPLAIN STUDY PREPARED BY MILDENBERG, BOENDER & ASSOC., INC. IN JULY 2014 AND WAS APPROVED UNDER SP-15-011 IN MAY 28, 2015.
- 12. WETLANDS, STREAM AND ITS BUFFER EXIST ON SITE AS CERTIFIED IN THE WETLAND REPORT PREPARED BY ECO-SCIENCE PROFESSIONALS, INC. IN JULY 2014 AMD WAS APPROVED UNDER SP-15-011 IN MAY 28, 2015.
- 13. FOREST STAND DELINEATION PERFORMED BY ECO-SCIENCE PROFESSIONALS, INC. IN JULY, 2014 AND WAS APPROVED UNDER SP-15-011 IN MAY 28, 2015. A TOTAL OF 11 SPECIMEN TREES EXIST ON SITE. 14. APFO ROAD TEST PREPARED BY MARS GROUP IN MAY 2014 AND WAS APPROVED UNDER SP-15-011
- IN MAY 5, 2015.
- 15. NOISE STUDY IS NOT REQUIRED FOR THIS PROJECT. 16. NO SIGNIFICANT HISTORIC STRUCTURES, CEMETERIES, OR GRAVE SITES EXIST ON-SITE.
- 17. SITE IS NOT ADJACENT TO A DESIGNATED SCENIC ROAD.
- 18. ALL EXISTING STRUCTURES WERE REMOVED ON DECEMBER 11, 2015.
- 19. FOREST CONSERVATION OBLIGATIONS IN ACCORDANCE WITH SECTION 16.1200 OF THE HOWARD COUNTY ACT FOR THIS SUBDIVISION WILL BE FULFILLED BY ON-SITE KETENTION OF 2.74 ACRES ON EASEMENT "A" AND A PAYMENT OF FEE-IN-LIEU FOR 0.39 ACRES OF REFORESTATION. FEE-IN-LIEU FOR 0.39 ACRES (16,988.40 SQ. FT.) OF REFORESTATION IN THE AMOUNT OF \$ 12,741.30 WILL BE POSTED AT FINAL PLAN STAGE. NO CLEARING, GRADING OR CONSTRUCTION IS PERMITTED WITHIN THE FOREST CONSERVATION EASEMENT; HOWEVER, FOREST MANAGEMENT PRACTICES AS DEFINED IN THE DEED OF FOREST CONSERVATION EASEMENT ARE ALLOWED.
- 20. THIS PLAN HAS BEEN PREPARED IN ACCORDANCE WITH THE PROVISIONS OF SECTION 16.124 OF THE HOWARD COUNTY CODE AND THE LANDSCAPE MANUAL.
- 21. FINANCIAL SURETY FOR THE REQUIRED LANDSCAPING (35 SHADE TREES) AND ADDITIONAL (22 SHADE TREES) PROVIDED IN LIEU OF REMOVING 11 SPECIMEN TREES ÀS A CONDITION OF APPROVED WAIVER WP-15-079 IN THE AMOUNT OF \$17,100 TO BE POSTED AS PART OF THE DEVELOPER'S AGREEMENT.
- 22. A SURETY IN THE AMOUNT OF \$ 16,800 FOR (56 SHADE TREES) PUBLIC STREET TREES WILL BE ADDRESSED UNDER DED'S COST ESTIMATE.
- 23. PER SECTION 16.121(a) OF THE HOWARD COUNTY SUBDIVISION AND LAND USE REGULATIONS. OPEN SPACE FOR THIS SUBDIVISION HAS BEEN PROVIDED THROUGH THE CREATION OF OPEN SPACE LOTS 22 THRU 27.
- 24. A PRE-SUBMISSION COMMUNITY MEETING FOR THIS PROJECT WAS HELD ON JANUARY 10, 2015 AT 6:00 PM AT THE ELKRIDGE LIBRARY.
- 25. DEVELOPMENT REGULATIONS PER COUNCIL BILL 45-2003 AND THE ZONING REGULATIONS AS AMENDED BY COUNCIL BILL 75-2003. DEVELOPMENT OR CONSTRUCTION ON LOTS MUST COMPLY WITH SETBACK AND BUFFER REGULATIONS IN EFFECT AT THE TIME OF SUBMISSION OF THE BUILDING / GRADING PERMIT
- 26. ALL LOTS/RESIDENTIAL UNITS IN THIS SUBDIVISION ARE SUBJECT TO THE MIHU FEE-IN-LIEU REQUIREMENT THAT IS TO BE CALCULATED AND PAID TO THE DEPARTMENT OF INSPECTIONS, LICENSES AND PERMITS AT THE TIME OF BUILDING PERMIT ISSUANCE BY THE PERMIT APPLICANT.
- 27. THIS PLAN IS SUBJECT TO WP-15-079, WAIVING SECTIONS 16.1205(a)97) AND 16.1205(a)(10) WHICH REQUIRES THE RETENTION OF SPECIMEN TREES (30" dbh OR GREATER) THAT ARE NOT CONTAINED WITHIN OTHER PRIORITY FOREST RETENTION AREAS AS OUTLINED IN SECTION 16.1205(a)(1-10). WAIVER WAS APPROVED ON FEBRUARY 2, 2015 SUBJECT
- TO THE FOLLOWING CONDITIONS: 1. WAIVER APPROVAL IS LIMITED TO THE REMOVAL OF SPECIMEN TREES 1-11 AS DEPICTED ON THE WAIVER EXHIBIT. ANY PROPOSAL TO REMOVE ADDITIONAL SPECIMEN TREES WILL REQUIRE A NEW WAIVER REQUEST OR AN AMENDMENT TO THIS WAIVER REQUEST.
- 2. A MINIMUM OF 22 ADDITIONAL, NATIVE 2-3" CALIPER TREES SHALL BE PROVIDED ON SITE AS PART OF THE MITIGATION FOR THE SPECIMEN TREE REMOVAL. THIS MITIGATION WILL BE ADDRESSED WITH THE PROJECT KNOWN AS "PINE ACRES" AND WILL BE IN ADDITION TO ANY REQUIRED LANDSCAPE OR FOREST CONSERVATION PLANTINGS. THE MITIGATION WILL BE SHOWN ON THE ASSOCIATED LANDSCAPE PLAN AND SURETY FOR THESE ADDITIONAL TREES WILL BE REQUIRED AS PART OF THE FINAL PLAN.
- 3. SOME OR ALL THE MITIGATION PLANTINGS SHOULD BE PLACED WITHIN THE REAR YARDS OF THE PROPOSED LOTS AFTER GRADING AND FILL OCCURS BUT PRIOR TO SALES OF INDIVIDUAL LOTS.
- 28. ALL CONSTRUCTION SHALL BE IN ACCORDANCE WITH THE LATEST STANDARDS AND SPECIFICATIONS OF HOWARD COUNTY PLUS MSHA STANDARDS AND SPECIFICATIONS IF APPLICABLE.
- 29. THE CONTRACTOR SHALL NOTIFY THE DEPARTMENT OF PUBLIC WORKS / BUREAU OF ENGINEERING, CONSTRUCTION INSPECTION DIVISION AT (410)313-1880 AT LEAST FIVE (5) WORKING DAYS PRIOR TO THE START OF WORK.
- 30. THE CONTRACTOR SHALL NOTIFY "MISS UTILITY" AT 1-800-257-7777 AT LEAST 48 HOURS PRIOR TO ANY EXCAVATION WORK BEING DONE.
- 31. TRAFFIC CONTROL DEVICES: A. THE R1-1 (STOP) SIGN AND STREET NAME (SNS) SIGN ASSEMBLY FOR THIS DEVELOPMENT MUST BE INSTALLED BEFORE THE BASE PAVING IS COMPLETED. THE TRAFFIC CONTROL DEVICE LOCATIONS ON THE PLAN ARE APPROXIMATE AND MUST BE FIELD APPROVED, BY
- THE HOWARD COUNTY TRAFFIC DIVISION (410-313-2430) PRIOR TO INSTALLATION OF ANY TRAFFIC CONTROLL ALL TRAFFIC CONTROL DEVICES AND THEIR LOCATION SHALL BE IN ACCORDANCE WITH THE LATEST EDITION OF THE "MARYLAND MANUAL OF UNIFORM TRAFFIC CONTROL DEVICES" (MDMUTSD).
- ALL SIGN POSTS USED FOR TRAFFIC CONTROL SIGNS INSTALLED IN THE COUNTY RIGHT OF WAY SHALL BE MOUNTED ON A 2" GALVANIZED STEEL, PERFORATED, SQUARED TUBE SLEEVE (12 GAUGE) - 3' LONG. THE ANCHOR SHALL NOT EXTEND MORE THAN TWO "QUICK PUNCH" HOLES ABOVE GROUND LEVEL. A GALVANIZED STEEL POLE CAP SHALL BE MOUNTED ON TOP OF EACH POST
- 32. STREET LIGHT PLACEMENT AND TYPE OF FIXTURE AND POLE SHALL BE IN ACCORDANCE WITH THE HOWARD COUNTY DESIGN MANUAL, VOLUME III (2006) SECTION 5.5.A. A MINIMUM SPACING OF 20' SHALL BE MAINTAINED BETWEEN ANY STREET LIGHT AND ANY TREE.
- 33. THE NUMBER OF SIGNS NEEDED AND THE LOCATIONS OF THE "NO PARKING" SIGNS WILL BE DETERMINED IN THE FIELD BY TRAFFIC ENGINEERING.
- 34. DEVELOPER SHALL NOTIFY DEPARTMENT OF RECREATION AND PARKS BUREAU OF CAPITAL PROJECTS. PARK PLANNING AND CONSTRUCTION 10 WORKING DAYS PRIOR TO THE BEGINNING OF THE PATHWAY CONSTRUCTION, AT

SHE

 $\alpha$ 

of **12** 




F-16-024

RD COUNTY, MA SECTIONS

ROFILES

PLAN,


ROAD




F-16-024

ASSOC.

ROAD





### (B-4-2) STANDARDS AND SPECIFICATIONS FOR SOIL PREPARATION, TOPSOILING, AND SOIL AMENDMENTS THE PROCESS OF PREPARING THE SOILS TO SUSTAIN ADEQUATE VEGETATIVE STABILIZATION TO PROVIDE A SUITABLE SOIL MEDIUM FOR VEGETATIVE GROWTH. CONDITIONS WHERE PRACTICE APPLIES WHERE VEGETATIVE STABILIZATION IS TO BE ESTABLISHED. A. SOIL PREPARATION 1. TEMPORARY STABILIZATION a. SEEDBED PREPARATION CONSISTS OF LOOSENING SOIL TO A DEPTH OF 3 TO 5 INCHES BY MEANS OF SUITABLE AGRICULTURAL OR CONSTRUCTION EQUIPMENT, SUCH AS DISC HARROWS OR CHISEL PLOWS OR RIPPERS MOUNTED ON CONSTRUCTION EQUIPMENT. AFTER THE SOIL IS LOOSENED, IT MUST NOT BE ROLLED OR DRAGGED SMOOTH BUT LEFT IN THE ROUGHENED CONDITION. SLOPES 3:1 OR FLATTER ARE TO BE TRACKED WITH RIDGES RUNNING PARALLEL TO THE CONTOUR OF THE SLOPE. APPLY FERTILIZER AND LIME AS PRESCRIBED ON THE PLANS. INCORPORATE LIME AND FERTILIZER INTO THE TOP 3 TO 5 INCHES OF SOIL BY DISKING OR OTHER 2. PERMANENT STABILIZATION a. A SOIL TEST IS REQUIRED FOR ANY EARTH DISTURBANCE OF 5 ACRES OR MORE. THE MINIMUM SOIL CONDITIONS REQUIRED FOR PERMANENT VEGETATIVE ESTABLISHMENT ARE: I SOIL PH BETWEEN 6.0 AND 7.0. II. SOLUBLE SALTS LESS THAN 500 PARTS PER MILLION (PPM) III. SOIL CONTAINS LESS THAN 40 PERCENT CLAY BUT ENOUGH FINE GRAINED MATERIAL (GREATER THAN 30 PERCENT SILT PLUS CLAY) TO PROVIDE THE CAPACITY TO HOLD A MODERATE AMOUNT OF MOISTURE. AN EXCEPTION: IF LOVEGRASS WILL BE PLANTED, THEN A SANDY SOIL (LESS THAN 30 PERCENT SILT PLUS CLAY) WOULD BE ACCEPTABLE. IV. SOIL CONTAINS 1.5 PERCENT MINIMUM ORGANIC MATTER BY WEIGHT. V. SOIL CONTAINS SUFFICIENT PORE SPACE TO PERMIT ADEQUATE ROOT PENETRATION. APPLICATION OF AMENDMENTS OR TOPSOIL IS REQUIRED IF ON-SITE SOILS DO NOT MEET THE ABOVE GRADED AREAS MUST BE MAINTAINED IN A TRUE AND EVEN GRADE AS SPECIFIED ON THE APPROVED PLAN, THEN SCARIFIED OR OTHERWISE LOOSENED TO A DEPTH OF 3 TO 5 INCHES. APPLY SOIL AMENDMENTS AS SPECIFIED ON THE APPROVED PLAN OR AS INDICATED BY THE RESULTS OF MIX SOIL AMENDMENTS INTO THE TOP 3 TO 5 INCHES OF SOIL BY DISKING OR OTHER SUITABLE MEANS. RAKE LAWN AREAS TO SMOOTH THE SURFACE, REMOVE LARGE OBJECTS LIKE STONES AND BRANCHES, AND READY THE AREA FOR SEED APPLICATION. LOOSEN SURFACE SOIL BY DRAGGING WITH A HEAVY CHAIN OR OTHER EQUIPMENT TO ROUGHEN THE SURFACE WHERE SITE CONDITIONS WILL NOT PERMIT NORMAL SEEDBED PREPARATION. TRACK SLOPES 3:1 OR FLATTER WITH TRACKED EQUIPMENT LEAVING THE SOIL IN AN IRREGULAR CONDITION WITH RIDGES RUNNING PARALLEL TO THE CONTOUR OF THE SLOPE. LEAVE THE TOP 1 TO 3 INCHES OF SOIL LOOSE AND FRIABLE. SEEDBED LOOSENING MAY BE UNNECESSARY ON NEWLY TOPSOIL IS PLACED OVER PREPARED SUBSOIL PRIOR TO ESTABLISHMENT OF PERMANENT VEGETATION. THE PURPOSE IS TO PROVIDE A SUITABLE SOIL MEDIUM FOR VEGETATIVE GROWTH. SOILS OF CONCERN HAVE LOW MOISTURE CONTENT, LOW NUTRIENT LEVELS, LOW PH, MATERIALS TOXIC TO PLANTS, AND/OR UNACCEPTABLE TOPSOIL SALVAGED FROM AN EXISTING SITE MAY BE USED PROVIDED IT MEETS THE STANDARDS AS SET FORTH IN THESE SPECIFICATIONS. TYPICALLY, THE DEPTH OF TOPSOIL TO BE SALVAGED FOR A GIVEN SOIL TYPE CAN BE FOUND IN THE REPRESENTATIVE SOIL PROFILE SECTION IN THE SOIL SURVEY PUBLISHED BY TOPSOILING IS LIMITED TO AREAS HAVING 2:1 OR FLATTER SLOPES WHERE: THE TEXTURE OF THE EXPOSED SUBSOIL/PARENT MATERIAL IS NOT ADEQUATE TO PRODUCE VEGETATIVE THE SOIL MATERIAL IS SO SHALLOW THAT THE ROOTING ZONE IS NOT DEEP ENOUGH TO SUPPORT PLANTS OR FURNISH CONTINUING SUPPLIES OF MOISTURE AND PLANT NUTRIENTS. THE ORIGINAL SOIL TO BE VEGETATED CONTAINS MATERIAL TOXIC TO PLANT GROWTH. THE SOIL IS SO ACIDIC THAT TREATMENT WITH LIMESTONE IS NOT FEASIBLE. AREAS HAVING SLOPES STEEPER THAN 2:1 REQUIRE SPECIAL CONSIDERATION AND DESIGN. TOPSOIL SPECIFICATIONS: SOIL TO BE USED AS TOPSOIL MUST MEET THE FOLLOWING CRITERIA TOPSOIL MUST BE A LOAM, SANDY LOAM, CLAY LOAM, SILT LOAM, SANDY CLAY LOAM, OR LOAMY SAND. OTHER SOILS MAY BE USED IF RECOMMENDED BY AN AGRONOMIST OR SOIL SCIENTIST AND APPROVED BY HE APPROPRIATE APPROVAL AUTHORITY. TOPSOIL MUST NOT BE A MIXTURE OF CONTRASTING TEXTURED SUBSOILS AND MUST CONTAIN LESS THAN 5 PERCENT BY VOLUME OF CINDERS, STONES, SLAG, COARSE FRAGMENTS, GRAVEL, STICKS, ROOTS, TRASH, OR OTHER MATERIALS LARGER THAN 11/2 INCHES IN DIAMETER. TOPSOIL MUST BE FREE OF NOXIOUS PLANTS OR PLANT PARTS SUCH AS BERMUDA GRASS, QUACK GRASS, JOHNSON GRASS, NUT SEDGE, POISON IVY, THISTLE, OR OTHERS AS SPECIFIED. TOPSOIL SUBSTITUTES OR AMENDMENTS, AS RECOMMENDED BY A QUALIFIED AGRONOMIST OR SOIL SCIENTIST AND APPROVED BY THE APPROPRIATE APPROVAL AUTHORITY, MAY BE USED IN LIEU OF NATURAL EROSION AND SEDIMENT CONTROL PRACTICES MUST BE MAINTAINED WHEN APPLYING TOPSOIL UNIFORMLY DISTRIBUTE TOPSOIL IN A 5 TO 8 INCH LAYER AND LIGHTLY COMPACT TO A MINIMUM THICKNESS OF 4 INCHES. SPREADING IS TO BE PERFORMED IN SUCH A MANNER THAT SODDING OR SEEDING CAN PROCEED WITH A MINIMUM OF ADDITIONAL SOIL PREPARATION AND TILLAGE. ANY IRREGULARITIES IN THE SURFACE RESULTING FROM TOPSOILING OR OTHER OPERATIONS MUST BE CORRECTED IN ORDER TO PREVENT THE FORMATION OF DEPRESSIONS OR WATER POCKETS. TOPSOIL MUST NOT BE PLACED IF THE TOPSOIL OR SUBSOIL IS IN A FROZEN OR MUDDY CONDITION, WHEN THE SUBSOIL IS EXCESSIVELY WET OR IN A CONDITION THAT MAY OTHERWISE BE DETRIMENTAL TO PROPER GRADING AND SEEDBED PREPARATION. C. SOIL AMENDMENTS (FERTILIZER AND LIME SPECIFICATIONS) 1. SOIL TESTS MUST BE PERFORMED TO DETERMINE THE EXACT RATIOS AND APPLICATION RATES FOR BOTH PERFORMED BY A RECOGNIZED PRIVATE OR COMMERCIAL LABORATORY. SOIL SAMPLES TAKEN FOR ENGINEERING PURPOSES MAY ALSO BE USED FOR CHEMICAL ANALYSES. FERTILIZERS MUST BE UNIFORM IN COMPOSITION, FREE FLOWING AND SUITABLE FOR ACCURATE APPLICATION BY APPROPRIATE EQUIPMENT. MANURE MAY BE SUBSTITUTED FOR FERTILIZER WITH PRIOR APPROVAL FROM THE APPROPRIATE APPROVAL AUTHORITY. FERTILIZERS MUST ALL BE DELIVERED TO THE SITE FULLY LABELED ACCORDING TO THE APPLICABLE LAWS AND MUST BEAR THE NAME, TRADE NAME OR TRADEMARK AND LIME MATERIALS MUST BE GROUND LIMESTONE (HYDRATED OR BURNT LIME MAY BE SUBSTITUTED EXCEPT WHEN HYDROSEEDING) WHICH CONTAINS AT LEAST 50 PERCENT TOTAL OXIDES (CALCIUM OXIDE PLUS MAGNESIUM OXIDE). LIMESTONE MUST BE GROUND TO SUCH FINENESS THAT AT LEAST 50 PERCENT WILL PASS THROUGH A #100 MESH SIEVE AND 98 TO 100 PERCENT WILL PASS THROUGH A #20 MESH SIEVE. LIME AND FERTILIZER ARE TO BE EVENLY DISTRIBUTED AND INCORPORATED INTO THE TOP 3 TO 5 INCHES OF SOIL BY DISKING OR OTHER SUITABLE MEANS. WHERE THE SUBSOIL IS EITHER HIGHLY ACIDIC OR COMPOSED OF HEAVY CLAYS, SPREAD GROUND LIMESTONE AT THE RATE OF 4 TO 8 TONS/ACRE (200-400 POUNDS PER 1,000 SQUARE FEET) PRIOR TO THE STANDARD SEDIMENT CONTROL NOTES WORKS, CONSTRUCTION INSPECTION DIVISION (CID), 410-313-1855 AFTER THE FUTURE LOD AND ENGINEER'S CERTIFICATE I CERTIFY THAT THIS PLAN FOR EROSION AND SEDIMENT CONTROL REPRESENT: A PRACTICAL AND WORKABLE PLAN BASED ON MY PERSONAL KNOWLEDGE OF THE SITE CONDITIONS AND THAT IT WAS PREPARED IN ACCORDANCE WITH THE REQUIREMENTS OF THE HOWARD SOIL CONSERVATION DISTRICT.

SIGNATURE OF ENGINEER

R. JACOB HIKMAT, PE

PRINTED NAME OF ENGINEER

DEVELOPERS CERTIFICATE

CERTIFY THAT ALL DEVELOPMENT AND CONSTRUCTION WILL BE DONE

INVOLVED IN THE CONSTRUCTION PROJECT WILL HAVE A CERTIFICATE OF

TRAINING PROGRAM FOR THE CONTROL OF SEDIMENT AND EROSION BEFORE

THIS DEVELOPMENT PLAN IS APPROVED FOR SOIL EROSION AND SEDIMENT

CONTROL BY THE HOWARD SOIL CONSERVATION DISTRICT.

Divards Stak

APPROVED: DEPARTMENT OF PLANNING AND ZONING

CHIEF, DEVELOPMENT ENGINEERING DIVISION

CHIEF, DIVISION OF LAND DEVELOPMENT

ACCORDING TO THIS PLAN, AND THAT ANY RESPONSIBLE PERSONNEL

ATTENDANCE AT A DEPARTMENT OF THE ENVIRONMENT APPROVED

to conquet periodic on—site inspection. 🖍

HOWARD SOIL CONSERVATION DISTRIC

CHIEF, BUREAU OF HIGHWAYS

Chil Edwisom

APPROVED: DEPARTMENT OF PUBLIC WORKS

PROTECTED AREAS ARE MARKED CLEARLY IN THE FIELD. A MINIMUM OF 48 HOUR NOTICE TO CID MUST BE GIVEN AT THE FOLLOWING STAGES: PRIOR TO THE START OF EARTH DISTURBANCE UPON COMPLETION OF THE INSTALLATION OF PERIMETER EROSION AND SEDIMENT CONTROLS, BUT BEFORE PROCEEDING WITH ANY OTHER EARTH DISTURBANCE OR GRADING, PRIOR TO THE START OF ANOTHER PHASE OF CONSTRUCTION OR OPENING OF ANOTHER PRIOR TO THE REMOVAL OR MODIFICATION OF SEDIMENT CONTROL PRACTICES. OTHER BUILDING OR GRADING INSPECTION APPROVALS MAY NOT BE AUTHORIZED UNTIL THIS INITIAL APPROVAL BY THE INSPECTION AGENCY IS MADE. OTHER RELATED STATE AND FEDERAL PERMITS SHALL BE REFERENCED, TO ENSURE COORDINATION AND TO AVOID CONFLICTS WITH THIS ALL VEGETATIVE AND STRUCTURAL PRACTICES ARE TO BE INSTALLED ACCORDING TO THE PROVISIONS OF THIS PLAN AND ARE TO BE IN CONFORMANCE WITH THE 2011 MARYLAND STANDARDS AND SPECIFICATIONS FOR SOIL EROSION AND SEDIMENT CONTROL, AND REVISIONS FOLLOWING INITIAL SOIL DISTURBANCE OR RE-DISTURBANCE, PERMANENT OR TEMPORARY STABILIZATION IS REQUIRED WITHIN THREE (3) CALENDAR DAYS AS TO THE SURFACE OF ALL BEGINNING THE PROJECT. HOWARD SOIL CONSERVATION DISTRICT IS AUTHORIZED PERIMETER CONTROLS, DIKES, SWALES, DITCHES, PERIMETER SLOPES, AND ALL SLOPES STEEPER THAN 3 HORIZONTAL TO 1 VERTICAL (3:1); AND SEVEN (7) CALENDAR DAYS AS TO ALL OTHER DISTURBED AREAS ON THE PROJECT SITE EXCEPT FOR THOSE AREAS UNDER ACTIVE GRADING. ALL DISTURBED AREAS MUST BE STABILIZED WITHIN THE TIME PERIOD SPECIFIED ABOVE IN ACCORDANCE WITH THE 2011 MARYLAND STANDARD AND SPECIFICATIONS FOR SOIL EROSION AND SEDIMENT CONTROL FOR TOPSOIL (SEC. B-4-2), PERMANENT SEEDING (SEC. B-4-5), TEMPORARY SEEDING (SEC. B-4-4) AND MULCHING (SEC. B-4-3). TEMPORARY STABILIZATION WITH MULCH ALONE CAN ONLY BE APPLIED BETWEEN THE FALL AND SPRING SEEDING DATES IF THE GROUND IS FROZEN. INCREMENTAL STABILIZATION (SEC. B-4-1) SPECIFICATIONS SHALL BE

ENFORCED IN AREAS WITH >15' OF CUT AND/OR FILL. STOCKPILES (SEC. B-4-8) IN EXCESS OF

SITE ANALYSIS:

TOTAL AREA OF SITE

AREA TO BE ROOFED OR PAVED:

AREA DISTURBED

TOTAL FILL

R. JACOB HIKMAT P.E

DATE

11-03-16

20 FT. MUST BE BENCHED WITH STABLE OUTLET. ALL CONCENTRATED FLOW, STEEP SLOPE, AND HIGHLY ERODIBLE AREAS SHALL RECEIVE SOIL STABILIZATION MATTING (SEC. B-4-6). ALL SEDIMENT CONTROL STRUCTURES ARE TO REMAIN IN PLACE, AND ARE TO BE MAINTAINED IN OPERATIVE CONDITION UNTIL PERMISSION FOR THEIR REMOVAL HAS BEEN OBTAINED FROM THE. 12.03 ACRES \_\_ACRES THERE IS NO AS-BUILT AREA TO BE VEGETATIVE STABILIZED: \_\_1.20\_\_ \_\_\_\_ACRES --3,500\_\_\_ \_\_\_CU. YDS. INFORMATION PROVIDED \_3,500\_\_\_\_CU. YDS. ON THIS SHEET OFFSITE WASTE/BORROW AREA LOCATION: OF MARK HEREBY CERTIFY THAT THESE DOCUMENTS WERE COB HIL PREPARED OR APPROVED BY ME AND THAT I AM A DULY LICENSED PROFESSIONAL ENGINEER UNDER THE LAWS OF THE STATE OF MARYLAND, LICENSE NO. 17942, EXP DATE 09/03/16

SONAL .

(B-4-3) STANDARDS AND SPECIFICATIONS

FOR SEEDING AND MULCHING

TO THE SURFACE OF ALL PERIMETER CONTROLS, SLOPES, AND ANY DISTURBED AREA NOT UNDER ACTIVE GRADING.

a. ALL SEED MUST MEET THE REQUIREMENTS OF THE MARYLAND STATE SEED LAW. ALL SEED MUST BE SUBJECT TO RE—TESTING BY A RECOGNIZED SEED LABORATORY. ALL SEED USED MUST HAVE BEEN TESTED WITHIN THE 6

MONTHS IMMEDIATELY PRECEDING THE DATE OF SOWING SUCH MATERIAL ON ANY PROJECT. REFER TO TABLE

b. MULCH ALONE MAY BE APPLIED BETWEEN THE FALL AND SPRING SEEDING DATES ONLY IF THE GROUND IS

C. INOCULANTS: THE INOCULANT FOR TREATING LEGUME SEED IN THE SEED MIXTURES MUST BE A PURE CULTURE OF NITROGEN FIXING BACTERIA PREPARED SPECIFICALLY FOR THE SPECIES. INOCULANTS MUST NOT BE USED

USE FOUR TIMES THE RECOMMENDED RATE WHEN HYDROSEEDING. NOTE: IT IS VERY IMPORTANT TO KEEP

d. SOD OR SEED MUST NOT BE PLACED ON SOIL WHICH HAS BEEN TREATED WITH SOIL STERILANTS OR

CHEMICALS USED FOR WEED CONTROL UNTIL SUFFICIENT TIME HAS ELAPSED (14 DAYS MIN.) TO PERMIT

I. INCORPORATE SEED INTO THE SUBSOIL AT THE RATES PRESCRIBED ON TEMPORARY SEEDING TABLE B.1,

II. APPLY SEED IN TWO DIRECTIONS, PERPENDICULAR TO EACH OTHER. APPLY HALF THE SEEDING RATE IN

b. DRILL OR CULTIPACKER SEEDING: MECHANIZED SEEDERS THAT APPLY AND COVER SEED WITH SOIL

EACH DIRECTION. ROLL THE SEEDED AREA WITH A WEIGHTED ROLLER TO PROVIDE GOOD SEED TO SOIL

I. CULTIPACKING SEEDERS ARE REQUIRED TO BURY THE SEED IN SUCH A FASHION AS TO PROVIDE AT LEAST

I. IF FERTILIZER IS BEING APPLIED AT THE TIME OF SEEDING, THE APPLICATION RATES SHOULD NOT EXCEED

THE FOLLOWING: NITROGEN, 100 POUNDS PER ACRE TOTAL OF SOLUBLE NITROGEN; P2 O5(PHOSPHOROUS),

II. APPLY SEED IN TWO DIRECTIONS, PERPENDICULAR TO EACH OTHER. APPLY HALF THE SEEDING RATE IN

c. HYDROSEEDING: APPLY SEED UNIFORMLY WITH HYDROSEEDER (SLURRY INCLUDES SEED AND FERTILIZER).

II. LIME: USE ONLY GROUND AGRICULTURAL LIMESTONE (UP TO 3 TONS PER ACRE MAY BE APPLIED BY HYDROSEEDING). NORMALLY, NOT MORE THAN 2 TONS ARE APPLIED BY HYDROSEEDING AT ANY ONE

a. STRAW CONSISTING OF THOROUGHLY THRESHED WHEAT, RYE, OAT, OR BARLEY AND REASONABLY BRIGHT IN

COLOR. STRAW IS TO BE FREE OF NOXIOUS WEED SEEDS AS SPECIFIED IN THE MARYLAND SEED LAW AND NOT MUSTY, MOLDY, CAKED, DECAYED, OR EXCESSIVELY DUSTY. NOTE: USE ONLY STERILE STRAW MULCH IN

III. MIX SEED AND FERTILIZER ON SITE AND SEED IMMEDIATELY AND WITHOUT INTERRUPTION.

b. WOOD CELLULOSE FIBER MULCH (WCFM) CONSISTING OF SPECIALLY PREPARED WOOD CELLULOSE

II. WCFM, INCLUDING DYE, MUST CONTAIN NO GERMINATION OR GROWTH INHIBITING FACTORS.

V. WCFM MUST CONFORM TO THE FOLLOWING PHYSICAL REQUIREMENTS: FIBER LENGTH OF

I. WOFM IS TO BE DYED GREEN OR CONTAIN A GREEN DYE IN THE PACKAGE THAT WILL PROVIDE AN

III. WCFM MATERIALS ARE TO BE MANUFACTURED AND PROCESSED IN SUCH A MANNER THAT THE WOOD CELLULOSE FIBER MULCH WILL REMAIN IN UNIFORM SUSPENSION IN WATER UNDER AGITATION AND WILL

BLEND WITH SEED, FERTILIZER AND OTHER ADDITIVES TO FORM A HOMOGENEOUS SLURRY. THE MULCH

MATERIAL MUST FORM A BLOTTER-LIKE GROUND COVER, ON APPLICATION, HAVING MOISTURE ABSORPTION

AND PERCOLATION PROPERTIES AND MUST COVER AND HOLD GRASS SEED IN CONTACT WITH THE SOIL

IV. WCFM MATERIAL MUST NOT CONTAIN ELEMENTS OR COMPOUNDS AT CONCENTRATION LEVELS THAT WILL

APPROXIMATELY 10 MILLIMETERS, DIAMETER APPROXIMATELY 1 MILLIMETER, PH RANGE OF 4.0 TO 8.5,

WHEN STRAW MULCH IS USED, SPREAD IT OVER ALL SEEDED AREAS AT THE RATE OF 2 TONS PER ACRE

TO A UNIFORM LOOSE DEPTH OF 1 TO 2 INCHES. APPLY MULCH TO ACHIEVE A UNIFORM DISTRIBUTION AND

ACRE. MIX THE WOOD CELLULOSE FIBER WITH WATER TO ATTAIN A MIXTURE WITH A MAXIMUM OF 50 POUNDS

OR WATER. THIS MAY BE DONE BY ONE OF THE FOLLOWING METHODS (LISTED BY PREFERENCE), DEPENDING

DEPTH SO THAT THE SOIL SURFACE IS NOT EXPOSED. WHEN USING A MULCH ANCHORING TOOL, INCREASE

WOOD CELLULOSE FIBER USED AS MULCH MUST BE APPLIED AT A NET DRY WEIGHT OF 1500 POUNDS PER

PERFORM MULCH ANCHORING IMMEDIATELY FOLLOWING APPLICATION OF MULCH TO MINIMIZE LOSS BY WIND

I. A MULCH ANCHORING TOOL IS A TRACTOR DRAWN IMPLEMENT DESIGNED TO PUNCH AND ANCHOR MULCH

II. WOOD CELLULOSE FIBER MAY BE USED FOR ANCHORING STRAW. APPLY THE FIBER BINDER AT A NET DRY

WEIGHT OF 750 POUNDS PER ACRE. MIX THE WOOD CELLULOSE FIBER WITH WATER AT A MAXIMUM OF

III. SYNTHETIC BINDERS SUCH AS ACRYLIC DLR (AGRO-TACK), DCA-70, PETROSET, TERRA TAX II, TERRA TACK AR OR OTHER APPROVED EQUAL MAY BE USED. FOLLOW APPLICATION RATES AS SPECIFIED BY THE

MANUFACTURER. APPLICATION OF LIQUID BINDERS NEEDS TO BE HEAVIER AT THE EDGES WHERE WIND

RECOMMENDATIONS. NETTING IS USUALLY AVAILABLE IN ROLLS 4 TO 15 FEET WIDE AND 300 TO 3,000

IV. LIGHTWEIGHT PLASTIC NETTING MAY BE STAPLED OVER THE MULCH ACCORDING TO MANUFACTURER

BUT IS LIMITED TO FLATTER SLOPES WHERE EQUIPMENT CAN OPERATE SAFELY. IF USED ON SLOPING LAND

ASH CONTENT OF 1.6 PERCENT MAXIMUM AND WATER HOLDING CAPACITY OF 90 PERCENT MINIMUM.

APPROPRIATE COLOR TO FACILITATE VISUAL INSPECTION OF THE UNIFORMLY SPREAD SLURRY.

INOCULANT AS COOL AS POSSIBLE UNTIL USED. TEMPERATURES ABOVE 75 TO 80 DEGREES FAHRENHEIT CAN

LATER THAN THE DATE INDICATED ON THE CONTAINER. ADD FRESH INOCULANTS AS DIRECTED ON THE PACKAGE.

FROZEN. THE APPROPRIATE SEEDING MIXTURE MUST BE APPLIED WHEN THE GROUND THAWS.

a. DRY SEEDING: THIS INCLUDES USE OF CONVENTIONAL DROP OR BROADCAST SPREADERS.

PERMANENT SEEDING TABLE B.3, OR SITE-SPECIFIC SEEDING SUMMARIES.

1/4 INCH OF SOIL COVERING. SEEDBED MUST BE FIRM AFTER PLANTING.

200 POUNDS PER ACRE; K20 (POTASSIUM), 200 POUNDS PER ACRE.

TIME. DO NOT USE BURNT OR HYDRATED LIME WHEN HYDROSEEDING.

IV. WHEN HYDROSEEDING DO NOT INCORPORATE SEED INTO THE SOIL.

B.4 REGARDING THE QUALITY OF SEED. SEED TAGS MUST BE AVAILABLE UPON REQUEST TO THE INSPECTOR TO

THE APPLICATION OF SEED AND MULCH TO ESTABLISH VEGETATIVE COVER.

WEAKEN BACTERIA AND MAKE THE INOCULANT LESS EFFECTIVE.

CONDITIONS WHERE PRACTICE APPLIES

VERIFY TYPE OF SEED AND SEEDING RATE

DISSIPATION OF PHYTO-TOXIC MATERIALS.

1. MULCH MATERIALS (IN ORDER OF PREFERENCE)

AREAS WHERE ONE SPECIES OF GRASS IS DESIRED

PROCESSED INTO A UNIFORM FIBROUS PHYSICAL STATE.

THE APPLICATION RATE TO 2.5 TONS PER ACRE.

OF WOOD CELLULOSE FIBER PER 100 GALLONS OF WATER.

UPON THE SIZE OF THE AREA AND EROSION HAZARD:

50 POUNDS OF WOOD CELLULOSE FIBER PER 100 GALLONS OF WATER.

CATCHES MULCH, SUCH AS IN VALLEYS AND ON CRESTS OF BANKS.

HIS PRACTICE SHOULD FOLLOW THE CONTOUR.

WITHOUT INHIBITING THE GROWTH OF THE GRASS SEEDLINGS.

APPLY MULCH TO ALL SEEDED AREAS IMMEDIATELY AFTER SEEDING.

TO PROTECT DISTURBED SOILS FROM EROSION DURING AND AT THE END OF CONSTRUCTION.

DEFINITION

A. SEEDING

1. SPECIFICATIONS

2. APPLICATION

A PRE-CONSTRUCTION MEETING MUST OCCUR WITH THE HOWARD COUNTY DEPARTMENT OF PUBLIC 7. ANY SEDIMENT CONTROL PRACTICE WHICH IS DISTURBED BY GRADING ACTIVITY FOR PLACEMENT OF UTILITIES MUST BE REPAIRED ON THE SAME DAY OF DISTURBANCE.

> ADDITIONAL SEDIMENT CONTROL MUST BE PROVIDED, IF DEEMED NECESSARY BY THE CID. THE SITE AND ALL CONTROLS SHALL BE INSPECTED BY THE CONTRACTOR WEEKLY; AND THE NEXT DAY AFTER EACH RAIN EVENT. A WRITTEN REPORT BY THE CONTRACTOR, MADE AVAILABLE UPON REQUEST, IS PART OF EVERY INSPECTION AND SHOULD

-INSPECTION TYPE (ROUTINE, PRE-STORM EVENT, DURING RAIN EVENT) -NAME AND TITLE OF INSPECTOR

-WEATHER INFORMATION (CURRENT CONDITIONS AS WELL AS TIME AND AMOUNT OF LAST RECORDED PRECIPITATION) -BRIEF DESCRIPTION OF PROJECT'S STATUS (E.G., PERCENT COMPLETE) AND/OR CURRENT ACTIVITIES -EVIDENCE OF SEDIMENT DISCHARGES

-IDENTIFICATION OF PLAN DEFICIENCIES -IDENTIFICATION OF SEDIMENT CONTROLS THAT REQUIRE MAINTENANCE -IDENTIFICATION OF MISSING OR IMPROPERLY INSTALLED SEDIMENT CONTROLS -COMPLIANCE STATUS REGARDING THE SEQUENCE OF CONSTRUCTION AND

STABILIZATION REQUIREMENTS —PHOTOGRAPHS -MONITORING/SAMPLING -MAINTENANCE AND/OR CORRECTIVE ACTION PERFORMED -OTHER INSPECTION ITEMS AS REQUIRED BY THE GENERAL PERMIT FOR

9. TRENCHES FOR THE CONSTRUCTION OF UTILITIES IS LIMITED TO THREE PIPE LENGTHS OR THAT WHICH CAN AND SHALL BE BACK-FILLED AND STABILIZED BY THE END OF EACH WORKDAY, 10. ANY MAJOR CHANGES OR REVISIONS TO THE PLAN OR SEQUENCE OF CONSTRUCTION MUST BE

STORMWATER ASSOCIATED WITH CONSTRUCTION ACTIVITIES (NPDES, MDE).

REVIEWED AND APPROVED BY THE HSCD PRIOR TO PROCEEDING WITH CONSTRUCTION. MINOR REVISIONS MAY ALLOWED BY THE CID PER THE LIST OF HSCD-APPROVED FIELD CHANGES. DISTURBANCE SHALL NOT OCCUR OUTSIDE THE L.O.D. A PROJECT IS TO BE SEQUENCED SO THAT GRADING ACTIVITIES BEGIN ON ONE GRADING UNIT (MAXIMUM ACREAGE OF 20 AC. PER

GRADING UNIT) AT A TIME. WORK MAY PROCEED TO A SUBSEQUENT GRADING UNIT WHEN AT LEAST 50 PERCENT OF THE DISTURBED AREA IN THE PRECEDING GRADING UNIT HAS BEEN STABILIZED AND APPROVED BY THE CID. UNLESS OTHERWISE SPECIFIED AND APPROVED BY THE CID. NO MORE THAN 30 ACRES CUMULATIVELY MAY BE DISTURBED AT A GIVEN TIME. 12. WASH WATER FROM ANY EQUIPMENT, VEHICLES, WHEELS, PAVEMENT, AND OTHER SOURCES

MUST BE TREATED IN A SEDIMENT BASIN OR OTHER APPROVED WASHOUT STRUCTURE. 13. TOPSOIL SHALL BE STOCKPILED AND PRESERVED ON-SITE FOR REDISTRIBUTION ONTO FINAL

14. ALL SILT FENCE AND SUPER SILT FENCE SHALL BE PLACED ON-THE-CONTOUR, AND BE IMBERICATED AT 25' MINIMUM INTERVALS, WITH LOWER ENDS CURLED UPHILL BY 2' IN 15. STREAM CHANNELS MUST NOT BE DISTURBED DURING THE FOLLOWING RESTRICTED TIME

PERIODS (INCLUSIVE):

USE I AND IP MARCH 1 - JUNE 15.

USE III AND IIIP OCTOBER 1 - APRIL 30

USE IV MARCH 1 - MAY 31 16. A COPY OF THIS PLAN, THE 2011 MARYLAND STANDARDS AND SPECIFICATIONS FOR SOIL EROSION AND SEDIMENT CONTROL AND ASSOCIATED PERMITS SHALL BE ON-SITE AND AVAILABLE WHEN THE SITE IS ACTIVE.

(B-4-5) STANDARDS AND SPECIFICATIONS FOR PERMANENT STABILIZATION

TO STABILIZE DISTURBED SOIL WITH PERMANENT VEGETATION. TO USE LONG-LIVED PERENNIAL GRASSES AND LEGUMES TO ESTABLISH PERMANENT GROUND COVER OF DISTURBED

CONDITIONS WHERE PRACTICE APPLIES EXPOSED SOILS WHERE GROUND COVER IS NEEDED FOR 6 MONTHS OR MORE. CRITERIA A. SEED MIXTURES

1. GENERAL USE

A. SELECT ONE OR MORE OF THE SPIECES OF MIXTURES LISTED IN TABLE B.3 FOR THE APPROPRIATE PLANT HARDINESS ZONE (FROM FIGURE B.3) AND BASED IN THE SITE CONDITION OR PURPOSE FOUND ON TABLE B.2. ENTER SELECTED MIXTURE(S), APPLICATION RATES, AND SEEDING DATES IN THE PERMANENT SEEDING SUMMARY

B. ADDITIONAL PLANTING SPECIFICATIONS FOR EXCEPTIONAL SITES SUCH AS SHORELINES, STREAM BANKS, OR DINES OR FOR SPECIAL PURPOSES SUCH AS WILDLIFE OR AESTHETIC TREATMENT MAY BE FOUND IN USDA-NRCS TECHNICAL FIELD GUIDE, SECTION 342-CRITICAL AREA PLANTING. FOR SITES HAVING DISTURBAD AREA OVER 5 ACRES, USE AND SHOW RATES RECOMMENDED BY THE

D. FOR AREAS RECEIVING LOW MAINTENANCE, APPLY UREA FROM FERTILIZED (40-0-01) AT 3 1/2 POUNDS PER 1000 S.F. (150 POUNDS PER ACRE) AT THE TIME OF SEEDING IN ADDITION TO THE SOIL AMENDMENTS SHOWN IN THE PERMANENT SEEDING SUMMARY.

AREAS WHERE TURFGRASS MAY BE DESIRE INCLUDE LAWNS, PARKS, PLAYGROUNDS, AND COMMERCIAL SITES WHICH WILL RECEIVE A MEDIUM TO HIGH LEVEL OF MAINTENANCE. SELECT ONE OR MORE OF THE SPECIES OF MIXTURES LISTED BELOW BASED ON THE SITE CONDITIONS OR PURPOSE. ENTER SELECTED MIXTURE(S), APPLOCATION RATES, AND SEEDING

DATES IN THE PERMANENT SEEDING SUMMARY. KENTUCKY BLUEGRASS: FULL SUN MIXTURE: FOR USE IN AREAS THAT RECEIVE INTENSIVE MANAGEMENT. IRRIGATION REQUIRED IN THE AREAS OF CENTRAL MARYLAND AND EASRERN SHORE RECOMMENDED CERTIFIED KENTUCKY BLUEGRASS SEEDING RETA: 1.5 TO 2.0 POUNDS PER 1000 S.I CHOOSE A MINIMUM OF THREE KENTUCKY BLUEGRASS CULTIVARS WITH EACH RANGING FROM 10 T 35 PERCENT OF THE TOTAL MIXTURE BY WEIGHT.

II. KENTUCKY BLUEGRASS/PERENIAL RYE: FULL SUN MIXTURE: FOR USE IN FULL SUN AREAS WHERE RAPID ESTABLISHMENT IS NECESSARY ABD WHEN TURF WILL RECEIVE MEDIUM TO INTENSUVE MANAGEMENT. CERTIFIED PERENIAL RYEGRASS CULTIVARS/CERTIFIED KENTUCKY BLUEGRASS SEEDINGRATE: 2 POUNDS MIXTURE PER 1000 S.F. SHOOSE A MINIMUM OF THREE KENTUCKYBLUEGRASS CULTIVARS EITH EACH RANGING FROM 10 TO 35 PERCENT OF THE TOTAL MIXTURE BY WEIGHT

III. TALL FESCUE/KENTUCKY BLUEGRASS: FULL MIXTURE: FOR USE IN DROUGHT AREAS AND/OR FOR AREAS RECEIVING LOW TO MEDIUM MANAGEENT IN FULL SUN TO MEDIUM SHADE, RECOMMENDED MIXTURE INCLUDES; CERTIFIED TALL FESCUE CULTIVARS 65 TO 100 PERCENT. CERTIFIED KENTUCKY BLUEGRASS CULTIVARS 0 TO 5 PERCENT. SEEDING RATE: 5 TO 8 PERCENT PER 1000 S.F. ONE OR MORE CULTIVARS MAY BE BLENDED. IV. KENTUCKY BLUEGRASS/FINE FESCUE: SHADE MIXTURE: FOR USE IN AREAS WITH SHADE IN BLUEGRASS LAWNS. FOR ESTABLISHMENT IN HIGH QUALITY, INTENSIVELY MANAGED TIRF AREA.

MIXTURE INCLUDES: CERTIFIED KENTUCKY BLUEGRASS CULTIVARS 30 TO 40 PERCANT AND CERTIFIES FINE FESCUE AND 60 TO 70 PERCENT. SEEDING RATES 1 1/2 TO 3 POUNDS PER 1000 S.F. C. IDEAL TIMES OF SEEDING FOR TURF GRASS MIXTURE WESTERN MD: MARCH 15 TO JUNE 1, AUGUST 1 TO OCTOBER 1 (HARDINESS ZONES: 5B,6A)

SOUTHERN MD. EASTERN SHORE: MARCH 1 TO MAY 15, AUGUST 15 TO OCTOBER 15 (HARDINESS ZONE: 7A, 7B) TILL AREAS TO RECEIVE SEED BY DISKING OR OTHER APPROVED METHODS TO A DEPTH OF 2 TO 4 INCHES, LEVEL AND RAKE THE AREAS TO PREPARE A PROPER SEEDBED. REMOVE STONE AND DEBRIS

CENTRAL MD: MARCH 1 TO MAY 15, AUGUST 15 TO OCTOBER 15 (HARDINESS ZONE: 6B)

OVER 1.5 INCHES IN DIAMETER. THE RESULTING SEEDBED MUST BE IN SUCH CONDITION THAT FUTURE IOWING OF GRASS WILL POSE NO DIFFICULTY. E. IF SOIL MOISTURE IS DEFICIENT, SUPPLY NEW SEEDINGS WITH ADEQUATE WATER FOR PLANT GROWTH 0.5 TO 1 INCH EVERY 3 TO 4 DAYS DEPENDING ON SOIL TEXTURE) UNTIL THEY ARE FIRMLY ESTABLISHED. THIS IS ESPECIALLY TRUE WHEN SEEDINGS ARE MADE LATE IN THE PLANTING SEASON,

(B-4-8) STANDARDS AND SPECIFICATION FOR STOCKPILE AREA

IN ABNORMALLY DRY OR HOT SEASON, OR ON ADVERSE SITES.

A MOUND OR PILE OF SOIL PROTECTED BY APPROPRIATELY DESIGNED EROSION AND SEDIMENT CONTROL MEASURES TO PROVIDE A DESIGNATED LOCATION FOR THE TEMPORARY STORAGE OF SOIL THAT CONTROLS THE POTENTIAL FOR EROSION, SEDIMENTATION ,AND CHANGES TO DRAINAGE PATTERNS. CONDITIONS WHERE PRACTICE APPLIES

STOCKPILE AREAS ARE UTILIZED WHEN IT IS NECESSARY TO SALVAGE AND STORE SOIL FOR LATER USE.

1. THE STOCKPILE LOCATION AND ALL RELATED SEDIMENT CONTROL PRACTICES MUST BE CLEARLY INDICATED ON THE EROSION AND SEDIMENT CONTROL PLAN.

2. THE FOOTPRINT OF STOCKPILE MUST BE SIZED TO ACCOMMODATE THE ANTICIPATED VOLUME OF MATERIAL AND BASED ON A SIDE SLOPE RATIO NO STEEPER THAN 2:1. BENCHING MUST BE PROVIDED IN ACCORDANCE WITH

3. RUNOFF FROM THE STOCKPILE AREA MUST DRAIN TO A SUITABLE SEDIMENT CONTROL PRACTICE. 4. ACCESS THE STOCKPILE AREA FROM THE UPGRADE SIDE.

5. CLEAR WATER RUNOFF INTO THE STOCKPILE AREA MUST BE MINIMIZED BY USE OF A DIVERSION DEVISE SUCH AS AN EARTH DIKE, TEMPORARY SWALE OR DIVERSION FENCE. PROVISIONS MUST BE MADE FOR DISCHARGING CONCENTRATED FLOW IN A NON-EROSIVE MANNER.

WHERE RUNOFF CONCENTRATES ALONG THE TOE OF THE STOCKPILE FILL, AN APPROPRIATE EROSION/SEDIMEN' CONTROL PRACTICE MUST BE USED TO INTERCEPT THE DISCHARGE. 7. STOCKPILE MUST BE STABILIZED IN ACCORDANCE WITH THE 3/7 DAY STABILIZATION REQUIREMENT AS WELL AS

STANDARD B-4-I INCREMENTAL STABILIZATION AND STANDARD B-4-4 TEMPORARY STABILIZATION. 8. IF THE STOCKPILE IS LOCATED ON AN IMPERVIOUS SURFACE, A LINER SHOULD BE PROVIDED BELOW THE STOCKPILE TO FACILITATE CLEANUP. STOCKPILES CONTAINING CONTAMINATED MATERIAL MUST COVERED WITH IMPERMEABLE

MAINTENANCE
THE STOCKPILE AREA MUST CONTINUOUSLY MEET THE REQUIREMENTS FOR ADEQUATE VEGETATIVE ESTABLISHMENT II

CCORDANCE WITH SECTION B-4 VEGETATIVE STABILIZATION. SIDE SLOPES MUST BE MAINTAINED AT NO STEEPER THAN 2:1 RATIO. THE STOCKPILE AREA MUST BE KEPT FREE OF EROSION. IF THE VERTICAL HEIGHT OF A STOCKPILE EXCEEDS 20 FEET FOR 2:1 SLOPES, 30 FEET FOR 3:1 SLOPES, OR 40 FEET FOR 4:1 SLOPES, BENCHING MUST BE PROVIDED IN ACCORDANCE WITH SECTION B-3 LAND GRADING.

# SEQUENCE OF CONSTRUCTION:

1. OBTAIN GRADING PERMIT (1 DAY).

2. PERFORM CLEARING AND GRUBBING AS NECESSARY FOR THE INSTALLATION OF PERIMETER CONTROLS (5 DAYS)

CONSTRUCT STABILIZED CONSTRUCTION ENTRANCE AT LOCATION INDICATED

4. CONSTRUCT SILT FENCES (SF), SUPER SILT FENCES (SSF), AND SEDIMENT TRAPS (10 DAYS).

CLEAR AND GRUB SITE (5 DAYS).

GRADE SITE AS SHOWN ON GRADING AND SEDIMENT CONTROL PLANS (10 DAYS).

CONSTRUCT TEMPORARY DIVERSION BERM (2 DAYS).

8. CONSTRUCT TEPORARY DIVERSION PIPE TO THE SEDIMENT TRAP. #1 AND REMOVE DIVERSION BERM. 2 DAYS).

9. CONSTRUCT STORM DRAIN SYSTEM AND INSTALL INLET PROTECTION, BLOCK INLET #5, 9, 10 AND 11 (10 DAYS)

10. STABILIZE ALL DISTURBED AREAS (2 DAYS).

11. REMOVE DIVERSION PIPE (1 DAYS).

12. CONSTRUCT PUBLIC WATER AND SEWER MAINS (15 DAYS).

13. CONSTRUCT FIRST COURSE OF PAVEMENT FOR NEW PUBLIC ROAD (5 DAYS)

14. CONSTRUCT MICRO-BIORETENTION FACILITIES MB # 2, 3, AND 4 (14 DAYS).

15. SEED AND MULCH DISTURBED AREA (1 DAY)

16. WHEN ALL DISTURBED AREAS HAVE BEEN STABILISED AND WITH PERMISSION OF SEDIMENT CONTROL INSPECTOR, CONVERT SEDIMENT TRAP #1 INTO MICRO-BIORETENTION MB #1 AND REMOVE SEDIMENT TRAPS # 2 AND 3 (14 DAYS).

17. COMPLETE FINAL GRADING


18. CONSTRUCT 8' PEDESTRIAN PATHWAY (7 DAYS).

19. WITH THE APPROVAL OF SEDIMENT CONTROL INSPECTOR REMOVE SILT FENCE FROM OPEN SPACE 9 OF ROCKBURN RUN SUBDIVISION WHICH WAS INSTALLED FOR THE CONSTRUCTION OF PUBLIC SEWER MAIN (1 DAY) LEAVE IN PLACE THE REMAINING SEDIMENT CONTROL DEVICES FOR FUTURE CONSTRUCTION OF THE HOUSES (SDP STAGE).

20. CONSTRUCT MONTGOMERY ROAD IMPROVEMENT (15 DAYS). 21. CONSTRUCT TOP COURSE OF PUBLIC ROADWAYS.

## **DEVELOPER**

C/O DORSEY FAMILY HOMES, INC. 10717-B BIRMINGHAM WAY WOODSTOCK, MARYLAND 21163 (410)465-7200



TEMP	ORAR	Y SI	EEDIN	G FOR SITE ST	TABILIZATION			
PLANT SPECIES	SEEDING RATE		SEEDING DEPTH	RECOMMENDED SEEDING DATED BY PLANT HARDINESS ZONE				
	LB/AC	LB/ 1000SF	(INCHES)	5B AND 6A	6B	7A AND 7B		
COOL SEASON GRASSES								
ANNUAL RYEGRASS (LOLIUM PERENNE SSP. MULTIFLORUM)	40	1.0	0.5	MAR 15 TO MAY 31; AUG 1 TO SEP 30	MAR 1 TO MAY 15; AUG 1 TO OCT 15	FEB.15 TO APR 30 AUG 15 TO NOV 3		
BARLEY (HORDEUM VULGARE)	96	2.2	0.5	MAR 15 TO MAY 31; AUG 1 TO SEP 30	MAR 1 TO MAY 15; AUG 1 TO OCT 15	FEB.15 TO APR 30 AUG 15 TO NOV 3		
OATS (AVENA SATIVA)	72	1.7	0.5	MAR 15 TO MAY 31; AUG 1 TO SEP 30	MAR 1 TO MAY 15; AUG 1 TO OCT 15	FEB.15 TO APR 30 AUG 15 TO NOV 3		
WHEAT (TRITICUM AESTIVUM)	120	2.8	0.5	MAR 15 TO MAY 31; AUG 1 TO SEP 30	MAR 1 TO MAY 15; AUG 1 TO OCT 15	FEB.15 TO APR 30 AUG 15 TO NOV 3		
CEREAL RYE (SECALE ITALICA)	112	2.8	0.5	MAR 15 TO MAY 31; AUG 1 TO OCT 31	MAR 1 TO MAY 15; AUG 1 TO OCT 15	FEB.15 TO APR 30 AUG 15 TO DEC 15		
WARM SEASON GRASSES	-			,				
FOXTAIL MILLET (SETARIA ITALICA)	30	0.7	0.5	JUN 1 TO JUL 31	MAY 16 TO JUL 31	MAY 1 TO AUG 14		
PEARL MILLET (PENNISETUM GLAUCUM)	20	0.5	0.5	JUN 1 TO JUL 31	MAY 16 TO JUL 31	MAY 1 TO AUG 14		

	PERMANENT SEEDING SUMMARY									
	HARDINESS ZONE (FROM FIGURE B.3): 6b FERTILIZER RATE SEED MIXTURE (FROM TABLE B.3): 8 (10-20-20)									
NO.	SPECIES	APPLICATION RATE (LB/AC)	SEEDING DATES	SEEDING DEPTHS	N	P <sub>2</sub> O <sub>5</sub>	K <sub>2</sub> O	LIME RATE		
1	TALL FESCUE	100	MARCH 1-MAY 15 AUG 15-OCT 15	1/4"-1/2"	45 LBS. PER ACRE (1 LB./1000 SF)	90 LBS. PER ACRE (2 LB./1000/SF)	90 LBS. PER ACRE (2 LB./1000 SF)	2 TONS / ACRE (90 LBS / 1000 SF)		

ENTRANCE

CONSTRUCTION SPECIFICATIONS

MOUNTABLE BERM\_ (6 IN MIN.)

PROFILE

PLAN VIEW

2. PIPE ALL SURFACE WATER FLOWING TO OR DIVERTED TOWARD THE SCE UNDER THE ENTRANCE, MAINTAINING POSITIVE DRAININGE, PROTECT PIPE INSTALLED THROUGH THE SCE WITH A MOUNTAIN BERNI WITH 5:1 SLOPES AND A MINIMUM OF 12 INCHES OF STONE OVER THE PIPE. PROVIDE PIE SPECIFIED ON APPROVED PLAN, WHEN THE SCE IS LOCATED AT A HIGH SPOT AND HAS NO DR. TO CONVEY, A PIPE IS NOT NECESSARY. A MOUNTABLE BERM IS REQUIRED WHEN SCE IS NOT LOCATED AT A HIGH SPOT.

MARYLAND STANDARDS AND SPECIFICATIONS FOR SOIL EROSION AND SEDIMENT CONTROL

CROSS SECTION

MARYLAND STANDARDS AND SPECIFICATIONS FOR SOIL EROSION AND SEDMENT CONTROL

U.S. DEPARTMENT OF AGRICULTURE 2011 MARYLAND DEPARTMENT OF ENVIRONME WATER MANAGEMENT ADMINISTRATION

DETAIL E-1 SILT FENCE

|-----SF-----

38 IN MIN. FENCE POST LENGTH DRIVEN MIN. 16 IN INTO GROUND

Le in Min. DEPTH INTO GROUND

16 IN MIN. HEIGHT OF WOVEN SLIT FILM GEOTEXTILE

DETAIL F-1 SILT FENCE

WOVEN SLIT FILM---

(B-4-4) STANDARDS AND SPECIFICATIONS FOR TEMPORARY STABILIZATION

MIXTURES 1, 4-7, 9, AND 10 FROM TABLE B.3 OF THE 2011 MARYLAND STANDARD AND SPECIFICATIONS FOR SOIL EROSION AND SEDIMENT CONTROL MAY BE USED.

TO STABILIZE DISTURBED SOIL WITH VEGETATION FOR UP TO 6 MONTHS.

TO USE FAST GROWING VEGETATION THAT PROVIDES COVER ON DISTURB SOIL.


CONDITIONS WHERE PRACTICE APPLIES
EXPOSED SOILS WHERE GROUND COVER IS NEEDED FOR A PERIOD OF 6 MONTHS OR LESS. FOR ONGER DURATION OF TIME, PERMANENT STABILIZATION PRACTICES ARE REQUIRED. 1. SELECT ONE OR MORE OF THE SPECIES OR SEED MIXTURES LISTED IN TABLE B.1 FOR THE

APPROPRIATE PLANT HARDINESS ZONE (FROM FIGURE B.3), AND ENTER THEM IN THE TEMPORARY SEEDING SUMMARY ALONG WITH APPLICATION RATES, SEEDING DATES AND SEEDING DEPTHS. IF THIS SUMMARY IS NOT PUT ON THE PLAN AND COMPLETED, THEN TABLE B-1 PLUS FORTELIZER AND LIME RATES MUST BE PUT ON THE PLAN.

FOR SITES HAVING SOIL TESTS PERFORMED, USE AND SHOW THE RECOMMENDED RATES BY THE TESTING AGENCY. SOIL TESTS ARE NOT REQUIRED FOR TEMPORARY SEEDING.

MULCH OR STRAW MULCH ALONE AS PRESCRIBED IN SECTION B-4-3.A.1b, AND

WHEN STABILIZATION IS REQUIRED OUTSIDE OF A SEEDING SEASON, APPLY SEED AND MAINTAIN UNTIL THE NEXT SEEDING SEASON DETAIL B-1 STABILIZED CONSTRUCTION



**DETAIL C-9 DIVERSION FENCE** 


----- OF ------

NAXIMUM DRAINAGE AREA = 2 ACRES

EXTEND SHEETING A MINIMUM OF 4 FEET ALONG FLOW SURFACE AND EMBED END A MINIMUM OF 8 INCHES INTO GROUND. SOIL STABILIZATION MATTING MAY BE USED IN LIEU OF IMPERIMEABLE SHEETING ALONG FLOW SURFACE.


WHEN TWO SECTIONS OF SHEETING ADJOIN EACH OTHER, OVERLAP BY 6 INCHES AND FOLD WITH SEAM

MARYLAND STANDARDS AND SPECIFICATIONS FOR SOIL EROSION AND SEDIMENT CONTROL DEPARTMENT OF AGRICULTURE 2011 MARYLAND DEPARTMENT OF ENVIRONMENT PLACE STABILIZED CONSTRUCTION ENTRANCE IN ACCORDANCE WITH THE APPROVED PLAN. VEHICLES FOR SINGLE RESIDENCE LOT), USE MINIMAIN WIDTH OF 10 FEET. FLARE SCE 10 FEET MINIMAIN AT THE EDISTING ROAD TO PROVIDE A TURNING RADIUS. DETAIL D-3-1 RIPRAP INFLOW PROTECTION PREPARE SUBGRADE AND PLACE NONWOVEN GEOTEXTILE, AS SPECIFIED IN SECTION H-1 MATERIA



PROVIDE NONWOVEN GEOTEXTILE, AS SPECIFIED IN SECTION H-1 MATERIALS, UNDER THE BOTTOM AN ALONG SIDES OF ALL RIPRAP. CONSTRUCT INFLOW CHANNEL WITH CLASS I RIPRAP OR EQUIVALENT RECYCLED CONCRETE LINING TO MINIMUM DEPTH OF 19 INCHES (2  $\times$   $D_{80}$ ) AND A 1 FOOT DEEP FLOW CHANNEL INFLOW RIPRAP PROTECTION CHANNEL MUST HAVE A TRAPEZCIDAL CROSS SECTION WITH 2:1 OR FLATTER SIDE SLOPES AND A 4 FOOT MINIMUM BOTTOM WIDTH. INSTALL ENTRANCE AND EXIT SECTIONS AS SHOWN ON THE PROFILE BLEND RIPRAP INTO EXISTING GROUND MAINTAIN LINE, GRADE, AND CROSS SECTION. REMOVE ACCUMULATED SEDIMENT AND DEBRIS. KEEP POINTS OF INFLOW AND OUTFLOW FREE OF EROSION.

S. DEPARTMENT OF AGRICULTURE 2011 MARYLAND DEPARTMENT OF EM.
RESOURCES CONSERVATION SERVICE 2011 WATER MANAGEMENT ADMINIS **DETAIL E-3** SUPER SILT FENCE



REMOVE ACCUMULATED SEDIMENT AND DEBRIS WHEN BULGES DEVELOP IN FENCE OR WHEN SEDIMENT REACHES 28% OF FENCE HIGHT. REPLACE GEOTEXTILE IF TORN, IF UNDERMINING OCCURS, REINSTALL CHAIN LINK FENCING AND GEOTEXTILE.

MARYLAND STANDARDS AND SPECIFICATIONS FOR SOIL EROSION AND SEDIMENT CONTROL

. USE WOOD POSTS 1% X 1% ± 1/6 INCH (MINIMUM) SQUARE CUT OF SOUND QUALITY HARDWOOD. AS AN ALTERNATIVE TO WOODEN POST USE STANDARD "T" OR "U" SECTION STEEL POSTS WEIGHING NOT LESS THAN 1 POUND PER LINEAR FOOT. I. USE WOVEN SLIT FILM GEOTEXTILE AS SPECIFIED IN SECTION H-1 MATERIALS AND FASTEN GEOTEXTI SECURELY TO UPSLOPE SIDE OF FENCE POSTS WITH WIRE TIES OR STAPLES AT TOP AND MID-SECTION. PROVIDE MANUFACTURER CERTIFICATION TO THE AUTHORIZED REPRESENTATIVE OF THE INSPECTION/EINFORCEMENT AUTHORITY SHOWING THAT THE GEOTEXTILE USED MEETS THE REQUIREMENTS IN SECTION H-1 MATERIALS.

|----SF-----|

EMBED GEOTEXTILE A MINIMUM OF 8 INCHES VERTICALLY INTO THE GROUND, BACKFILL AND COMPACT THE SOIL ON BOTH SIDES OF FABRIC. WHERE TWO SECTIONS OF GEOTEXTILE ADJOIN: OVERLAP, TWIST, AND STAPLE TO POST IN ACCORDANCE WITH THIS DETAIL.


EXTEND BOTH ENDS OF THE SILT FENCE A MINIMUM OF FIVE HORIZONTAL FEET UPSLOPE AT 45 DEGREES TO THE MAIN FENCE ALIGNMENT TO PREVENT RUNOFF FROM GOING AROUND THE ENDS OF THE SILT FENCE. REMOVE ACCUMULATED SEDMENT AND DEBRIS WHEN BULGES DEVELOP IN SILT FENCE OR WHEN SEDMENT REACHES 25% OF FENCE HEIGHT. REPLACE GEOTEXTILE IF TORN. IF UNDERMINING OCCURS, REINSTALL FENCE. MARYLAND STANDARDS AND SPECIFICATIONS FOR SOIL EROSION AND SEDIMENT CONTROL

INSTALL 2% INCH DIAMETER GALVANIZED STEEL POSTS OF 0.095 INCH WALL THICKNESS AND SIX FOOT LENGTH SPACED NO FURTHER THAN 10 FEET APART. DRIVE THE POSTS A MINIMUM OF 36 INCHES INTO THE GROUND. Fasten 9 gauge or heavier galvanized chain link fence (2% inch maximum opening) 42 inches in height securely to the fence posts with wire ties or hug rings. WHERE ENDS OF THE GEOTEXTILE COME TOGETHER, THE ENDS SHALL BE OVERLAPPED BY 6 INCHES, FOLDED, AND STAPLED TO PREVENT SEDIMENT BY PASS. EXTEND BOTH ENDS OF THE SUPER SILT FENCE A MINIMUM OF FIVE HORIZONTAL FEET UPSLOPE AT 45 DEGREES TO THE MAIN FENCE ALIGNMENT TO PREVENT RUNOFF FROM GOING AROUND THE ENDS OF THE SIDES BUT FENCE. Provide Manufacturer certification to the inspection/enforcement authority showing that Geotextile used meets the requirements in section H-1 materials.

20 M AI S~ U U

LDEN

6 of 12




7 OF 12


PROFILES

DRAIN


STORM



8 of 12



MICRO-BIORETENTION (M-6 DETAIL NOT TO SCALE



### MICRO-BIORETENTION SCHEDULE

(M-6) DETAIL
SCALE : NTS

FACILITY	TOP EL.	TOP OF BERM	INV. IN	INV. OUT	AREA AT TOP EL.
MB #1	334.00 🗸	′ 335.00√	330.90	330.70√	1,530 SF
MB #2	344.00 V	345.00 🗸	340.90√	340.70	1,620 SF
MB #3	326.8	327.8	323.7	323.5	1,430 SF
MB #4	344.8	345.B	34).7	341.5 s	1,035 SF

The state of the s


11.08-16

# <u>DEVELOPER</u>


C/O DORSEY FAMILY HOMES, INC. 10717-B BIRMINGHAM WAY WOODSTOCK, MARYLAND 21163 (410)465-7200

CHIEF, DEVELOPMENT ENGINEERING DIVISION

CHIEF, DIVISION OF LAND DEVELOPMENT



I HEREBY CERTIFY THAT THESE DOCUMENTS WERE PREPARED OR APPROVED BY ME AND THAT I AM A DULY LICENSED PROFESSIONAL ENGINEER UNDER THE LAWS OF THE STATE OF MARYLAND, LICENSE NO//17942\_EXP DATE 09/03/16



OPERATION AND MAINTENANCE SCHEDULE

FOR MICRO-BIORETENTION (M-6)

ANNUAL MAINTENANCE OF PLANT MATERIAL, MULCH LAYER AND

SOIL LAYER IS REQUIRED. MAINTENANCE OF MULCH AND SOIL IS

LIMITED TO CORRECTING AREAS OF EROSION OR WASH OUT. ANY

AND PRUNING. ACCEPTABLE REPLACEMENT PLANT MATERIAL IS LIMITED TO THE FOLLOWING: 2000 MARYLAND STORMWATER DESIGN

MULCH REPLACEMENT SHALL BE DONE IN THE SPRING. PLANT

INFESTATION AND MAINTENANCE WILL ADDRESS DEAD MATERIAL

SCHEDULE OF PLANT INSPECTION WILL BE TWICE A YEAR IN

AND REPLACEMENT OF ALL DEFICIENT STAKES AND WIRES.

DEAD AND DISEASED VEGETATION CONSIDERED BEYOND

SPRING AND FALL. THIS INSPECTION WILL INCLUDE REMOVAL OF

TREATMENT, TREATMENT OF ALL DISEASED TREES AND SHRUBS

MULCH SHALL BE INSPECTED EACH SPRING. REMOVE PREVIOUS


MULCH LAYER BEFORE APPLYING NEW LAYER ONCE EVERY 2 TO 3

SOIL EROSION TO BE ADDRESSED ON AN AS NEEDED BASIS, WITH

A MINIMUM OF ONCE PER MONTH AND AFTER HEAVY STORM


MATERIAL SHALL BE CHECKED FOR DISEASE AND INSECT


MANUAL VOLUME II, TABLE A.4.1 AND 2.



and meets with the approved

plans and specifications.





MODIFIED DRYWELL (M-5) DETAIL X

NOTE: ADJUST COVER OVER CHAMBER TO ENSURE THAT THE CLEAN WASHED SAND LAYER IS NOT PLACED IN FILL.

NOTE: TYPE AND NUMBER OF DRYWELLS TO BE DETERMINE AT SITE DEVELOPMENT PLAN


1 STANDARD DRYWELL CAN BE REPLACED WITH MOD. DRYWELLS (SC-740 STORMTECH CHAMBERS)


### DRYWELL REPLACEMENT SCHEDULE

LOT #	SIZE OF STANDARD DRYWELL	NO. OF DRYWELLS	VOLUME IN STANDARD DRYWELLS	NO. OF SC-740	VOLUME IN STANDARD SC-740
3	11.5'x7.5'x5.0'	V 2	345.0 C.F.	V 5	374.5 C.F.
4–11	10.5'x7.0'x5.0'	/ 2	294.0 C.F.	V 4	299.6 C.F.
12	13.0'x8.5'x5.0'	V 2	442.0 C.F.	V 6	449.4 C.F.
13–18	10.5'x7.0'x5.0'	V 2	294.0 C.F.	V 4	299.6 C.F.
19	12.0'x7.0'x5.0'	V 2	336.0 C.F.	V 5	374.5 C.F.


### OPERATION AND MAINTENANCE SCHEDULE FOR PRIVATELY OWNED AND MAINTAINED DRY WELLS (M-5)

- A. THE OWNER SHALL INSPECT THE MONITORING WELLS AND STRUCTURES ON A QUARTERLY BASIS AND AFTER EVERY HEAVY STORM EVENT.
- B. THE OWNER SHALL RECORD THE WATER LEVELS AND SEDIMENT BUILD UP IN THE MONITORING WELLS OVER A PERIOD OF SEVERAL DAYS TO INSURE TRENCH DRAINAGE.
- C. THE OWNER SHALL MAINTAIN A LOG BOOK TO DETERMINE THE RATE AT WHICH THE FACILITY DRAINS.
- D. WHEN THE FACILITY BECOMES CLOGGED SO THAT IT DOES NOT DRAIN DOWN WITHIN A SEVENTY-TWO (72) HOUR TIME PERIOD, CORRECTIVE ACTION SHALL BE TAKEN.
- E. THE MAINTENANCE LOG BOOK SHALL BE AVAILABLE TO HOWARD COUNTY FOR INSPECTION TO INSURE COMPLIANCE WITH OPERATION AND MAINTENANCE CRITERIA
- F. ONCE THE PERFORMANCE CHARACTERISTICS OF THE INFILTRATION FACILITY HAVE BEEN VERIFIED, THE MONITORING SCHEDULE CAN BE REDUCED TO AN ANNUAL BASIS UNLESS THE PERFORMANCE DATA INDICATES THAT A MORE FREQUENT SCHEDULE IS REQUIRED.





GE&T appreciates the opportunity to provide this geotechnical engineering service to you. Should you have any questions regarding this letter report, or require additional services, please feel free to contact our office.




 $10 \, \text{OF} \, 12$ 

,8 -20 M/

SOIL DETAILS 21

ASSOC.




11 of 12

ONSERVATION

SOC.

45



TS

Ċί

ASSOC.

12 of 12

F-16-024