GENERAL NOTES

- 1. ALL WORK SHALL BE PERFORMED IN ACCORDANCE WITH THE HOWARD COUNTY DESIGN MANUAL VOLUME IV - STANDARD SPECIFICATIONS AND DETAILS.
- 2. ELEVATIONS SHOWN ARE BASED ON THE JOHNS HOPKINS UNIVERSITY APPLIED PHYSICS LABORATORY DATUM. JHU-APL DATUM-.94' = HOWARD COUNTY DATUM. TOPOGRAPHIC SURVEY WAS DONE IN NOVEMBER
- 3. THE CONTRACTOR SHALL NOTIFY MISS UTILITY (301) 559-0100 FIVE DAYS PRIOR TO START OF CONSTRUCTION.
- 4. POLYFILTER X FILTER CLOTH BLANKET OR EQUAL SHALL BE PLACED UNDER ALL STONE RIP RAP.
- 5. APPROXIMATE LOCATION OF EXISTING UTILITIES ARE SHOWN. THE CONTRACTOR SHALL TAKE ALL NECESSARY PRECAUTIONS TO PROTECT THE EXISTING UTILITIES AND TO MAINTAIN AN UNINTERRUPTED
- ANY DAMAGE BY THE CONTRACTOR'S OPERATIONS SHALL BE REPAIRED IMMEDIATELY AT THE CONTRACTOR'S EXPENSE.
- 6. ACCESS TO THE CONSTRUCTION AREA THROUGH THE SECURE AREA OF THE APPLIED PHYSICS LABORATORY (WITHIN THE FENCED ENCLOSURE) MUST BE ARRANGED IN ADVANCE BY CONTACTING THE PLANT ENGINEERING OFFICE (301) 792-5134.
- 7. SECURITY MUST BE MAINTAINED WITHIN THE EXISTING FENCED AREA. ALL REQUIRED FENCE CONSTRUCTION AND RELOCATION SHALL BE BY THE JOHNS HOPKINS UNIVERSITY APPLIED PHYSICS LABORATORY... HOWEVER THE CONTRACTOR SHALL BE RESPONSIBLE TO COORDINATE
- WITH JHU APL AS TO WHEN SUCH WORK IS REQUIRED. 8. THE CONTRACTOR SHALL CONTACT MR. ARTHUR STUCKI, PLANT ENGINEER (301) 792-5133 AT LEAST FIVE DAYS BEFORE STARTING WORK OR SHUTTING DOWN ANY UTILITIES.
- 9. THE CONTRACTOR SHALL SHUTDOWN AND TIE-IN TO THE EXISTING UTILITIES ONLY AFTER NORMAL WORKING HOURS AT JHU-APL. WORK MUST BE SCHEDULED ACCORDINGLY. NORMAL WOEKING HOURS ARE 8:30 AM TO 5:00 PM.
- 10. ALL PIPE ELEVATIONS SHOWN ARE INVERT ELEVATIONS.
- 11. ALL WATER MAINS SHALL BE DUCTILE IRON CLASS 52.
- 12. ALL SANITARY SEWER MAINS SHALL BE HOWARD COUNTY SCHEDULE 35 PVC UNLESS OTHERWISE NOTED. 13. THE CONTRACTOR OR DEVELOPER SHALL CONTACT THE CONSTRUCTION
- INSPECTION DIVISION, 24 HOURS IN ADVANCE OF COMMENCEMENT OF WORK, AT 992-2417 OR 2418. 14. TOP OF ALL WATER MAINS SHALL HAVE A MINIMUM OF 3 1/2 FT. OF
- COVER UNLESS OTHERWISE NOTED.
- 15. ALL FITTINGS SHALL BE BUTTRESSED OR ANCHORED WITH CONCRETE IN ACCORDANCE WITH THE STANDARD DETAILS UNLESS OTHERWISE PROVIDED FOR ON THE DRAWING.
- 16. CLEAR ALL UTILITIES BY A MINIMUM OF 6". CLEAR ALL POLES 2'-0" MINIMUM OR TUNNEL AS REQUIRED. 17. THE CONTRACTOR SHALL NOT OPERATE ANY WATER MAIN VALVES ON THE
- EXISTING WATER SYSTEMS.
- 18. THE CONTRACTOR SHALL PROVIDE A JOINT IN ALL SEWER MAINS WITHIN 2'-0" OF EXTERIOR MANHOLE WALL.
- 19. THE CONTRACTOR SHALL PERMANENTLY SEED AND STABILIZE ALL DISTURBED AREAS THAT ARE NOT TO BE PAVED.
- 20. THE BUILDINGS PROPOSED ARE FOR RESEARCH AND DEVELOPMENT. 21. THERE ARE NO WETLANDS WITHIN THE LIMIT OF DISTURBANCE SHOWN. THEREFORE SECTION 404 AND SECTION 401 DO NOT APPLY AND PERMITS ARE NOT REQUIRED.
- 22. ALL ON-SITE WATER AND SEWER SYSTEMS ARE PRIVATE.

SITE ANALYSIS

PRESENT ZONING - - - - - - - RURAL -R" AREA OF PROPERTY - - - - - - - 366 ACRES. AREA OF SUBMISSION ---- -- - GO ACRES.

	ACKES
BUILDING FLOOR SPACE:	
EXISTING	1,419,078 S.F.
PROPOSED	7,190
	1,426,268 S.F.
NUMBER OF EMPLOYEES	
EXISTING	3,100
	0 .
NUMBER OF PARKING COLORS	3,100
NUMBER: OF PARKING SPACES	
EXISTING	3,180
REQUIRED 3,100 X 0.7	2,170
PROVIDED	3,180
GREEN AREA	3,100
EXISTING	304.5 AC. 83.2%
PROPOSED	304.2 AC.
BUILDING COVERAGE	504.2 AC.
EXISTING	12.004
	13.99 Ac. 3.82 %
PROP03ED	14.154 Ac. 3.86%
PAVING AREA .	,
EXISTING	46.8 AC. 12.8%
PROPOSED	46.97AC. 12.83%
-	1015/AU. 12.036

NOTE: THERE IS NO ADDITIONAL PARKING PROPOSED BY THIS

Consulting Engineers • Land Planners • Surveyors 3220 Bethany Lane, Suite 4, Ellicott City, Maryland 301-465-0400




APPLIED PHYSICS LABORATORY THE JOHN HOPKINS UNIVERSITY


APPROVED FOR THE UNIVERSITY BY:


THE JOHNS HOPKINS UNIVERSITY APPLIED PHYSICS LABORATORY

1. General: All water main construction shall conform to the requirements contained in the current issue of the "Howard County Design Manual, Volume IV, Standard Specifications and Details for Construction", Article 10 except as modified herein. 2. Modifications a. Valves Valves shall open left - counterclockwise. Where indicated on the plans they shall be furnished with post type operators. All outlet nozzles shall have National Standard Fire UNIVERSITY Hose Coupling Screw Threads. LAPPLIED PHYSICS c. Pipe Joint Bonding 1) All pipe joints shall be bonded to insure electrical continuity. Bonding may be accomplished either with shop welded copper terminal straps and copper jumper straps with corrosion resistant bolts or with copper wire exothermic welded in the field. 2) All bonding between joints for pipe, fittings, valves, and specials shall be tested for electrical continuity. Each joint shall be inspected and resistance tested prior to coating and backfilling. No registance will be permissible across any joint, 3) All bonded joints shall be coated with a rustinhibitive paint. ADDRESS CHART PROPOSED PARCEL NUMBER STREET ADDRESS P. 123/129 11100 JOHNS HOPKINS ROAD PROPERTY LINE SUBDIVISION NAME SECT./AREA | LOT/PARCEL HOPKINS ROAD LTD. PARTHERSHIP J.H.U. APPLIED PHYSICS LAB. P.123/289 TAX/ZONE MAP ELEC DIST CENSUS T P-124 AND P-125 ZONED: FEC. WATER CODE SEWER CODE 6480000 E-71 APPROVED; FOR PUBLIC WATER AND PUBLIC SEWERACE SYSTEMS HOWARD COUNTY HEALTH DEPARTMENT JOSEPH GREGOR LASZLO HOWARD COUNTY DEPARTMENT OF PLANNING & ZONING CHIEF, DIVISION OF COMMUNITY PLANNING & LAND DEVELOPMENT MILDRED B. PRICE ET AL 145/235 146/76 P-128 ZONED: RUFAL WEST VIRGINIA PULP AND PAPER COMPANY P-300 ZONED: RURAL APPROVED: FOR PUBLIC WATER AND PUBLIC SEWERAGE. STORM DRAINAGE SYSTEMS AND PUBLIC ROADS LOCATION PLAN Scale |"= 400" 2-26-90 County Comments SCALE : AS SHOWN SHEET GROUNDSKEEPING FACILITY COVER SHEET 11100 JOHNS HOPKINS ROAD DATE: 1-2-90 LAUREL. MARYLAND 20707 REVISIONS

Water Main Notes








DRAINAGE AREA TABULATIONS

INLET NO.	AREA (ACRES)	С	% IMPERVIOUS
OFFSITE	6.08	.60	54
EX. INLET	.41	.55	47
I-10	1.36	.69	65
EX. I - 8	.41	.60	54
	OFFSITE EX. INLET I - 10	OFFSITE 6.08 EX. INLET .41 I-10 1.36	EX. INLET .41 .55 I - 10 1.36 .69



DRAINAGE AREA MAP

Scale: 1"-50"

GROUNDSKEEPING FACILITY

DRAINAGE AREA

MAP

EXISTING UTILITY PLAN

AND

MEDICAL TO 10-90

ALLEY

AND

COM

Part - 2 control

Com

ALLEY

AS SHOWN

GREYISIONS

DATE: 90

GREYISIONS

1-2-90

GREYISIONS

DATE: 90


GREYISIONS

1-2-90

GREYISIONS


1-

SPP-90-119




STABILIZED CONSTRUCTION ENTRANCE not to scale

STANDARD SYMBOL



CONSTRUCTION SPECIFICATIONS

- 1. Stone Size Use 2" stone, or reclaimed or recycled concrete equivalent. 2. Length - As required, but not less than 50 feet (except on a single residence lot where a 30 foot minimum length would apply).
- 3. Thickness Not less than six (6) inches. 4. Width - Ten (10) foot minimum, but not less than the full width at
- points where ingress or egress occurs.
- 5. Filter Cloth Will be placed over the entire area prior to placing of sto Filter will not be required on a single family residence lot.
- 6. Surface Water All surface water flowing or diverted toward construction entrances shall be piped across the entrance. If piping is impractical,
- a mountable berm with 5:1 slopes will be permitted. 7. Maintenance - The entrance shall be maintained in a condition which will prevent tracking or flowing of sediment onto public rights-of-way. This may require periodic top dressing with additional stone as conditions demand and repair and/or cleanout of any measures used to trap sediment. All sediment spilled, dropped, washed or tracked onto public rights-of- way mus
- be removed immediately. 8. Washing - Wheels shall be cleaned to remove sediment prior to entrance onto public rights-of-way. When washing is required, it shall be done on an are stabilized with stone and which drains into an approved sediment trapping
- 9. Periodic inspection and needed maintenance shall be provided after each rain



CONSTRUCTION NOTES FOR FABRICATED SILT FENCE

- Woven wire fence to be fastened securely TO FENCE POSTS WITH WIRE TIES OR STAPLES
- 2. FILTER CLOTH TO BE FASTENED SECURELY TO WOVEN WIRE FENCE WITH TIES SPACED EVERY 24" AT TOP AND MID SECTION.
- 3. WHEN TWO SECTIONS OF FILTER CLOTH ADJOIN EACH OTHER THEY SHALL BE OVER-LAPPED BY SIX INCHES AND FOLDED,
- 4. MAINTENANCE SHALL BE PERFORMED AS NEEDED AND MATERIAL REMOVED WHEN BULGES DEVELOP IN THE SILT FENCE
- PREFABRICATED UNIT: GEOFAB, ENVIROFENCE, OR APPROVED

PERMANENT SEEDING NOTES

The second secon

Apply to graded or cleared areas not subject to immediate further disturbance where a permanent long-lived vegetative cover immedial.

Seedbed Preparation: Losen upper three inches of soil by making, discing or other acceptable means before seeding. It not present lessend.

- Soil Amendments: In lieu of soil test recommendations, use one of the following schedules 1) Preferred - Apply 2 tens per acre dolomists limestone (92 lbs/1000 square ft) and 600 lbs per acre 10-10-10 fertilizer (14 lbs/2000 sq ft) before seeding. Harrow or disc into upper three inches of soil. At time of seeding, apply 400 lbs per acre 30-0-0 ureaform fertilizer (9 lbs/1000 sq St).
- 2) Acceptable Apply 2 tons per acre dolomitic limestone (92 lbs/1000 sq ft) and 1000 lbs per acre 10-10-10 fertilizer (23 lbs/1000 sq ft) before seeding. Harrow or disc into upper three inches of soil.

Seeding - For the periods March 1 thru April 30, and August 1 thru October 15, seed with 60 lbs per acre (1.4 lbs/1000 sq ft) of Kentucky 31 Tall Fescue. For the period May 1 thre July 31, seed with 60 lbs Kentucky 31 Tall Pasque per acre and 2 lbs per acre (.05 lbs/1000 sq ft) of weeping lovegrass. During the period of October 16 thru February 28, protect site by: Option (1) 2 tons per acre of well anchored straw mulch and seed as soon as possible in the spring. Option (2) Use sod. Option (3) Seed with 60 lbs/ acre Kentucky 31 Tall Fescue and mulch with 2 tons/acre well anchored straw.

Mulching - Apply 11 to 2 tons per acre (70 to 90 lbs/1000 sq ft) of unrotted small grain straw immediately after seeding. Anchor mulch immediately after application using mulch anchoring tool or 218 gallons per acre (5 gal/1000 sq ft) of emulsified asphalt on flat areas. On slopes 8 feet or higher, use 348 gallons per acre (8 gal/1000 sq ft) for anchoring.

Matinenance - Inspect all seeded areas and make needed repairs, replacements and

TEMPORARY SEEDING NOTES

Apply to graded or cleared areas likely to be redisturbed where a short-term vegetative cover is needed.

Seedbed Preparation: Loosen upper three inches of soil by raking, discing or other acceptable means before seeding. Is not previous loosened.


Soil Amendments: Apply 600 lbs per acre 10-10-10 fertilizer (14 lbs/1000 sq ft)

Seeding: For periods March 1 thru April 30 and from August 15 thru November 15, seed with 22 bushel per acre of annual rye (3.2 lbs/1000 sq ft). For the period May 1 thru August 14, seed with 3 lbs per acre of weeping lovegrass (.07 lbs/1000 sq ft). For ther period November 16 thru February 28, protect sice by applying 2 tons per acre of well anchored straw mulch and seed as soon as possible in the spring, or use sod.

Mulching: Apply 1 to 2 tons per acre 670 to 90 lbs/1000 sq ft) of unrotted small grain straw immediately after seeding. Anchor mulch immediately after application using mulch anchoring tool or 218 gal per acre (5 gal/1000 sq ft) of emulsified asphalt on flat areas. On slopes, 8 ft or higher, use 348 gal per acre (8 gal/1000 sq ft) for anchoring.

Refer to the 1983 MARYLAND STANDARDS AND SPECIFICATIONS FOR SOIL EROSION AND SEDIMENT CONTROL for rate and methods not covered.

STONE OUTLET SEDIMENT TRAP Y



OPTION: A one foot layer of 2" stone may be placed on the upstream side of the riprap in

- CONSTRUCTION SPECIFICATIONS FOR ST-V
- Area under embankment shall be cleared, grubbed and stripped of any vegetation and root
- 2. The fill material for the embankment shall be free of roots and other woody wegetation as well as over-sized stones, rocks, organic material or other objectionable material. The embankment shall be compacted by traversing with equipment while it is being constructed.
- 3. All cut and fill slopes shall be 2:1 or flatter.
- 4. The stone used in the outlet shall be small riprap 4"-8" along with a 1' thickness of 2" aggregate placed on the up-grade side on the small riprap oR embedded filter cloth in the
- 5. Sediment shall be removed and trap restored to its original dimensions when the sediment has accumulated to 4 the design depth of the trap.
- 6. The structure shall be inspected after each rain and repairs made as needed.
- 7. Construction operations shall be carried out in such a manner than erosion and water
- 8. The structure shall be removed and the ates stabilized when the drainage area has been properly stabilized.

I certify that this plan erosion and sediment control represents a practical and workable plan based on my personal knowledge of the site conditions. This plan was prepared in accordance with the requirements of the Howard Soil Conservation District.

The second section of the second section of the second section is a second section of the second section of the second section is a second section of the second section secti

ENGINEER'S CERTIFICATE

Medeld Signature of Engineer

11100 JOHNS HOPKINS ROAD

I/We certify that all development and/ or construction will be done according to these plans, and that any responsible personnel involved in the construction project will have a Certificate of Attendance at a Department of Natural Resources Approved Training Program for Control of Sediment and Erosion before beginning the project. I also authorize periodic on-site inspection by the · Howard Soil Conservation District.

DEVELOPER'S CERTIFICATE

Signature of Developer

SELEMENT CONTROL NOTES

SEDIMENT CONTROL.

lishment of grasses.

Total Area of Sice

· Area to be roofed or paved

Offsite waste/borrow area location

repaired on the same day of disturbance.

8) Any sediment control practice which is disturbed by

9) Additional sediment controls must be provided, if

grading activity for placement of ugilities must be

Area Disturbed

Drainage.

7) Sice Apalyais:

.; 1) A minimum of 24 hours motice must be given to

the Moward County Office of Inspection and Permits prior to the start of any construction. (992-2437)

installed according to the provisions of this plan

STANDARDS AND SPECIFICATIONS FOR SOIL ERGSION AND

3) Following initial soil discurbance or redisturbance,

and are to be in conformance with the 1920 MARYLAND

permanent or temporary stabilitation shall be completed

4) All sediment traps/basins shown must be fenced and warning signs

posted around their perimeter in accordance with Vol. 1,

within: a) 7 calendar days for all perimeter sediment

control structures, dikes, perimeter slopes and all

slopes greater than 3:1, b) 14 days as to all other

Chapter 12, of the HOWARD COUNTY DESIGN MANUAL, STOTIE

disturbed or graded areas on the project site.

5) All disturbed areas must be stabilized within the

time period specified above in accordance with the

1983 MARYLAND STANDARDS AND SPECIFICATIONS FOR SOIL

EROSION AND SEDIMENT CONTROL for permanent seedings

mulching (Sec. 52.) Temporary stabilization with mulch alone can only be done when recommended seeding

dates do not allow for proper germination and estab-

6) All sediment control structures are to remain in place

and are to be maintained in operative condition until

Area to be vegetatively stabilized 12 Acres
Total Cut
Total Fill
150, Cu. yds
Offstra meta/harra

_,60 Acres

deemed nacessary by the Howard County DPW sediment control inspector.

installation of perimeter erosion and sediment entrols, but before

building or grading inspection approvals may not be authorized until

10) On all sites with disturbed areas in excess of 2 acres, approval

of the inspection agency shall be requested upon completion of

proceeding with any other earth disturbance or grading. Other

this initial approval by the inspection agency is made.

permission for their removal has been obtained from

the Howard County Sediment Control Inspector

(Sec. 51) sod (Sec. 54), temporary seeding (Sec. 50) and

2) All vegetative and structural productes at to be

THE JOHNS HOPKINS UNIVERSITY APPLIED PHYSICS LABORATORY

LAUREL MARYLAND 20707


GENERAL NOTES

- 1) Refer to "1983 Maryland Standards and Specifications for Soil Exosion and Sediment Control for standard details and detailed specifications of each practice specified herein.
- 2) With the approval of the sediment control inspector, minor field adjustments can and will be made to insure the control of any sediment. Changes in sediment control practices require prior approval of the sediment control inspector and the County Soil Conservation District.
- 3) At the end of each working day, all sediment control practices will be inspected and left in operational condition.
- 4) Following initial soil disturbance or redisturbance, permanent or temporary stabilization shall be completed within: a.) seven calendar days as to the surface of all perimeter controls, dikes, males, ditches, perimeter slopes, and all slopes greater than 3 horizontal to 1 vertical (3:1) and b.) fourteen days as to all other disturbed or graded areas on the project site.
- Any change to the grading proposed on this plan requires re-submission County Soil Conservation District for approval.
- 6) Pust control will be provided for all disturbed areas. Refer to 1983 Heryland Standards and Specifications for Soil Erosion and Sediment Control, pp 6801 and 62.02 for acceptable methods and specifications for dust control.
- 1) Any variation from the sequence of operations stated on this plan requires the approval of the sediment control inspector and the County Soil Conservation District prior to the initiation of the change.
- 8) Excess cut or borrow material shall go to or come from, respectively. a site with an approved sediment control plan.

The following item may be used as applicable:

9) Refer to "Maryland's Guidelines to Waterway Construction" by the Water Resources Administration (WRA), dated January, 1986 for standard details and detailed specifications of each practice specified herein for waterway construction.

EARTH DIKE



ALL DINES SIGLE HAVE INCLUDE DESIGNATE TO AN OUTER.

TOP WIDTH MAY BE WIDER AND SIDE SLOPES MAY BE FLATTER IF DESIRED TO FACIL CROSSING BY CONSTRUCTION TRAFFIC.

FIELD LOCATION SHOULD BE ADJUSTED AS NEEDED TO UTILIZE A STABILIZED SAFE DOTALL BE CONVEYED TO A SEDIMENT TRAPPING DEVICE SUCH AS A SEDIMENT TRAP OF SEDIMENT WHERE EITHER THE DIKE CHANNEL OR THE DRAINAGE AREA ABOVE THE DIKE ARE NOTED TO A SEDIMENT TRAPPING DEVICE SUCH AS A SEDIMENT DEVICE

ADEQUATELY STABILIZED.

STABILIZATION SHALL BE: (A) IN ACCORDANCE WITH STANDARD SPECIFICATIONS FOR AND STRAW MULCH OR STRAW MULCH IF NOT IN SEEDING SEASON, (B) FLOW CHANNE AS THE CHART BELOW.

ELON CHARRIES CTARTS TO

		FLUM CHANNEL STABILIZATION	
TYPE OF IREALMENT	CHANNEL GRADE	DIKE A	DIKI ±
1	.5-3.0%	SEED AND STRAW MULCH	SEED AND STRAW
. 2	3.1-5.0%	SEED AND STRAW MULCH	SEED USING JUT EXCELSION: SUB
3	5.1-8.0%	SEED WITH JUTE, OR SOD;	LINED RIP-RAF
4	8.1-20%	I INET RID-RAD U-9"	F

LINED KIP-KAP 4-8 ENGINEERING DES. A. Stone to be 2 inch stone, or recycled concrete equivalent, in a layer at 157 inches in thickness and be pressed into the soil with construction equipments. RIP-RAP to be 4-8 inches in a layer at least 8 inches thickness and pressed

THE SOIL.

C. APPROVED EQUIVALENTS CAN BE SUBSTITUTED FOR ANY OF THE ABOVE MATERIALS.

PERIODIC INSPECTION AND REQUIRED MAINTENANCE MUST BE PROVIDED AFTER EACH RATE. EX

APPROVED; FOR PUBLIC WATER AND PUBLIC SERVER HOWARD COUNTY HEALTH DEPARTMENT APPROVED: HOWARD COUNTY DEPARTMENT CHIED, DIVISION OF COMMUNITY PLANNING 2/14/9. AND LAND DEVELOPMENT APPROVED: FOR PUBLIC WATER AND PUBLIC SEWERAGE STORM DRAINAGE SYSTEMS AND PUBLIC ROADS HOWARD COUNTY DEPARTMENT OF PUBLIC WORK

2-26-90 COUNTY COMMENTS

REVISION

SCALE: SHEET DATE:

1-2-90

9 City Maryland

de. 040.

APPLIED PHYSICS LABORATORY

THE JOHN HOPKINS UNIVERSITY

These plans for soil and sediment control meet

the requirements of the Howard Soil Conservation

These plans have been reviewed for the Howard

Soil Conservation District and meet the technical requirements for soi! and sediment

JOHNS HOPKINS ROAD HOWARD COUNTY MARYLAND APPROVED FOR THE UNIVERSITY BY: DATE: 12/29/89 TITLE: Fromp &

SEDIMENT CONTROL

NOTES